


SCHEMATIC



Rating	AC125V 1A	Mechanical Life	500,000 cycles
Withstand Voltage	AC500V 1 minute	Electrical Life	30,000 cycles
Insulation Resistance	$\geq 100M\Omega$ DC500V	Ambient Temper.Used	-25°C to +65°C
Contact Resistance	$\leq 50m\Omega$	Ambient Humidity Used	Less than 85%RH
Soldering Temper.	245 $\pm$ 5°C 3Sec.	Operating Force	110 $\pm$ 30gf



REVISION	DESCRIPTION	REVISED BY	TOLERANCES X $\pm$ 0.3	ANGLE $\frac{1}{2}^\circ$	UNIT	PART NAME	DWG NO
△					mm	DM1 SPEC DRAWING	S0235B
△			DRAWN BY 吳美玉	DESIGNED BY ERIC			
△			CHECKED BY	APPROVED BY			
△	2004.05.07 修改機械及電氣壽命					DM1-00P-110-3	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Basic / Snap Action Switches](#) category:*

*Click to view products by [Canal manufacturer](#):*

Other Similar products are found below :

[83228001](#) [01.098.1358.1](#) [602EN1-6B](#) [602EN532](#) [602EN535-RB](#) [602HE5-RB1](#) [604HE162](#) [604HE223-6B](#) [624HE17-RB](#) [6HM89](#) [6PA78-JM](#)  
[6SE1](#) [6SX1-H58](#) [70500840](#) [MBD5B1](#) [MBH2731](#) [73-316-0012](#) [79211759](#) [79211923](#) [79218589](#) [7AS12](#) [ML-1155](#) [ML-1376](#) [831010C3.0](#)  
[831060C3.TL](#) [831090C2.EL](#) [83131904](#) [84212012](#) [8AS239](#) [8HM73-3](#) [903VB1-PG](#) [914CE1-6G](#) [PL-100](#) [11SM1077-H4](#) [11SM1077-H58](#)  
[11SM1-TN107](#) [11SM405](#) [11SM703-T](#) [11SM8423-H2](#) [11SX37-T](#) [11SX48-H58](#) [11SX55-H58](#) [11SM2442-T](#) [11SM76-T](#) [11SM77-H58](#)  
[11SM77-T](#) [11SM863-T](#) [11SM866](#) [11SX47-H58](#) [A7CN-1M-1-LEFT](#)