




YAEV8C-H1



Specifications Documents Tools & Dies

Dimensional	
Tongue Angle	Straight
Length (in)	1.60
Tongue Type	Ring
Stud Size (in)	1/4
Pad Width (in)	0.46
Strip Length	7/16
Electrical	
Max Voltage Rating	600
General	
Product Description	Ring-Tongue Terminals, 8 Max. Insul.Dia.: .30" Sleeve, Color: Red, 6-8, 1.54 in L, Nylon-Insulated For Expanded Insulation, 600 Volts Max.
Other	
Installation Tooling	M8ND withN8CET-2 DieMy28-6Y35, Y29 withU8CET Die
Physical	
Type of Plating	Tin
Connector Type	Terminal
Color Code	Red
Insulation Type	Nylon
Plated (Yes or No)	Y
Approvals / Certifications	
UL Listed	Y
CSA Certified	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	Military Specified (Mil-Spec),UL486
Conductor(s)	
Aircraft Cable Size (Range)	AN 8
Copper Solid Size (Range)	N/A
Navy Cable Size (Range)	N/A
Copper Stranded (Range)	8
Other Features	
UPC	7818100395955

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminals](#) category:

Click to view products by [FCT Electronics](#) manufacturer:

Other Similar products are found below :

[HT-13-10](#) [71M-250-32-NB](#) [01-2065-1-0216](#) [00581P0075](#) [M10-10RX](#) [M10BCK](#) [60205-1](#) [604200-1](#) [60598-1-CUT-TAPE](#) [60617-1-C](#) [60873-1](#) [M14-516R/SK](#) [M14-6RSX](#) [M18-10FLX](#) [M18-8FBX](#) [M18-8R/LX](#) [M18BCK](#) [61314-6-C](#) [61-S](#) [61-SN-A](#) [62-NBM-A](#) [63-S](#) [640179-1](#) [640917-2-CUT-TAPE](#) [6501550002](#) [66107-2-C](#) [66107-4-C](#) [696683-1](#) [696834-1](#) [696861-1](#) [696931-1](#) [696999-1](#) [M8-516RK](#) [M86700006](#) [MA250DMFMX-A](#) [701-2007](#) [701-2307](#) [701-7761-03](#) [70F-110-32-PB](#) [718-N-A](#) [71M-187-20-NBL](#) [71M-250-32-NBL](#) [72F-187-20-NBL](#) [72M-250-32-NBL](#) [7310](#) [73F-250-32](#) [73F-250-32-NBL](#) [73F-250-32-NL](#) [F14-10C](#) [F-1M](#)