### **TYPES YBA-A**

#### BREAK-AWAY™ HYLUG™

Copper and Aluminum Compression Terminals


UL Listed 90° C, 600 Volts to 35 kV

The Break-Away line of Copper and Aluminum HYLUG™ terminals are designed to provide maximum field flexibility by allowing the installer (using the breakaway feature) to easily convert a two-hole terminal into a one-hole terminal to suit the application.


The Break-Away HYLUG™ line of terminals encompasses a wide range of features that offers the installer the flexibility to meet the requirements of challenging projects.


#### Features & Benefits

 Break-Away feature allows for field modification of the terminal from a two-hole design to a one-hole design while retaining UL Listing and CSA Certification



- Field modification of the terminal does not require specialized tooling or training
- Stud size is 1/2" on the first stud as well as the slotted second stud
- Slotted second stud provides built in flexibility for the terminal to conform to various bus bar dimensions. With the slotted second stud the terminal can be used on two-hole spacing ranging from 1.75" down to 1.00" for 1/2" stud size
- Narrow tongue design allows for the terminal to fit into tight spaces
- Accommodates a wide range of conductor combinations (AWG, Compact, DLO, Flex and Metric)
- Break-Away HYLUG™ line of terminals





can be installed with standard BURNDY® tooling such as PAT750XT-18V and U-Dies

 Terminals are range taking when installed with Y644 or PAT644 tooling platforms





## **Aluminum Conductor**

	Conductor Size (Concentric and Compact)	Dimensions						Installation Tooling (# of crimps)					
Catalog Number		Stud Hole Spacing	Stud Hole Size	Tongue Width	В	т	L	Dieless	MD6, MD7, MD7-34R platforms OUR840**	Y500CTHS, PAT60018V, PATMD6 platform	Y35, Y39, Y750, *Y46, PAT750, *PAT46 platforms	Color Code	Die Index
YBA25A	1/0	1" to 1.75"	1/2"	1.03"	1.05"	0.17"	4.59"	MY29 (MY29 platform tools can only be used on Code Conductor), PAT644 & Y644 platforms (1), 4-POINT® Y81K, PAT81K, Y4PC, PAT4PC platforms (2)	W241 (2) X241 (4)	W241 (2)	U25ART (1)	Tan	296
YBA26A	2/0				1.17"	0.20"	4.78"		_	_	U26ART (2)	Olive	297
YBA27A	3/0			1.04"	1.31"	0.26"	5.02"		_	_	U27ART (2)	Ruby	467
YBA28A	4/0			1.17"	1.39"	0.30"	5.19"		W660 (4) X660 (8)	W660 (4)	U28ART (2)	White	298
YBA29A	250 kcmil			1.26"	1.45"	0.33"	5.28"	PAT644 & Y644 platforms (1), 4-POINT® Y81K,	_	_	U29ART (2)	Red	324
YBA30A	300 kcmil			1.38"	1.53"	0.36"	5.64"	PAT81K, Y4PC, PAT4PC platforms (2)	_	_	U30ART (2)	Blue	470
YBA31A	350 kcmil			1.52"	1.85"	0.39"	6.07"	PAT644 & Y644 platforms (1), 4-POINT® Y81K, PAT81K, Y4PC, PAT4PC	_	_	U31ART (2)	Brown	299
YBA32A	400 kcmil			1.62"	2.26"	0.43"	6.15"		_	_	U32ART (4)	Green	472
YBA34A	500 kcmil				2.34"	0.46"	6.80"		_	_	U34ART (4)	Pink	300
YBA36A	600 kcmil			1.31"	2.47"	0.52"	7.09"		_	_	U36ART (4)	Black	473
YBA39A	700 & 750 kcmil			1.62"	2.46"	0.43"	7.07"	platforms (4)	_	_	U39ART-2 (2)	Yellow	936
YBA42A	900 kcmil AL 600 kcmil CU			1.62"	2.46"	0.43"	7.07"	Y644MBH (2) Y644HSXT (2) PAT644XT -18V (2)	_	_	U42ART (4)^	Gray	303
YBA44A	1000 kcmil			1.65"	2.74"	0.55"	7.76"	Y644MBH (1)	_	_	P44ART† (4)	Brown	302

<sup>†</sup> Can only be crimped with PAT46 or Y46 platform tools using the P44ART die.

<sup>\*</sup> Y46 and PAT46 platforms require PUADP-1 adaptor to use U dies

<sup>\*\*</sup> OUR840 can use X-style dies only.

A U die for 900 AL only

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Terminals category:

Click to view products by FCT Electronics manufacturer:

Other Similar products are found below:

HT-13-10 71M-250-32-NB 01-2065-1-0216 00581P0075 M10-10RX M10BCK 60205-1 604200-1 60598-1-CUT-TAPE 60617-1-C 60873
1 M14-516R/SK M14-6RSX M18-10FLX M18-8FBX M18-8R/LX M18BCK 61314-6-C 61-S 61-SN-A 62-NBM-A 63-S 640179-1

640917-2-CUT-TAPE 6501550002 66107-2-C 696683-1 696834-1 696861-1 696931-1 696999-1 M8-516RK M86700006

MA250DMFMX-A 701-2007 701-2307 701-7761-03 70F-110-32-PB 718-N-A 71M-187-20-NBL 71M-250-32-NBL 72F-187-20-NBL

72M-250-32-NBL 7310 73F-250-32 73F-250-32-NBL 73F-250-32-NL F14-10C F-1M 751-250