



Recommend PCB Layout
Tolerance=±0.05

- NOTE:**
1. Materials:
 - 1.1 Base: Thermoplastic, UL94 V-0, Color of black.
 - Temp. Range: -40°C to +105°C.
 - 1.2 Positive & Negative Contacts: Copper Alloy.
 2. Specification:
 - 2.1 Dielectric Withstanding Voltage: AC 500V AC.
 - 2.2 Insulation Resistance: 1000MΩ min.
 - 2.3 Contact Resistance: 100mΩ Max.
 3. Part Number Code:
 - DS1092-04 - X X X X

- Housing material: P: PA66
- Contact plating: 6: Tin
- Housing color: B: Black

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
C	MATERIAL CHANGE	JLZ 04/24/15'	~	
B	DIM. CHANGE	JLZ 12/11/14'	~	LJC 12/11/14'
A	NEW RELEASE	YCH 08/07/12'	~	LJC 08/07/12'

GENERAL TOLERANCE		X. ±0.60		X. ±0.38		.XX ±0.25	
ANGLE TOLERANCE		X. ±5.		.X ±3.		.XX ±2.	
DRAWING TYPE		CUSTOMER					
SCALE		1:1		SHEET		10F1	
DRAWING NO.		C-DS1092-04-XXX-C					

UNITS	mm
SHEET SIZE	A4
SERIES	DS1092-04 Series
2032 Lithium Coin Cell Battery Holders Horizontal Insert type	
PROJECTION	
TITLE	

晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO., LTD

DRAWING NO. C-DS1092-04-XXX-C

SCALE 1:1 SHEET 10F1

DRAWING TYPE CUSTOMER

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Coin Cell Battery Holders](#) category:

Click to view products by [Connfly](#) manufacturer:

Other Similar products are found below :

[3035](#) [1026](#) [1059](#) [1060](#) [1063](#) [1065](#) [1068](#) [1093](#) [D2](#) [D3](#) [46400000](#) [BC-0403](#) [BH-121-1B](#) [BH-1/2AA-2A](#) [BH-131A](#) [BH-3101A](#) [BH-3103B](#)
[BH-311-1A](#) [BH-311-1D](#) [BH-321-1B](#) [BH-321-1D](#) [BH-331-3D](#) [BH-331P](#) [BH-333A](#) [BH-341-1P](#) [BH-342-1A](#) [BH-351A](#) [BH-383A](#) [BH-421A](#)
[BH-422A](#) [BH-425A](#) [BH-431-1B](#) [BH-463A](#) [BH-511A](#) [BHC-18650-1P](#) [46300000](#) [46600000](#) [1058TR](#) [SBH-321-1AS](#) [SBH-331A](#) [SBH-341-1A](#) [SBH-341-AS](#) [SBH-421-1A](#) [SBH-431-1AS](#) [SBH-441A](#) [SBH-9VA](#) [BH-121-1A](#) [BHC-18650-1A](#) [SBH-421-1AS](#) [SBH-441AS](#)