



**NOTE:**

- 1.1 Base: Thermoplastic, UL94 V-0, Color of black.
- Temp. Range: -40°C to +105°C.
- 1.2 Positive & Negative Contacts: Copper Alloy.
2. Specification:
  - 2.1 Dielectric Withstanding Voltage: AC 500V AC.
  - 2.2 Insulation Resistance: 1000M $\Omega$  min.
  - 2.3 Contact Resistance: 100m $\Omega$  Max.
3. Part Number Code: DS1092-11 - X X X X

Housing material: S: PPS  
 Contact plating: 8: Gold Flash  
 Housing color: N: Brown

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 08/07/12'	~	LJC 08/07/12'
B	DRAWING ARRANGEMENT	JLZ 10/30/15'	~	

GENERAL TOLERANCE		X. $\pm 0.60$		X. $\pm 0.38$		X. $\pm 0.25$	
ANGLE TOLERANCE		X. $\pm 5$		X. $\pm 3$		XX $\pm 2$	
DRAWING TYPE		CUSTOMER					
SCALE		1:1		SHEET		10F1	
DRAWING NO.		C-DS1092-11-XXX-B					

UNITS	mm
SHEET SIZE	A4
SERIES	DS1092-11 Series
2032 Lithium Coin Cell Battery Holders Horizontal Insert SMT type	
PROJECTION	
TITLE	

CONNELY ELECTRONIC CO., LTD		晨翔电子有限公司
-----------------------------	--	----------

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Coin Cell Battery Holders](#) category:*

*Click to view products by [Connfly](#) manufacturer:*

Other Similar products are found below :

[3035](#) [1026](#) [1059](#) [1060](#) [1063](#) [1065](#) [1068](#) [1093](#) [D2](#) [D3](#) [46400000](#) [BC-0403](#) [BH-121-1B](#) [BH-1/2AA-2A](#) [BH-131A](#) [BH-3101A](#) [BH-3103B](#)  
[BH-311-1A](#) [BH-311-1D](#) [BH-321-1B](#) [BH-321-1D](#) [BH-331-3D](#) [BH-331P](#) [BH-333A](#) [BH-341-1P](#) [BH-342-1A](#) [BH-351A](#) [BH-383A](#) [BH-421A](#)  
[BH-422A](#) [BH-425A](#) [BH-431-1B](#) [BH-463A](#) [BH-511A](#) [BHC-18650-1P](#) [46300000](#) [46600000](#) [1058TR](#) [SBH-321-1AS](#) [SBH-331A](#) [SBH-341-1A](#) [SBH-341-AS](#) [SBH-421-1A](#) [SBH-431-1AS](#) [SBH-441A](#) [SBH-9VA](#) [BH-121-1A](#) [BHC-18650-1A](#) [SBH-421-1AS](#) [SBH-441AS](#)