



NOTE:

1. Materials:
 - 1.1 Base: Thermoplastic, UL94 V-0, Color of black.
 - Temp. Range: -40°C to +105°C.
 - 1.2 Positive & Negative Contacts: Copper Alloy.
2. Specification:
 - 2.1 Dielectric Withstanding Voltage: AC 500V AC.
 - 2.2 Insulation Resistance: 1000MΩ min.
 - 2.3 Contact Resistance: 100mΩ Max.
3. Part Number Code:
 - DS1092-14 - X X X X

Housing material: P: PBT
 Contact plating: 6: Tin
 Housing color: B: Black

REV.	A	NEW RELEASE	YCH 08/07/12'		
DESCRIPTION		DRAWN			
		CHECKED			
APPROVED					

GENERAL TOLERANCE		X. ±0.60	X. ±0.38	.XX ±0.25
ANGLE TOLERANCE		±5.	±3.	±2.
DRAWING TYPE		CUSTOMER		
SCALE		1:1	SHEET	10F1
DRAWING NO.		C-DS1092-14-XXX-A		
COMPANY				
PROJECTION				
UNITS		mm		
SHEET SIZE		A4		
SERIES		DS1092-14 Series		
TITLE		2032 Lithium Coin Cell Battery Holders Horizontal Insert type		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Coin Cell Battery Holders](#) category:

Click to view products by [Connfly](#) manufacturer:

Other Similar products are found below :

[3035](#) [1026](#) [1059](#) [1060](#) [1063](#) [1065](#) [1068](#) [1093](#) [D2](#) [D3](#) [46400000](#) [BC-0403](#) [BH-121-1B](#) [BH-1/2AA-2A](#) [BH-131A](#) [BH-3101A](#) [BH-3103B](#)
[BH-311-1A](#) [BH-311-1D](#) [BH-321-1B](#) [BH-321-1D](#) [BH-331-3D](#) [BH-331P](#) [BH-333A](#) [BH-341-1P](#) [BH-342-1A](#) [BH-351A](#) [BH-383A](#) [BH-421A](#)
[BH-422A](#) [BH-425A](#) [BH-431-1B](#) [BH-463A](#) [BH-511A](#) [BHC-18650-1P](#) [46300000](#) [46600000](#) [1058TR](#) [SBH-321-1AS](#) [SBH-331A](#) [SBH-341-](#)
[1A](#) [SBH-341-AS](#) [SBH-421-1A](#) [SBH-431-1AS](#) [SBH-441A](#) [SBH-9VA](#) [BH-121-1A](#) [BHC-18650-1A](#) [SBH-421-1AS](#) [SBH-441AS](#)