



DRAWING NO. C-DS1106-XXX		DRAWING TYPE CUSTOMER	
SCALE 1:1	SHEET 1 OF 1	GENERAL TOLERANCE X. ±0.60 X. ±0.38 X. ±0.25	
DRAWING NO. C-DS1106-XXX		ANGLE TOLERANCE X. ±5° X. ±3° X. ±2°	
SHEET SIZE A4		UNITS mm	
SERIES DS1106		PROJECTION	
TITLE		IEEE 1394 6PIN MALE SOLDER TYPE	

REV. A	DESCRIPTION NEW RELEASE	DRAWN HP 22/06/05	CHECKED	APPROVED

NOTES:
 1. SPECIFICATIONS
 . Contact Resistance: 50mΩ max
 . Insulator Resistance: 100MΩ min.
 . Current Rating: 1.5A per pin max.
 . Rated Voltage: 30V DC
 . Dielectric withstanding voltage: AC 100V For 1 minute
 . Contact: Copper Alloy
 . Housing: Thermoplastic(UL 94V-0)
 2. PRODUCT NUMBER CODE:
 DS1106 - X X X
 X Contact plating
 0: Selective gold flash
 C: Selective 3u" gold
 Shell plating
 N: Nickel
 6: Tin
 Color of housing
 B: Black

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Cables / IEEE 1394 Cables](#) category:

Click to view products by [Connfly](#) manufacturer:

Other Similar products are found below :

[68768-0173](#) [FNY-W6003-01](#) [88764-0800](#) [13805532](#) [148700-1](#) [17-200621](#) [17-250051P](#) [954](#) [AC102012-2](#) [IP-USB1\(C10\)S-RW](#)
[CABLE/RTP/USB/DT](#) [0847290003](#) [10115240-12200LF](#) [RS232-GTD](#) [USBFTVX2SA2N03A](#) [USBFTV2SA2N03A](#) [1689404-1](#) [FTP-](#)
[629Y401](#) [FTP-628Y402](#) [943301-001](#) [FNY-W6022](#) [FNY-W6003-03](#) [1310-1015-05](#) [1310-1019-04](#) [0887283402](#) [UA-30AMFM-SL7B02](#) [UA-](#)
[30AMFM-SL7B01](#) [UA-30AFM-LD7B03](#) [UA-30AMFM-SL7B03](#) [USBAPSCC7202A](#) [UES-1001A160](#) [UES-1003A160](#)
[USBFTVX7SA2N20A](#) [USBFTVX2SA2N20A](#) [USBFTV2PEMSA2N10A](#) [FTP-629Y602](#) [USBCAMCM100](#) [USB A/F*2 to 2.54 2*5P-SH](#)
[L=400mm](#) [EP-CBUSB10P2FLT](#) [1310-1033-01](#) [1310-1037-04](#) [ASR-USB](#) [68784-0075](#) [17-241361](#) [17-230471](#) [217B-BC02](#) [USB-29](#) [19800-](#)
[010500-200-RS](#) [USB+MINI DIN 6P WITH BKT](#) [088738-8100](#)