


## Single Output, 3.3W to 50W Power Supplies

### Features

- ◆ Universal Input (85 - 265VAC)
- ◆ Input transient protected
- ◆ 2 year warranty
- ◆ High quality design
- ◆ Peak Power capability



### Key Market Segments & Applications



Specifications				
Model		ZWS5 ZWS10	ZWS15 ZWS30	ZWS50
AC Input Voltage range	-	85-265VAC (47-440Hz)		
DC Input Voltage range	-	110 - 330VDC		
Inrush Current (100/200VAC) (1)	A	15 / 30		
Temperature Coefficient	-	<0.02%/°C		
Overcurrent Protection (2)	-	~125%		
Overvoltage Protection	V	~140% diode clamp		~115 - 130%, manual reset
Hold Up Time (Typ) @ 100VAC	ms	17		
Remote Sense	-	None		
Operating Temperature	°C	(open frame) -10°C~+60°C, derate linearly to 70% load from 50°C~60°C		
Operating Temperature	°C	(with cover) Additional derating applies, please consult Installation Manual		
Storage Temperature	°C	-30 to +85°C		
Humidity (non condensing)	-	10 - 95% RH		
Cooling	-	Convection		
Withstand Voltage	-	Input to Ground 2kVAC (20mA), Input to Output 3kVAC (20mA), Output to Ground 500VAC (100mA) for 1 min.		
Isolation Resistance	-	>100M at 25°C & 70%RH, Output to Ground 500VDC		
Vibration (non operating)	-	10 - 55Hz (1 minute sweep), 19.6m/s <sup>2</sup> constant X, Y, Z 1 hour		
Shock	-	< 196.1 m/s <sup>2</sup>		
Safety Agency Approvals	-	UL60950-1, CSA60950-1, EN60950-1, CE Mark		
Conducted & Radiated	EM	EN55022-B, FCC Class B, VCCI-B		
Recommended EMI Filter	-	RSEL-20R5W	RSEL-2001W RSEL-2002W	RSEL-2002W
Weight (Typ)	g	120/120	140/270	370
Size (WxHxD)	mm	See Outline Drawings		
Warranty	yrs	2 years		

Notes:

- (1) 25°C ambient (cold start)
- (2) Avoid prolonged operation in overload

## 2 Output Module Codes


Model	Voltage	Adjust Range	Max Curr. A	Peak Curr. A	Load Reg mV	Line Reg mV	Ripple Noise mV	Eff. %
ZWS5-3	3.3V	2.97-3.63	1	1.2	40	20	120	62
ZWS10-3	3.3V	2.97-3.63	2	2.4	40	20	120	62
ZWS15-3	3.3V	2.97-3.63	3	3.6	40	20	120	63
ZWS30-3	3.3V	2.97-3.63	6	7.2	40	20	120	70
ZWS50-3	3.3V	2.97-3.63	10	12	40	20	120	73
ZWS5-5	5V	4.5-5.5	1	1.2	40	20	120	67
ZWS10-5	5V	4.5-5.5	2	2.4	40	20	120	70
ZWS15-5	5V	4.5-5.5	3	3.6	40	20	120	71
ZWS30-5	5V	4.5-5.5	6	7.2	40	20	120	75
ZWS50-5	5V	4.5-5.5	10	12	40	20	120	77
ZWS5-12	12V	10.8-13.2	0.42	0.51	96	48	150	68
ZWS10-12	12V	10.8-13.2	0.85	1.02	96	48	150	70
ZWS15-12	12V	10.8-13.2	1.25	1.5	96	48	150	71
ZWS30-12	12V	10.8-13.2	2.5	3	96	48	150	77
ZWS50-12	12V	10.8-13.2	4.3	5.16	96	48	150	80
ZWS5-15	15V	13.5-16.5	0.34	0.41	120	60	150	68
ZWS10-15	15V	13.5-16.5	0.7	0.84	120	60	150	71
ZWS15-15	15V	13.5-16.5	1	1.2	120	60	150	71
ZWS30-15	15V	13.5-16.5	2	2.4	120	60	150	77
ZWS50-15	15V	13.5-16.5	3.5	4.2	120	60	150	81
ZWS5-24	24V	21.6-26.4	0.22	0.27	150	96	200	70
ZWS10-24	24V	21.6-26.4	0.45	0.54	150	96	200	71
ZWS15-24	24V	21.6-26.4	0.65	0.78	150	96	200	71
ZWS30-24	24V	21.6-26.4	1.3	1.56	150	96	200	78
ZWS50-24	24V	21.6-26.4	2.1	2.52	150	96	200	82
ZWS30-36	36V	32.4-39.6	0.9	1.08	240	144	300	78
ZWS50-36	36V	32.4-39.6	1.4	1.68	240	144	300	82
ZWS30-48	48V	43.2-52.8	0.7	0.84	300	192	400	78
ZWS50-48	48V	43.2-52.8	1.1	1.32	300	192	400	82

Note for Peak Current: For 10s maximum, 35% duty cycle, average power not to exceed maximum ratings.

## Options

Suffix	Description
-	Molex Terminals
/A	Cover option
/J	JST Connectors*
/JA	JST Connectors & Cover
Note:	* Recommended for new designs

## ZWS Outline Drawing



### DIMENSIONS:

MODEL	A	B	C	D	E	F	G	H	J	K	L
ZWS5	3.86	1.77	3.580	1.500	-	-	.14	.83	1.05	.54	-
	(98.0)	(44.9)	(90.9)	(38.1)			(3.5)	(21.0)	(26.6)	(13.7)	
ZWS10	4.14	1.97	3.860	1.690	-	-	.14	.83	.99	.67	-
	(105.1)	(50.0)	(98.0)	(42.9)			(3.5)	(21.0)	(25.1)	(18.4)	
ZWS15	4.93	1.97	4.650	1.690	-	-	.14	.83	1.04	.57	-
	(125.2)	(50.0)	(118.1)	(42.9)			(3.5)	(21.0)	(25.0)	(14.4)	
ZWS30	5.24	2.17	4.850	1.770	-	-	.20	1.02	.20	1.16	-
	(133.0)	(55.1)	(123.1)	(45.0)			(5.0)	(25.9)	(31.0)	(40.2)	
ZWS50	7.68	2.17	7.290	1.770	-	-	.20	1.02	1.32	.72	-
	(195.0)	(55.1)	(185.1)	(45.0)			(5.0)	(25.9)	(33.5)	(18.2)	

## Other Industrial Products

ZWS-AF	50W to 150W Active PFC
ZWD/ZWQ	100W to 440W Single & multiple output
SC	30W to 120W Single, dual, & triple output
HWS	15W to 1800W Single output enclosed

For Additional Information, please visit  
[us.tdk-lambda.com/lp/products/zws-series.htm](http://us.tdk-lambda.com/lp/products/zws-series.htm)



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Switching Power Supplies](#) category:*

*Click to view products by [TDK-Lambda](#) manufacturer:*

Other Similar products are found below :

[70841011](#) [73-551-0005](#) [AAD600S-4-OP](#) [R22095](#) [HWS50A-5/RA](#) [KD0204](#) [9021](#) [S-15F-12](#) [LDIN100150](#) [LPM000-BBAR-01](#) [LPX17S-C](#)  
[EVS57-10R6/R](#) [FDC40-24S12](#) [FRV7000G](#) [22929](#) [CQM1IA121](#) [40370121900](#) [VI-PU22-EXX](#) [40370121910](#) [LDIN5075](#) [432703037161](#)  
[WRB01X-U](#) [LPX140-C](#) [08-30466-1040G](#) [09-160CFG](#) [70841004](#) [70841025](#) [VPX3000-CBL-DC](#) [LPM000-BBAR-05](#) [LPM000-BBAR-08](#)  
[LPM124-OUTA1-48](#) [LPM000-BBAR-07](#) [LPM109-OUTA1-10](#) [LPM616-CHAS](#) [08-30466-1055G](#) [08-30466-2175G](#) [DMB-EWG](#) [TVQF-](#)  
[1219-18S](#) [6504-226-2101](#) [CQM1IPS01](#) [XPFM201A+](#) [MAP80-4000G](#) [LFP300F-24-TY](#) [SMP21-L20-DC24V-5A](#) [VI-MUL-ES](#) [08-30466-](#)  
[0065G](#) [CME240P-24](#) [VI-RU031-EWWX](#) [08-30466-0028G](#) [S82Y-TS01](#)