

Spec-Kon® cable ties

The right cable tie for the right application

Characteristics


A complete range of cable ties for control panel applications.

- Available in different packaging quantities to respond to the user's need
- Available in different lengths and tensile strengths
- Sophisticated, ergonomic fastening installation tools and easy to use cable ties dispenser

Technical Information

Material	Polyamide 6.6
Temperature range	-40°C to +85°C
Colour	Natural
Flammability rating	UL 94 V-2
Other properties	Halogen free, Silicone free

Product Ref.	Length L [mm]	Width W [mm]	Min. tensile strength [N]	Bundle Dia. from... to... [mm]	Quantity [pieces]	Bags/ Carton
SKT100-80-100	100	2,5	80	1.5 - 22	100	550
SKT100-80	100	2,5	80	1.5 - 22	1000	70
SKT140-80-100	140	2,5	80	1.5 - 33	100	450
SKT140-80	140	2,5	80	1.5 - 33	1000	55
SKT160-80-100	160	2,5	80	1.5 - 40	100	400
SKT160-80	160	2,5	80	1.5 - 40	1000	45
SKT200-80-100	200	2,5	80	1.5 - 53	100	300
SKT200-80	200	2,5	80	1.5 - 53	1000	32
SKT140-180-100	140	3,6	180	2 - 33	100	300
SKT140-180	140	3,6	180	2 - 33	1000	30
SKT200-180-100	200	3,6	180	2 - 53	100	200
SKT200-180	200	3,6	180	2 - 53	1000	22
SKT300-180-100	300	3,6	180	2 - 76	100	120
SKT300-180	300	3,6	180	2 - 76	1000	12
SKT370-180-100	370	3,6	180	2 - 102	100	120
SKT370-180	370	3,6	180	2 - 102	1000	12
SKT188-220-100	188	4,8	220	3 - 46	100	160
SKT188-220	188	4,8	220	3 - 46	1000	16
SKT250-220-100	250	4,8	220	3 - 60	100	120
SKT250-220	250	4,8	220	3 - 60	1000	12
SKT300-220-100	300	4,8	220	3 - 76	100	80
SKT300-220	300	4,8	220	3 - 76	1000	8
SKT370-220-100	370	4,8	220	3 - 102	100	70
SKT370-220	370	4,8	220	3 - 102	1000	7
SKT300-540-100	300	7,6	540	7 - 76	100	50
SKT300-540	300	7,6	540	7 - 76	500	10
SKT370-540-100	370	7,6	540	7 - 102	100	40
SKT370-540	370	7,6	540	7 - 102	500	8
SKT750-540-50	750	7,6	540	7 - #N/A	50	30
SKT776-780-50	776	9,0	780	7 - 228	50	30
SKT912-780-50	912	9,0	780	7 - 263	50	10



Spec-Kon® cable ties

The right cable tie for the right application

Characteristics


A complete range of cable ties for control panel applications.

- Available in different packaging quantities to respond to the user's need
- Available in different lengths and tensile strengths
- Sophisticated, ergonomic fastening installation tools and easy to use cable ties dispenser

Technical Information

Material	Polyamide 6.6
Temperature range	-40°C to +85°C
Colour	UV-resistant black
Flammability rating	UL 94 V-2
Other properties	UV-resistant, Halogen free, Silicone free

Product Ref.	Length L	Width W	Min. tensile strength	Bundle Dia. from... to...	Quantity	Bags/ Carton
	[mm]	[mm]	[N]	[mm]	[pieces]	
SKT100-80X-100	100	2,5	80	1,5 - 22	100	550
SKT100-80X	100	2,5	80	1,5 - 22	1000	70
SKT140-80X-100	140	2,5	80	1,5 - 33	100	450
SKT140-80X	140	2,5	80	1,5 - 33	1000	55
SKT160-80X-100	160	2,5	80	1,5 - 40	100	400
SKT160-80X	160	2,5	80	1,5 - 40	1000	45
SKT200-80X-100	200	2,5	80	1,5 - 53	100	300
SKT200-80X	200	2,5	80	1,5 - 53	1000	32
SKT140-180X-100	140	3,6	180	2 - 33	100	300
SKT140-180X	140	3,6	180	2 - 33	1000	30
SKT200-180X-100	200	3,6	180	2 - 53	100	200
SKT200-180X	200	3,6	180	2 - 53	1000	22
SKT300-180X-100	300	3,6	180	2 - 76	100	120
SKT300-180X	300	3,6	180	2 - 76	1000	12
SKT370-180X-100	370	3,6	180	2 - 102	100	120
SKT370-180X	370	3,6	180	2 - 102	1000	12
SKT188-220X-100	188	4,8	220	3 - 46	100	160
SKT188-220X	188	4,8	220	3 - 46	1000	16
SKT250-220X-100	250	4,8	220	3 - 60	100	120
SKT250-220X	250	4,8	220	3 - 60	1000	12
SKT300-220X-100	300	4,8	220	3 - 76	100	80
SKT300-220X	300	4,8	220	3 - 76	1000	8
SKT300-540X-100	300	7,6	540	7 - 76	100	50
SKT300-540X	300	7,6	540	7 - 76	500	10
SKT370-540X-100	370	7,6	540	7 - 102	100	40
SKT370-540X	370	7,6	540	7 - 102	500	8
SKT750-540X-50	750	7,6	540	7 - #N/A	50	30
SKT776-780X-50	776	9,0	780	7 - 228	50	30
SKT912-780X-50	912	9,0	780	7 - 263	50	10



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cable Ties](#) category:

Click to view products by [ABB](#) manufacturer:

Other Similar products are found below :

[20093-0](#) [SJ-3463](#) [SJ3518FR-1x50](#) [SJ3526N-Beige-2"x50yd](#) [SJ3526N BLACK 58" X 50YD](#) [SJ3571](#) [SJ-3571-1"x50yd-Black](#) [20113-0](#)
[T56137](#) [3-350087-0](#) [CTB75X75BKA-C](#) [3722](#) [561-B110120](#) [561-EZAB580T](#) [561-EZS375B40](#) [561-N3510](#) [561-TA250125](#) [08350-0](#) [08443-0](#)
[08600-0](#) [10035-0](#) [10036-0](#) [10037-0](#) [10325-0](#) [10362-0](#) [10606-0](#) [561-EZ250](#) [561-EZ500](#) [561-EZ625](#) [561-EZ750](#) [561-TA00600](#) [SJ3519FR](#)
[BLACK 1X50](#) [SJ3527N-Beige-2"x50yd](#) [SJ3527N-LOOP-BLACK-1](#) [SJ3572-2"x50yd-Black](#) [157-00039](#) [3719](#) [SJ-3401 BLACK 1"](#) [08445-0](#)
[08582-0](#) [08386-0](#) [10431-0](#) [08359-0](#) [10056-0](#) [10620-0](#) [10345-0](#) [10344-0](#) [08416-0](#) [08384-0](#) [08401-0](#)