

RP series, RPH series, high-power metal film chip resistors

SSM
THIN FILM TECHNOLOGY



Resistors with high power in small size are realized as 1/3W for 2.0×1.25mm(0805) size, 1/5W for 1.6×0.8mm(0603) size and 1/6W for 1.0×0.5mm(0402) size.

A tight resistance tolerance at $\pm 1\%$ is achieved.

NEW RPH1608 resistors with more high power are realized as 1/4W for 1.6×0.8mm(0603) size.


RoHS compliant

Completely lead free



SPECIFICATIONS

Mechanical



Dimension (Inch Size)	RP1005 (0402)		RP1608 (0603) RPH1608 $R \leq 0.16\Omega$	RP2012 (0805)
	Single side structure	Double sides structure $R \leq 0.16\Omega$		
L		1.0±0.05	1.6±0.20	2.0±0.2
W		0.5±0.05	0.8±0.10	1.25±0.2
A		0.15±0.10	0.2±0.15	0.4±0.2
B	0.25±0.10	0.15±0.10	0.25±0.20	0.4±0.2
T	0.35±0.10	0.35±0.15/-0.10	0.45±0.10	0.4±0.1

(unit : mm)

Electrical

Type	RP1005	RP1608	RPH1608 NEW	RP2012
Power	1/6W	1/5W	1/4W	1/3W
Tolerance % (code)	± 1 (F), ± 2 (G), ± 5 (J)	± 1 (F), ± 2 (G), ± 5 (J)	± 1 (F), ± 2 (G), ± 5 (J)	± 1 (F), ± 2 (G), ± 5 (J)
Resistance Range (Ω)	0.1~47	0.1~68	0.01~0.082	0.1~10
TCR ppm /°C (code)	0 ~+200 (S)	0 ~+200 (S)	0 ~+350 (T)	0 ~+350 (T)
Resistance Value	E-24	E-24	E-12	E-24
Max Operating Voltage for an element	$\sqrt{P \cdot R}$	$\sqrt{P \cdot R}$	$\sqrt{P \cdot R}$	$\sqrt{P \cdot R}$
Operating Temp. Rating	-40~125°C	-40~125°C	-40~125°C	-40~125°C
Package	10,000pcs/reel	5,000pcs/reel	5,000pcs/reel	5,000pcs/reel

· Please contact us for specific resistance to surge voltage.

· Please contact us for 0.1Ω or lower(TCR 0 - +350ppm/°C) resistance value in RP1005,RP1608,RP2012.

PART NUMBER

RP 1608 S - 102 - F

Resistance Tolerance

Resistance

Temperature Coefficient of Resistance

Dimensions

Part Code

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Current Sense Resistors - SMD category:

Click to view products by Susumu manufacturer:

Other Similar products are found below :

[5112 65709-330JE](#) [PF2512FKF7W0R007L](#) [PR2512FKF7W0R003L](#) [PR2512FKF7W0R005L](#) [RCWL0603R500JNEA](#) [ERJ-3BQF1R1V](#) [ERJ-L14UJ42MU](#) [2-2176088-5](#) [PF2512FKF7W0R006L](#) [PF2512FKF7W0R033L](#) [2-2176089-4](#) [CD2015FC-0.10-1%](#) [PR2512FKF7W0R004L](#) [CGSSL1R01J](#) [CGSSL1R047J](#) [RC1005F124CS](#) [RCWE2512R110FKEA](#) [RCWL0805R330JNEA](#) [RL73H3AR47FTE](#) [RL73K3AR56JTDF](#) [RL7520WT-R001-F](#) [RL7520WT-R009-G](#) [RL7520WT-R020-F](#) [RLP73N1ER43JTD](#) [TL3AR01FTDG](#) [TLR3A20DR0005FTDG](#) [LRC-LR2512LF-01-R820J](#) [ERJ-3BQF4R3V](#) [ERJ-L14UF68MU](#) [TLR3A20DR001FTDG](#) [TLR3A30ER0005FTDG](#) [WR06X104JGLJ](#) [RLP73K1ER82JTD](#) [TL2BR01F](#) [TLR3A20DR01FTDG](#) [WSR3R0600FEA32](#) [ERJ-14BQF1R6U](#) [ERJ-14BQJR30U](#) [SP1220RJT](#) [SP1R12J](#) [ERJ-14BQF6R2U](#) [RL7520WT-R039-G](#) [PF1206FRF7W0R02L](#) [RL7520WT-R002-F](#) [RL7520WT-R047-F](#) [RLP73N2BR068FTDF](#) [RL7520WT-R005-F](#) [RCWE2512R220FKEA](#) [RCWE120625L0FMEA](#)