



# Series 800 Mighty Mouse UN Mating Thread Plug

## 800-006 Thru 800-009 Ordering Information



**Glenair's Smallest Mighty Mouse Connector** has compact size and rugged design for hostile environments. UN mating thread. Connector shells are machined aluminum or stainless steel. Supplied with crimp contacts, packaged separately. Terminate contacts with standard M22520 tools. Metal clips inside the connector body lock contact into place. Contacts are removable. Fluorosilicone seals and rear grommet protect connector from water ingress. Choose hex or knurled coupling nut. Terminate cable shield directly to connector body with Band-Master™ ATS strap, or choose rear accessory thread to attach optional cable clamp or backshell. Available in shell sizes 5 through 12 in 36 contact arrangements.

C

How To Order						
<b>Sample Part Number</b>	<b>800-006</b>	<b>-06</b>	<b>M</b>	<b>6-7</b>	<b>P</b>	<b>N</b>
<b>Series (See Table I)</b>	<p><b>800-006</b> = Hex Plug with Banding Platform  <b>800-007</b> = Hex Plug with Accessory Thread  <b>800-008</b> = Plug with Band Platform  <b>800-009</b> = Plug with Accessory Thread</p>					
<b>Shell Style</b>	<p><b>-06</b> = Standard Coupling Nut  <b>-16</b> = Coupling Nut with Anti-Decoupling Wave Spring</p>					
<b>Shell Material and Finish</b>	<p><b>C</b> = Aluminum / Black Anodize (Non-Conductive) RoHS Compliant  <b>M</b> = Aluminum / Electroless Nickel RoHS Compliant  <b>NF</b> = Aluminum / Cadmium with Olive Drab Chromate  <b>ZNU</b> = Aluminum / Zinc-Nickel with Black Chromate  <b>MT</b> = Aluminum / Nickel-PTFE RoHS Compliant  <b>Z1</b> = Stainless Steel / Passivated RoHS Compliant</p>					
<b>Shell Size - Insert Arrangement</b>	See Contact Arrangements page C-2					
<b>Contact Type</b>	<p><b>Connector supplied with crimp contacts</b></p> <p><b>P</b> = Pin <b>S</b> = Socket</p>	<p><b>Connector supplied without contacts</b></p> <p><b>A</b> = Pin Connector <b>B</b> = Socket Connector</p>	<p><b>Connector supplied with 30 AWG crimp contacts</b></p> <p><b>G</b> = Pin <b>H</b> = Socket</p>			
<b>Shell Key Positions (See Table II)</b>	<b>N</b> = Normal <b>X</b> = Pos. X <b>Y</b> = Pos. Y <b>Z</b> = Pos. Z					

Table I: Series			
<b>800-006</b> Hex Plug with Banding Platform	<b>800-007</b> Hex Plug with Accessory Thread	<b>800-008</b> Knurled Round Plug with Band Platform	<b>800-009</b> Knurled Round Plug with Accessory Thread

Dimensions in Inches (millimeters) are subject to change without notice.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Circular MIL Spec Connector](#) category:*

*Click to view products by [Glenair](#) manufacturer:*

Other Similar products are found below :

[89075GULPR](#) [0025-262-542](#) [0025-264-3014](#) [58-570121-04S](#) [0134-213-1208](#) [0134-213-2209](#) [0025-258-000](#) [60-042022-07P](#) [60-042022-19P](#)  
[60-042022-23P](#) [60-042217-10P](#) [60-042217-11P](#) [0114-201-1278](#) [012-0467-000](#) [602GB06EG24-61SN](#) [0134-201-1207](#) [0134-213-1006](#) [6104-](#)  
[207-2302](#) [6104-208-1902](#) [61-168211-04P](#) [61-168617-10P](#) [6131-202-19149P](#) [6131-204-21149P](#) [6131-208-13149P](#) [6131-209-17149P](#) [6131-](#)  
[210-11149P](#) [6131-211-19149P](#) [6131-216-19149P](#) [6131-259-21149P](#) [6131-259-23149P](#) [6131-265-17149P](#) [6131-265-19149P](#) [CS3100A18-1P-](#)  
[472](#) [CS3100A-36-77P](#) [CS3101A-16-55P](#) [CS3102A-10SL-55P](#) [CS3102A-14S-58P](#) [CS3102A-18-1P116](#) [CS3102A-32-17P](#) [CS3102A32-25S](#)  
[CS3102C18-4P-472](#) [CS3106A10SL3S004](#) [CS3106A-18-73S](#) [CS3108A-14S-52S](#) [CS3108A-28-51S](#) [6162-233-1277](#) [6162-324-1231](#)  
[M243082296Z](#) [M2884010AC1S1](#) [CT0-24-10SC](#)