

Current - Maximum per Contact

Grounding to PCB

This document was generated on 02/05/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

	432498925		\frown
Status: A	ctive		
Overview: M	odular Jacks and Plugs		
		e, Low Profile, 8/8, Panel Stops	<i>E</i> /
•			
Documents:			
<u>3D Model</u>		Product Specification PSX-43249 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
Agency Certification			
CSA		LR19980	Series image - Reference only
UL		E107635	
A 1			EU ELV
General		· · · · · · · · · · ·	Not Relevant
Product Family		Modular Jacks/Plugs	
Series		<u>43249</u>	EU RoHS China RoHS
Component Type		PCB Jack	Compliant
Magnetic		No	REACH SVHC
Overview		Modular Jacks and Plugs	Contains SVHC(2014
Performance Category		3, 4	December 17): No
Power over Ethernet (PoE	Ξ)	N/A	Halogen-Free
Product Name		RJ45	<u>Status</u>
UPC		800756395494	Not Low-Halogen
			Need more information on product
Physical			environmental compliance?
Boot Color		N/A	
Color - Resin		Black	Email productcompliance@molex.com
Durability (mating cycles r	max)	500	Please visit the <u>Contact Us</u> section for an
Flammability		94V-0	non-product compliance questions.
Inverted / Top Latch		No	
Jack Height		13.00mm	China ROHS Green Image
Lightpipes/LEDs		None	ELV Not Relevant
Material - Metal		Phosphor Bronze	,
Material - Plating Mating		Gold	
Material - Plating Termina	ation	Tin	
Material - Resin		High Temperature Thermoplastic	Search Parts in this Series
Net Weight		5.244/g	43249 Series
Orientation		Right Angle (Side Entry)	
PCB Locator		Yes	Mates With
PCB Retention		Yes	FCC 68 Plugs
PCB Retention PCB Thickness - Recomn	nended	1.57mm	,
	nended		
Packaging Type		Tray	
Pitch - Mating Interface Pitch - Termination Interfa		1.02mm 1.27mm	
Plating min - Mating		1.270µm	
Plating min - Termination		2.540µm	
Ports		1	
Positions / Loaded Contac		8/8	
Surface Mount Compatible		Yes	
Temperature Range - Ope		-40°C to +85°C	
Termination Interface: Sty	/le	Through Hole	
Waterproof / Dustproof		No	
Wire/Cable Type		N/A	
Flootriac			
Electrical			

1.5A

Yes

Grounding to Panel Shielded Voltage - Maximum

Solder Process Data Lead-freeProcess Capability

Material Info

Reference - Drawing Numbers	
Product Specification	
Sales Drawing	

Top Panel Ground Tabs Yes 150V AC (RMS)

WAVE

PSX-43249 SDA-43249

This document was generated on 02/05/2016 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Telecom ICs category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 87180-066
 B78476A9558A003
 4C9965
 RH1041W-MFP-GNL
 5C3263
 7J8004
 SCMS7D43AY100PT1
 43841-0003-CUT-TAPE

 HX6106NLT
 75586-0004-CUT-TAPE
 JC0-0201NL
 0432498916
 0757840156
 93899-001LF
 9455511103
 10118067-5136210LF
 69253-001

 H1062
 P129
 T7015NLT
 T1231NL
 432238149
 428786360
 432498908
 441500007
 446200003
 432028918
 432498925
 428788458

 443800019
 443801016
 754500001
 757830252
 757840212
 757865001
 950432801
 760925002
 133148
 ST7010QNL
 T-1250SCT
 T3023NL

 66010-004LF
 203156
 68899-002LF
 73327-111LF
 95672-001LF
 95678-001ALF
 45-5614-BU
 DS2174QN+
 CPC1465D