


**SAK terminal with screw connection**  
**SAK 4/35**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com



The Weidmüller SAK feed-through terminals satisfy the requirements of IEC 60947-1 and are available with rated cross-sections from 0.08 mm<sup>2</sup> to 240 mm<sup>2</sup>.

**General ordering data**

Order No.	<a href="#">0443660000</a>
Type	SAK 4/35
Version	SAK terminal with screw connection, Feed-through terminal, Rated cross-section: 4 mm <sup>2</sup> , Screw connection, Direct mounting
GTIN (EAN)	4008190019990
Qty.	100 pc(s).

**SAK terminal with screw connection  
SAK 4/35**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-2083  
 www.weidmueller.com

**Technical data**
**Dimensions**

Length	45 mm	Width	6.5 mm
Height	44 mm	Height of lowest version	44 mm
Net weight	8.6 g		

**Temperatures**

Operating temperature		Storage temperature	
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	100 °C

**Rated data IECEx/ATEX**

Certificate No. (ATEX)	KEMA97ATEX1798U	ATEX certificate	IECExKEM06.0014U
ATEX certificate	KEMA97ATEX1798U_e.pdf	Certificate No. (IECEX)	IECExKEM06.0014U
IEC Ex certificate	IECExKEM06.0014U_e.pdf	max. voltage	550 V
Current (ATEX)	28 A	Wire cross section max. (ATEX)	4 mm <sup>2</sup>
max. voltage	550 V	Current (IECEX)	28 A
Wire cross section max. (IECEX)	4 mm <sup>2</sup>	Voltage, cross-connection	CrossConnectionGuide.pdf
Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity	Marking EN 60079-7	
Marking ATEX Directive 94/9/EC	II 2 G D		Ex e II

**Additional technical data**

Explosion-tested version	Yes	Installation advice	Direct mounting
Number of similar terminals	1	Open sides	right
Type of mounting	Snap-on	Version	Double terminal

**CSA ratings data**

Certificate No. (CSA)	12400-129	Voltage size C (CSA)	600 V
Current size C (CSA)	36 A	Wire cross section max. (CSA)	10 AWG
Wire cross section min. (CSA)	26 AWG		

**Clampable wires (additional connection)**

Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, min.	0.5 mm <sup>2</sup>	Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, max.	4 mm <sup>2</sup>
---	---------------------	---	-------------------

## SAK terminal with screw connection SAK 4/35

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

### Technical data

#### Clampable wires (rated connection)

Type of connection	Screw connection	Stripping length	12 mm
Blade size	0.6 x 3.5 mm	Connection direction	on side
Number of connections	2	Clamping range, rated connection, min.	0.13 mm <sup>2</sup>
Clamping range, rated connection, max.	6 mm <sup>2</sup>	Clamping screw	M 3
Tightening torque, min.	0.5 Nm	Tightening torque, max.	1 Nm
Gauge to IEC 60947-1	A4	Wire connection cross section, solid core, max. rated connection	0.5 mm <sup>2</sup>
Wire connection cross section, solid core max. rated connection	6 mm <sup>2</sup>	Wire connection cross section, stranded, rated connection, min.	0.5 mm <sup>2</sup>
Wire connection cross section, stranded, rated connection, max.	4 mm <sup>2</sup>	Wire connection cross section, finely stranded, max.	4 mm <sup>2</sup>
Wire connection cross-section, finely stranded, min.	0.5 mm <sup>2</sup>	Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, min.	0.5 mm <sup>2</sup>
Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, max.	4 mm <sup>2</sup>	Cross-section for connected conductor, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, min.	0.5 mm <sup>2</sup>
Wire connection cross-section, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, max.	4 mm <sup>2</sup>	Twin wire-end ferrules, min.	0.5 mm <sup>2</sup>
Twin wire-end ferrules, max.	2.5 mm <sup>2</sup>	Wire connection cross section AWG, min.	AWG 26

#### Rated data

Rated cross-section	4 mm <sup>2</sup>	Rated voltage	800 V
Rated impulse withstand voltage	8 kV	Rated current	32 A
Current at maximum wires	41 A	Standards	IEC 60947-7-1
Pollution severity	3		

#### UL ratings data

Certificate No. (UR)	E60693VOL1SEC14	Voltage size C (UR)	600 V
Current size C (UR)	30 A	Conductor size Factory wiring max. (UR)	10 AWG
Conductor size Factory wiring min. (UR)	22 AWG	Conductor size Field wiring max. (UR)	10 AWG

#### Material data

Material	PA 66	Colour	Beige
Flammability class UL 94	V-2		

#### System specifications

Product family	SAK terminal with screw connection	Type of connection	Screw connection
Connection direction	on side	Number of levels	1
Number of connections	2	No. of clamping points per level	2
Levels cross-connected internally	No	End cover plate required	Yes

**SAK terminal with screw connection  
SAK 4/35**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

**Technical data****Classifications**

ETIM 2.0	EC000897	ETIM 3.0	EC000897
UNSPSC	30-21-18-11	eClass 4.1	27-14-11-20
eClass 5.1	27-14-11-20	eClass 6.0	27-14-11-20
eClass 7.0	27-14-11-20		

**Product information**

Descriptive text technical data      With twin ferrules ZH 0.5 to ZH 2.5, rated voltage is 690 V.

**Downloads**

STEP      [0443660000\\_24195\\_SAK\\_4-35\\_STP.stp](#)

**SAK terminal with screw connection  
SAK 4/35**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

**Accessories**

**End plate / partition disc**



013010 TW für SAK 4

In order to do justice to the different requirements placed on our products, it is necessary to use various insulating materials tailored to the particular application. None of the insulating materials used by Weidmüller contain any hazardous substances. Above all, we ensure that all our materials are free from cadmium. Furthermore, they contain no colour pigments based on heavy metals and do not lead to the formation of dioxin/furan.

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">0130100000</a>	TW SAK4-10 EP/SW	SAK Series, Partition plate, Black, 2.53 mm	4008190407599	20 pc(s).

**Test plugs**



The solution with Weidmüller test plugs and sockets guarantees a proper test of the installation.

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">0299600000</a>	PS 4 F.STB 4	General accessories, Test plug	4008190074043	20 pc(s).

**SAK terminal with screw connection  
SAK 4/35**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-2083  
 www.weidmueller.com

**Accessories**

**Custom printing**



The **dekafix (DEK)** marker is the universal marker for all conductor and plug-in connectors as well as for electronics modules. The system is ideal for small groups of consecutive numbers and covers a large range of ready-printed markers. Being mounted as strips means that they are quickly clipped on in one operation. The printing is legible with good contrast, and is available in five widths.

- Large selection of ready-to-use markers
- In strips for fast installation
- Connector markers are suitable for all Weidmüller conductor connectors
- Available as blank cards, MultiCard or as cards with standard printing

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">1609850000</a>	DEK 5/6.5 MC BEDRUCKT	Terminal markers, MultiCard, 5 x 6.5 mm, Polyamide 66, Colour: To customer specification	4008190456610	180 pc(s).

**Removable crossconnection links**



Some 60% of all modular terminals have a cross-connection. Weidmüller has a huge range of solutions on offer.

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">0285100000</a>	VH 19/5/3.5 SAK4-16	SAK Series, Connecting sleeve, for cross-connection link, No. of poles: 1	4008190189297	50 pc(s).
<a href="#">0197000000</a>	VL 2 SAK4	SAK Series, Cross-connection lug, for cross-connection link, No. of poles: 2	4008190000271	50 pc(s).
<a href="#">0292500000</a>	BFSC M3X25	General accessories, Fixing screw, for cross-connection link, 25 mm	4008190177027	100 pc(s).

**SAK terminal with screw connection  
SAK 4/35**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

**Accessories**

**AP end cover plates**



Apart from a few exceptions, the last terminal in a terminal strip must be closed off with an AP end plate. End plates must also be used within a terminal strip when it makes use of terminals of different sizes . The overall dimensions of the end plates match the external dimensions of the associated terminal. The end plate is held in place by the end bracket.

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">0117960000</a>	AP SAK4-10	SAK Series, End plate, 1.5 mm, Beige, Direct mounting	4008190081485	20 pc(s).
<a href="#">0117920000</a>	AP SAK4-10 KRG	SAK Series, End plate, 1.5 mm, Dark beige, Yellow, Direct mounting	4008190135904	20 pc(s).
<a href="#">0117970000</a>	AP SAK4-10 KRG/BL	SAK Series, End plate, 1.5 mm, Blue, Direct mounting	4008190049607	20 pc(s).
<a href="#">0117980000</a>	AP SAK4-10 BL	SAK Series, End plate, 1.5 mm, Blue, Direct mounting	4008190171087	20 pc(s).
<a href="#">0117930000</a>	AP SAK4-10 KRS	SAK Series, End plate, 1.5 mm, Anthracite, Direct mounting	4008190049553	20 pc(s).

**connecting sleeve**



VH 12/4.9/3.3 024900

Some 60% of all modular terminals have a cross-connection. Weidmüller has a huge range of solutions on offer.

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">0248500000</a>	VH 13.5/4.9/3.3 SAK4	SAK Series, Connecting sleeve, for cross-connection link, No. of poles: 1	4008190022723	100 pc(s).

**SAK terminal with screw connection  
SAK 4/35**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

**Accessories**

**Plastic screws**



Electrical systems should always be operated in a safe condition. Weidmüller therefore has a large range of covers and marking materials.

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">0128900000</a>	BFSC M3X22 PA/RT	General accessories, Fixing screw, for cross-connection link, 22 mm	4008190084158	100 pc(s).

**Q ... SAK**



This type of cross-connection has a pre-assembled captive cross-connection lug, cross-connection sleeve and fixing screw.  
All the individual parts are available separately on request. During installation, the pre-assembled cross-connectors are simply placed in the cross-connection slot in the middle of the terminal and screwed tight.

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">0336900000</a>	Q 4 SAK4	SAK Series, Cross-connector, for cross-connection link, No. of poles: 4	4008190036201	50 pc(s).
<a href="#">0368800000</a>	Q 10 SAK4	SAK Series, Cross-connector, for cross-connection link, No. of poles: 10	4008190049478	20 pc(s).
<a href="#">0336800000</a>	Q 3 SAK4	SAK Series, Cross-connector, for cross-connection link, No. of poles: 3	4008190089795	50 pc(s).
<a href="#">0336700000</a>	Q 2 SAK4	SAK Series, Cross-connector, for cross-connection link, No. of poles: 2	4008190033842	50 pc(s).



**SAK terminal with screw connection  
SAK 4/35**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

**Accessories**

**TSCH**



In order to maintain the rated voltage it is necessary to use the partition walls TW or the partition discs TSch in the products WDL, SAKT und WTL.

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">0319160000</a>	TSCH 1	General accessories, Small partition, Beige, 2 mm	4008190097219	100 pc(s).
<a href="#">0353660000</a>	TSCH 2	General accessories, Small partition, Beige, 0.6 mm	4008190128432	100 pc(s).

**StB 5.5 ... 17**



The SAKR disconnect terminals are available already fitted with sockets (see disconnect terminals). The sockets are equipped with a slit so that they can be actuated with a screwdriver. Weidmüller can supply special screwdrivers with a shoulder for this purpose.

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">0168600000</a>	STB 14/D5/2.3/M3 SAK2.5	SAK Series, Socket	4008190135225	50 pc(s).

**SAK terminal with screw connection  
SAK 4/35**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

**Accessories**

**Blank**



The **dekafix (DEK)** marker is the universal marker for all conductor and plug-in connectors as well as for electronics modules. The system is ideal for small groups of consecutive numbers and covers a large range of ready-printed markers. Being mounted as strips means that they are quickly clipped on in one operation. The printing is legible with good contrast, and is available in five widths.

- Large selection of ready-to-use markers
- In strips for fast installation
- Connector markers are suitable for all Weidmüller conductor connectors
- Available as blank cards, MultiCard or as cards with standard printing

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">1609840000</a>	DEK 5/6.5 MC NEUTRAL	Terminal markers, MultiCard, 5 x 6.5 mm, Polyamide, Colour: White	4008190203429	900 pc(s).

**AD 3 (4-pole)**



Electrical systems should always be operated in a safe condition. Weidmüller therefore has a large range of covers and marking materials.

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">0285300000</a>	AD 4 SAK4	SAK Series, cover plate, Yellow, 25.6 mm	4008190072902	50 pc(s).

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DIN Rail Terminal Blocks](#) category:*

*Click to view products by [Weidmuller](#) manufacturer:*

Other Similar products are found below :

[1045932](#) [00110420202](#) [00110430402](#) [5724.2/L](#) [592808-3](#) [CTS25U/BL](#) [CTS2.5U-N/Y](#) [91.010](#) [91.040](#) [DP25-GY-ND](#) [15288](#) [90.070](#) [90.905](#)  
[91.001](#) [91.020](#) [91.201](#) [91.340](#) [2713793](#) [2757571](#) [280-331](#) [283-317](#) [283-607](#) [2909044](#) [2909798](#) [29-2052](#) [SRT2-OD08CL-1](#)  
[CDL4U\(E\)MOV](#) [2757801](#) [2794660](#) [284-317](#) [2890975](#) [2907033](#) [3048496](#) [CTS2.5U-N/O](#) [5542152](#) [5602077](#) [0709880](#) [5520682](#) [5605444](#)  
[5607102](#) [EPUSC](#) [SRT2-OD16P](#) [2901288](#) [591620-2](#) [1-591651-1](#) [NRA37-1/2](#) [592814-1](#) [592814-3](#) [SRT2-ID16P](#) [NRA37-12](#)