

This document was generated on 10/30/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 76165-9807

Status: Active

Overview: Impact™ Backplane Connectors and Cable Assemblies

Description: Impact[™] 100 Ohm 3 Pair Vertical Backplane Header, Right Guide, Left Endwall, 8

Columns, 72 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm,

Lead-Free

Documents:

<u>Application Specification AS-76060-990 (PDF)</u>

<u>Drawing (PDF)</u>
<u>RoHS Certificate of Compliance (PDF)</u>

Product Specification PS-76060-999 (PDF)

Agency Certification

UL E29179

General

Product Family Backplane Connectors

Series 76165
Application Conventional
Application Tooling Documents TM-622018799
Component Type PCB Header

Overview <u>Impact™ Backplane Connectors and Cable Assemblies</u>

UPC 883906402389

Physical

Circuits (Loaded) 72
Circuits (maximum) 72
Color - Resin Black
Durability (mating cycles max) 200
First Mate / Last Break No
Flammability 94V-0
Guide to Mating Part Yes
Keying to Mating Part None

Material - Metal High Performance Alloy (HPA)

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

4.945/g Net Weight **Number of Columns Number of Pairs** 3 Number of Rows Orientation Vertical PC Tail Length 1.40mm **PCB** Locator No **PCB** Retention None PCB Thickness - Recommended 1.00mm

PCB Thickness - Recommended
Packaging Type
Tray
Pitch - Mating Interface
Pitch - Termination Interface
Plating min - Mating
Polarized to PCB
Tray
0.762
Polarized to PCB
Tray
1.90
0.762
Polarized to PCB
Yes

Temperature Range - Operating -55°C to +85°C

Termination Interface: Style Through Hole - Compliant Pin



Series

image - Reference only

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

76165Series

Mates With

76170 Impact™ 100 Ohm Daughtercard

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

DescriptionProduct #Backplane Header0621009610Removal Tool forGbX-U™, I-Trac™,Impact™, or TinMan

Backplane Insertion <u>0621005800</u>

Tool for Signal

Contact

Press-in-Tool for <u>0622018674</u>

Daughter Card Signal Module, 3-

Pair by 8-Column Assemblies

Electrical

Current - Maximum per Contact 0.75A

Data Rate 25.0 Gbps

Impedance 100#

Shield Type N/A

Shielded No

Voltage - Maximum 30V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Application Specification AS-76060-990 Product Specification PS-76060-999

Sales Drawing SD-76155-003, SD-76165-003

Symbol/Footprint Data SYM-76165-9807

This document was generated on 10/30/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

2332816-1 89006-1137LF 650827-1 65762-001LF 73474-201LF 74040-1346 74075-0267 88911-201LF 9514M0C20D 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 2187462-1 2226278-6 KA81-07 91290-101LF 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 2226279-2 22354-8 437-5040-000 5-1393565-0 532449-3 532803-2 34745-0001 0740618502 0760151403 0760551105 0760551608 0761451128 0761651124 0761655108 0761659807 0769853208 0736440217 0758324203