



Technical data

- In accordance to DIN VDE 0262/12.95 and DIN VDE 0281 part 13, with insulation wall thickness for 1 kV
- **Temperature range**
flexing -15 °C¹⁾ to +80 °C
fixed installation -40 °C to +80 °C
- **Nominal voltage** U₀/U 0,6/1 kV
- **Test voltage** 4000 V
- **Breakdown voltage** min. 8000 V
- **Insulation resistance**
min. 20 MOhm x km
- **Current carrying capacity**
in accordance to VDE 0298 part 4
- **Minimum bending radius**
flexing 7,5x cable ø
fixed installation 4x cable ø
- **Radiation resistance**
up to 80x10⁶ cJ/kg (up to 80 Mrad)
- ¹⁾ cold bending test, impact resistance test at low temperatures, elongation test at low temperatures. Tested according VDE 0473 part 811-1-4, EN 60811-1-4

Cable structure

- Bare copper, fine wire conductors, as per DIN VDE 0295 cl. 5, BS 6360 cl. 5 and IEC 60228 cl. 5
- Special PVC core insulation TI2, to DIN VDE 0281 part 1
- Black cores with white figure imprints to DIN VDE 0293
- Green-yellow earth core in the outer layer (3 cores and above)
- Cores stranded in layers with optimal lay-length
- Special PVC outer sheath TM2, to DIN VDE 0281 part 1
- Colour black (RAL 9005)
- with meter marking, change-over in 2011

Properties

- Extensively oil resistant, oil-/ chemical resistance - see table Technical Informations
- PVC self-extinguishing and flame retardant according to VDE 0482-332-1-2, DIN EN 60332-1-2/ IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers
- **UV- resistant**

Note

- G = with green-yellow earth core;
x = without green-yellow earth core (OZ).
- Different dimensions are also available with red resp. blue cores.
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².
- **screened analogue type:**
JZ-600-Y-CY see page A 36

Application

Wiring cable for measuring and controlling purposes in tool machinery, conveyor belts and production lines, for plant installations, air conditioning and in steel production plants and rolling mills. Suitable for installation for flexible use for medium mechanical stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms as well as outside (fixed installation). Is not suitable to be used as direct burial- or as underwater cable. The cores have been numbered in such a way that the numbers are easily identifiable, even if the cable has only been stripped back a few cm. The core numbers have been underlined to avoid confusion. The earth core is located in the outer layer. The black, special PVC outer sheath is resistant to the ultra violet radiation. Mainly used in South-European, Eastern and Arabian countries.

CE The product is conformed with the EC Low-Voltage Directive 2006/95/EG.

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.	Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
10550	2 x 0,5	6,3	9,6	56,0	20	10582	2 x 0,75	6,6	14,4	66,0	18
10551	3 G 0,5	6,6	14,4	68,0	20	10583	3 G 0,75	6,9	21,6	74,0	18
10552	3 x 0,5	6,6	14,4	68,0	20	10584	3 x 0,75	6,9	21,6	74,0	18
10553	4 G 0,5	7,2	19,0	100,0	20	10585	4 G 0,75	7,5	29,0	126,0	18
10554	4 x 0,5	7,2	19,0	100,0	20	10586	4 x 0,75	7,5	29,0	126,0	18
10555	5 G 0,5	8,0	24,0	117,0	20	10587	5 G 0,75	8,4	36,0	140,0	18
10556	5 x 0,5	8,0	24,0	117,0	20	10588	5 x 0,75	8,4	36,0	140,0	18
10557	6 G 0,5	8,7	29,0	126,0	20	10589	6 G 0,75	9,3	43,0	170,0	18
10558	7 G 0,5	8,7	33,6	138,0	20	10590	6 x 0,75	9,3	43,0	170,0	18
10559	7 x 0,5	8,7	33,6	138,0	20	10591	7 G 0,75	9,3	50,0	190,0	18
10560	8 G 0,5	9,5	38,0	150,0	20	10592	7 x 0,75	9,3	50,0	190,0	18
10561	8 x 0,5	9,5	38,0	150,0	20	10593	8 G 0,75	10,0	58,0	212,0	18
10562	10 G 0,5	10,6	48,0	176,0	20	10594	8 x 0,75	10,0	58,0	212,0	18
10563	12 G 0,5	11,4	58,0	200,0	20	10595	9 G 0,75	10,9	65,0	227,0	18
10564	12 x 0,5	11,4	58,0	200,0	20	10596	10 G 0,75	11,1	72,0	238,0	18
10565	14 G 0,5	12,3	67,0	230,0	20	10597	12 G 0,75	12,2	86,0	257,0	18
10566	16 G 0,5	12,9	76,0	250,0	20	10598	12 x 0,75	12,2	86,0	257,0	18
10567	18 G 0,5	13,8	86,0	276,0	20	10599	14 G 0,75	12,9	101,0	286,0	18
10568	20 G 0,5	14,4	96,0	293,0	20	10600	15 G 0,75	13,8	108,0	319,0	18
10569	21 G 0,5	14,4	96,0	305,0	20	10601	18 G 0,75	14,5	130,0	362,0	18
10570	25 G 0,5	16,1	120,0	335,0	20	10602	20 G 0,75	15,4	144,0	394,0	18
10571	30 G 0,5	17,2	144,0	348,0	20	10603	21 G 0,75	15,4	151,0	422,0	18
10572	32 G 0,5	18,0	154,0	355,0	20	10604	25 G 0,75	17,2	180,0	486,0	18
10573	34 G 0,5	18,7	163,0	520,0	20	10605	32 G 0,75	19,0	230,0	595,0	18
10574	40 G 0,5	19,5	192,0	590,0	20	10606	34 G 0,75	19,9	245,0	638,0	18
10575	42 G 0,5	20,1	202,0	595,0	20	10607	37 G 0,75	19,9	260,0	696,0	18
10576	50 G 0,5	22,1	240,0	715,0	20	10608	40 G 0,75	20,6	288,0	726,0	18
10577	52 G 0,5	22,1	252,0	740,0	20	10609	41 G 0,75	20,6	296,0	750,0	18
10578	61 G 0,5	23,6	293,0	840,0	20	10610	42 G 0,75	21,5	302,0	770,0	18
10579	65 G 0,5	24,4	312,0	880,0	20	10611	50 G 0,75	23,7	360,0	895,0	18
10580	80 G 0,5	27,2	384,0	960,0	20	10612	61 G 0,75	25,3	439,0	1070,0	18
10581	100 G 0,5	31,2	480,0	1050,0	20	10613	65 G 0,75	26,0	468,0	1110,0	18
						10614	80 G 0,75	28,9	576,0	1500,0	18
						10615	100 G 0,75	33,2	720,0	1889,0	18

Continuation ▶

JZ-600 flexible, number coded, 0,6/1kV, meter marking



Part no.	No.cores x cross-sec. mm²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
10616	2 x 1	7,0	19,2	80,0	17
10617	3 G 1	7,4	29,0	96,0	17
10618	3 x 1	7,4	29,0	96,0	17
10619	4 G 1	8,2	38,4	100,0	17
10620	4 x 1	8,2	38,4	100,0	17
10621	5 G 1	9,2	48,0	130,0	17
10622	5 x 1	9,2	48,0	130,0	17
10623	6 G 1	9,9	58,0	150,0	17
10624	7 G 1	9,9	67,0	170,0	17
10625	7 x 1	9,9	67,0	170,0	17
10626	8 G 1	10,9	77,0	230,0	17
10627	9 G 1	11,6	86,0	250,0	17
10628	10 G 1	11,9	96,0	270,0	17
10629	10 x 1	11,9	96,0	270,0	17
10630	12 G 1	13,1	115,0	290,0	17
10631	12 x 1	13,1	115,0	290,0	17
10632	14 G 1	14,0	134,0	320,0	17
10633	16 G 1	14,8	154,0	360,0	17
10634	18 G 1	15,7	173,0	405,0	17
10635	18 x 1	15,7	173,0	405,0	17
10636	20 G 1	16,7	192,0	450,0	17
10637	20 G 1	16,7	192,0	480,0	17
10638	21 G 1	16,7	205,0	510,0	17
10639	24 G 1	18,4	236,0	550,0	17
10640	25 G 1	18,6	240,0	570,0	17
10641	25 x 1	18,6	240,0	570,0	17
10642	26 G 1	18,8	252,0	590,0	17
10643	30 x 1	19,8	308,0	650,0	17
10644	34 G 1	21,5	326,0	750,0	17
10645	36 G 1	21,5	346,0	790,0	17
10646	40 G 1	22,5	384,0	850,0	17
10647	40 x 1	22,5	384,0	850,0	17
10648	41 G 1	23,2	394,0	890,0	17
10649	42 G 1	23,2	403,0	900,0	17
10650	50 G 1	25,6	480,0	1100,0	17
10651	56 G 1	26,4	538,0	1190,0	17
10652	61 G 1	27,5	586,0	1266,0	17
10653	65 G 1	28,3	628,0	1560,0	17
10654	80 G 1	31,4	786,0	1810,0	17
10655	100 G 1	36,0	960,0	1950,0	17
10656	2 x 1,5	8,2	29,0	95,0	16
10657	3 G 1,5	8,6	43,0	112,0	16
10658	3 x 1,5	8,6	43,0	112,0	16
10659	4 G 1,5	9,6	58,0	139,0	16
10660	4 x 1,5	9,6	58,0	139,0	16
10661	5 G 1,5	10,7	72,0	170,0	16
10662	5 x 1,5	10,7	72,0	170,0	16
10663	6 G 1,5	11,6	86,0	190,0	16
10664	7 G 1,5	11,6	101,0	225,0	16
10665	7 x 1,5	11,6	101,0	225,0	16
10666	8 G 1,5	13,8	115,0	250,0	16
10667	9 G 1,5	15,2	130,0	280,0	16
10668	10 G 1,5	15,2	144,0	300,0	16
10669	11 G 1,5	15,5	158,0	330,0	16
10670	12 G 1,5	15,5	173,0	370,0	16
10671	12 x 1,5	15,5	173,0	370,0	16
10672	14 G 1,5	16,6	202,0	400,0	16
10673	16 G 1,5	17,5	230,0	450,0	16
10674	18 G 1,5	18,6	259,0	520,0	16
10675	19 G 1,5	18,6	279,0	550,0	16
10676	20 G 1,5	19,7	288,0	600,0	16
10677	21 G 1,5	20,6	302,0	600,0	16
10678	25 G 1,5	22,5	360,0	730,0	16
10679	32 G 1,5	24,5	461,0	880,0	16
10680	34 G 1,5	25,6	490,0	950,0	16
10681	40 G 1,5	26,7	576,0	990,0	16
10682	42 G 1,5	27,6	605,0	1120,0	16
10683	50 G 1,5	30,4	720,0	1400,0	16
10684	56 G 1,5	31,5	806,0	1530,0	16
10685	61 G 1,5	32,6	878,0	1700,0	16
10686	65 G 1,5	34,8	936,0	1900,0	16
10687	80 G 1,5	37,4	1152,0	2300,0	16
10688	100 G 1,5	41,6	1440,0	2700,0	16
10689	2 x 2,5	9,6	48,0	160,0	14

Part no.	No.cores x cross-sec. mm²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
10690	3 G 2,5	10,1	72,0	175,0	14
10691	3 x 2,5	10,1	72,0	175,0	14
10692	4 G 2,5	11,2	96,0	203,0	14
10693	4 x 2,5	11,2	96,0	203,0	14
10694	5 G 2,5	12,5	120,0	251,0	14
10695	5 x 2,5	12,5	120,0	251,0	14
10696	7 G 2,5	13,8	168,0	330,0	14
10697	7 x 2,5	13,8	168,0	330,0	14
10698	8 G 2,5	15,1	192,0	400,0	14
10699	12 G 2,5	18,3	288,0	553,0	14
10700	14 G 2,5	19,6	336,0	630,0	14
10701	18 G 2,5	22,0	432,0	795,0	14
10702	21 G 2,5	23,3	504,0	930,0	14
10703	25 G 2,5	26,2	600,0	1110,0	14
10704	34 G 2,5	30,4	816,0	1450,0	14
10705	42 G 2,5	33,0	1008,0	1750,0	14
10706	50 G 2,5	36,2	1200,0	2100,0	14
10707	61 G 2,5	38,8	1464,0	2540,0	14
10708	100 G 2,5	50,2	2400,0	3850,0	14
10709	2 x 4	11,1	77,0	180,0	12
10710	3 G 4	11,7	115,0	230,0	12
10711	4 G 4	13,0	154,0	310,0	12
10712	5 G 4	14,5	192,0	410,0	12
10713	7 G 4	16,0	269,0	540,0	12
10714	8 G 4	17,4	307,0	710,0	12
10715	12 G 4	21,4	461,0	860,0	12
10716	3 G 6	13,1	173,0	370,0	10
10717	4 G 6	14,5	230,0	430,0	10
10718	5 G 6	16,2	288,0	650,0	10
10719	7 G 6	18,0	403,0	860,0	10
10720	3 G 10	16,5	288,0	660,0	8
10721	4 G 10	18,2	384,0	790,0	8
10722	5 G 10	20,3	480,0	960,0	8
10723	7 G 10	22,5	672,0	1300,0	8
10724	3 G 16	20,1	461,0	700,0	6
10725	4 G 16	22,3	614,0	1100,0	6
10726	5 G 16	25,0	768,0	1600,0	6
10727	7 G 16	27,4	1075,0	1890,0	6
10728	3 G 25	24,8	720,0	1450,0	4
10729	4 G 25	27,4	960,0	1600,0	4
10730	5 G 25	30,5	1200,0	2050,0	4
10731	7 G 25	33,8	1680,0	2900,0	4
10732	3 G 35	27,1	1008,0	1900,0	2
10733	4 G 35	30,0	1344,0	2400,0	2
10734	5 G 35	33,3	1680,0	2900,0	2
10735	3 G 50	32,4	1440,0	2700,0	1
10736	4 G 50	35,8	1920,0	3400,0	1
10742	5 G 50	40,0	2400,0	4361,0	1
10737	3 G 70	36,9	2016,0	3300,0	2/0
10738	4 G 70	40,9	2688,0	4400,0	2/0
10743	5 G 70	45,5	3360,0	5807,0	2/0
10739	3 G 95	41,7	2736,0	5050,0	3/0
10740	4 G 95	46,2	3648,0	6010,0	3/0
10744	5 G 95	51,7	4560,0	7752,0	3/0
10741	4 G 120	51,6	4608,0	7500,0	4/0
10745	4 G 150	58,5	5760,0	8640,0	300 kcmil
10746	4 G 185	61,1	7104,0	10380,0	350 kcmil

Dimensions and specifications may be changed without prior notice. (RA01)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [Helukabel](#) manufacturer:

Other Similar products are found below :

[M27500-20SP2S23](#) [M3905-BK005](#) [6502FE 8771000](#) [CV6807-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [720451-000](#) [752687-000](#) [83709-002-1000](#) [8469 060100](#) [877541-000](#) [88444-002-1000](#) [9444 060U1000](#) [9497 0001000](#) [9684-060-1000](#) [1302110032](#) [EPD6062-12-9CS1693](#) [EPD-RWC-10972](#) [EPD-RWC-12305](#) [C35473-000](#) [2020D1301-9](#) [219538-6](#) [2412F-010-1000](#) [9534 060U500](#) [29531-010-2000](#) [22759/41-22-9CS2620](#) [259633-000](#) [29529C-010-2000](#) [29532-010-1500](#) [302595-000](#) [CTC-0018-22-9/5-9CS2340](#) [3600B/50 100SF](#) [3644B/16-100SF](#) [CXA-0078-20-3-9CS2405](#) [CXA-0092-14-6/9CS2973](#) [MC6A-16/0.2T2-YWGN](#) [44A0211-20-9CS3030](#) [44A0311-12-9-F871](#) [44A1221-14-9/9-9CS3030](#) [44A1221-16-9/9-9CS3030](#) [44A1321-14-9/9-9CS3030](#) [44A9685-0-F957CS2855](#) [506087-000](#) [5102UE 008500](#) [5201UE 0081000](#) [534553-000](#)