


# BUS Cables

CAN Bus fixed installed

 **HELUKABEL®**

PVC



## Type Cable structure

Inner conductor diameter:  
Core insulation:  
Core colours:  
Stranding element:  
Separator:  
Shielding 1:  
Total shielding:  
Outer sheath material:  
Cable external diameter:  
Outer sheath colour:

## Fixed installation, indoor 2x2x0.50 mm<sup>2</sup> (stranded)

Copper, bare (AWG 20/7)  
Foam-skin-PE  
wh/bn, gn/ye  
Double core  
Polyester foil over stranded bundle  
-  
Cu braid, tinned  
PVC  
app. 9,6 mm ± 0,3 mm  
Violet similar to RAL 4001

## Electrical data

Characteristic impedance: 120 Ohm ± 10 %  
Conductor resistance, max.: 34,4 Ohm/km  
Insulation resistance, min.: 5 GOhm x km  
Loop resistance: 68 Ohm/km max.  
Mutual capacitance: 40 nF/km nom.  
Nominal voltage: 250 V  
Test voltage: 1,5 kV

## Technical data

Weight: app. 116 kg/km  
bending radius, repeated: 150 mm  
Operating temperature range min.: -40°C  
Operating temperature range max.: +70°C  
Caloric load, approx. value: 1,62 MJ/m  
Copper weight: 60,00 kg/km

## Norms

Applicable standards: CAN Bus acc. to ISO 11898-2  
Flame-retardant acc. to IEC 60332-1-2  
UL Style: CMX 75°C (shielded)  
CSA standard: CSA FT1

## Application

HELUKABEL® CAN Bus for fixed installation and occasion motion, for normal requirements. The two signal pairs are provided in the form twisted pairs. As a result, the diameter is somewhat larger than that of 800685. In the event of diameter problems, please have a look at this type. For cable lengths up to 600m (observe CAN specifications).

## Part no.

**803722**, CAN BUS

Dimensions and specifications may be changed without prior notice.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Ethernet Cables / Networking Cables](#) category:*

*Click to view products by [Helukabel](#) manufacturer:*

Other Similar products are found below :

[0152660053](#) [603020002](#) [73-7797-25](#) [73-8890-10](#) [73-8890-14](#) [73-8891-14](#) [73-8891-25](#) [73-8892-50](#) [73-8894-10](#) [73-8894-3](#) [73-8895-14](#) [73-8896-7](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [9QA0-111-12-3.00](#) [1200650742](#) [1200700174](#) [1200860368](#) [1200650013](#) [1201080008](#) [1-21919-1](#) [1300500373](#) [1300101844](#) [1300101845](#) [130050-0004](#) [1300500014](#) [1410147](#) [E16A06002M030](#) [E200102-009-S1](#) [MT14-187L](#) [17-103530](#) [NK5EPC18RDY](#) [NK5EPC18VLY](#) [NK5EPC18YLY](#) [NK5EPC1GRY](#) [NK5EPC30BLY](#) [NK5EPC30VLY](#) [NK5EPC30YLY](#) [NK5EPC4Y](#) [NK5EPC6YLY](#) [NK5EPC8BLY](#) [NK5EPC9YLY](#) [NK6PC30BUY](#) [NK6PC30GRY](#) [NK6PC30RDY](#) [NK6PC30Y](#) [NK6PC30YLY](#) [1969343-6](#) [C501100010](#) [C501106002](#)