



SECTION X-X

- 1 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
- 2 POINT OF MEASUREMENT FOR PLATING THICKNESS.
- 3 OBSOLETE PART NUMBER.
- 4 POSTS: .000030 GOLD IN CONTACT AREA, .000100-.000200 MATTE TIN-LEAD ON SOLDER TAIL, ALL OVER .000050 NICKEL.
- 5 POSTS: .000030 GOLD IN CONTACT AREA, .000100-.000200 MATTE TIN ON SOLDER TAIL, ALL OVER .000050 NICKEL.
- 6 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI.



RECOMMENDED HOLE LAYOUT

	5	3.506	.106	3.732	3.600	36	74	6	8-103168-5
	5	3.406	.106	3.632	3.500	35	72	6	8-103168-4
	5	3.306	.106	3.532	3.400	34	70	6	8-103168-3
	5	3.206	.106	3.432	3.300	33	68	6	8-103168-2
	5	3.106	.106	3.332	3.200	32	66	6	8-103168-1
	5	3.006	.106	3.232	3.100	31	64	6	8-103168-0
	5	2.906	.106	3.132	3.000	30	62	6	7-103168-9
	5	2.806	.106	3.032	2.900	29	60	7	7-103168-8
	5	2.706	.106	2.932	2.800	28	58	6	7-103168-7
	5	2.606	.106	2.832	2.700	27	56	6	7-103168-6
	5	2.506	.106	2.732	2.600	26	54	6	7-103168-5
	5	2.406	.106	2.632	2.500	25	52	6	7-103168-4
	5	2.306	.106	2.532	2.400	24	50	7	7-103168-3
	5	2.206	.106	2.432	2.300	23	48	6	7-103168-2
	5	2.106	.106	2.332	2.200	22	46	6	7-103168-1
	5	2.006	.106	2.232	2.100	21	44	7	7-103168-0
	5	1.906	.106	2.132	2.000	20	42	6	6-103168-9
	5	1.806	.106	2.032	1.900	19	40	6	6-103168-8
	5	1.706	.106	1.932	1.800	18	38	6	6-103168-7
	5	1.606	.106	1.832	1.700	17	36	6	6-103168-6
	5	1.506	.106	1.732	1.600	16	34	6	6-103168-5
	5	1.406	.106	1.632	1.500	15	32	6	6-103168-4
	5	1.306	.106	1.532	1.400	14	30	6	6-103168-3
	5	1.206	.106	1.432	1.300	13	28	6	6-103168-2
	5	1.106	.106	1.332	1.200	12	26	6	6-103168-1
	5	1.006	.106	1.232	1.100	11	24	6	6-103168-0
	5	.906	.106	1.132	1.000	10	22	5	5-103168-9
	5	.806	.106	1.032	.900	9	20	5	5-103168-8
	5	---	.406	.932	.800	8	18	5	5-103168-7
	5	---	.306	.832	.700	7	16	5	5-103168-6
	5	---	.306	.732	.600	6	14	5	5-103168-5
	5	---	.206	.632	.500	5	12	5	5-103168-4
	5	---	.206	.532	.400	4	10	5	5-103168-3
	5	---	.106	.432	.300	3	8	5	5-103168-2
	5	---	.106	.332	.200	2	6	5	5-103168-1
PLATING		E	D	C	B	A	NO OF POSN		ASSEMBLY PART NUMBER

	4	3.506	.106	3.732	3.600	36	74	3	3-103168-5
	4	3.406	.106	3.632	3.500	35	72	3	3-103168-4
	4	3.306	.106	3.532	3.400	34	70	3	3-103168-3
	4	3.206	.106	3.432	3.300	33	68	3	3-103168-2
	4	3.106	.106	3.332	3.200	32	66	3	3-103168-1
	4	3.006	.106	3.232	3.100	31	64	3	3-103168-0
	4	2.906	.106	3.132	3.000	30	62	2	2-103168-9
	4	2.806	.106	3.032	2.900	29	60	2	2-103168-8
	4	2.706	.106	2.932	2.800	28	58	2	2-103168-7
	4	2.606	.106	2.832	2.700	27	56	2	2-103168-6
	4	2.506	.106	2.732	2.600	26	54	2	2-103168-5
	4	2.406	.106	2.632	2.500	25	52	2	2-103168-4
	4	2.306	.106	2.532	2.400	24	50	2	2-103168-3
	4	2.206	.106	2.432	2.300	23	48	2	2-103168-2
	4	2.106	.106	2.332	2.200	22	46	2	2-103168-1
	4	2.006	.106	2.232	2.100	21	44	2	2-103168-0
	4	1.906	.106	2.132	2.000	20	42	1	1-103168-9
	4	1.806	.106	2.032	1.900	19	40	1	1-103168-8
	4	1.706	.106	1.932	1.800	18	38	1	1-103168-7
	4	1.606	.106	1.832	1.700	17	36	1	1-103168-6
	4	1.506	.106	1.732	1.600	16	34	1	1-103168-5
	4	1.406	.106	1.632	1.500	15	32	1	1-103168-4
	4	1.306	.106	1.532	1.400	14	30	1	1-103168-3
	4	1.206	.106	1.432	1.300	13	28	1	1-103168-2
	4	1.106	.106	1.332	1.200	12	26	1	1-103168-1
	4	1.006	.106	1.232	1.100	11	24	1	1-103168-0
	4	.906	.106	1.132	1.000	10	22		103168-9
	4	.806	.106	1.032	.900	9	20		103168-8
	4	---	.406	.932	.800	8	18		103168-7
	4	---	.306	.832	.700	7	16		103168-6
	4	---	.306	.732	.600	6	14		103168-5
	4	---	.206	.632	.500	5	12		103168-4
	4	---	.206	.532	.400	4	10		103168-3
	4	---	.106	.432	.300	3	8		103168-2
	4	---	.106	.332	.200	2	6		103168-1
PLATING		E	D	C	B	A	NO OF POSN		ASSEMBLY PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. **STC** TE Connectivity

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN H. MOLL 04 SEP 87	APVD R. FEJDT 09 SEP 87
0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± .005
4 PLC ± -	ANGLES ± -	SIZE	CAGE CODE
MATERIAL: HOUSING: FUME-RESISTANT THERMOPLASTIC; COLOR: BLACK; POSTS: PHOS BRINZE	FINISH: SEE TABLE	WEIGHT	RESTRICTED TO
CUSTOMER DRAWING		SCALE: 4:1	SHEET 1 OF 1 REV J4

HDR ASSY, MOD II, SHROUDED, 4 SIDES, DBL ROW, VERTICAL, .100X.100, WITH .025 SQ POSTS

00779C=103168

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)