


BN 19

Hexagon socket button head screws
 partially / fully threaded
 partially / fully threaded

ISO 7380



Material	Steel	Proof stress 0,2%	900 N/mm2
Surface	black	Elongation after fracture	min. 9%
Quality	010.9 / 10.9 012.9 / 12.9		

Article No. - 1135058

d ₁	M4
L	30
d ₂ max.	7,6
b	20
k max.	2,2
s	2,5
t min.	1,3

Limited use:

M2; M2,5: Not according to ISO 7380

Dimension d₂ according to ISO not on stock: M3 (5,7 mm); M4 (7,6 mm); M10 (17,5 mm)

Fully threaded or partially threaded at manufacturer's option.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Screws & Fasteners](#) category:

Click to view products by [Bossard](#) manufacturer:

Other Similar products are found below :

[5721-1440-1/4-SS](#) [593503FX](#) [0098.0094](#) [0098.9206](#) [0098.9219](#) [0098.9221](#) [0098.9262](#) [596-2114-013](#) [59781-4](#) [59781-6](#) [0098.0026](#)
[0098.9210](#) [0098.9212](#) [60227-01](#) [60227-04](#) [60227-08](#) [60228-09](#) [618-00001](#) [62153-03](#) [62153-11](#) [M316-KSSTMCZ100](#) [M3440-SS](#) [M3442-SS](#) [M3448-SS](#) [6291A](#) [6292-1](#) [6-306105-9](#) [6-306131-4](#) [690432-1](#) [699161-000](#) [700989](#) [7-18023-1](#) [7-21002-8](#) [7230-3](#) [7235-3](#) [7248-1](#) [7248-2](#)
[73542-02](#) [CAPTIVE SHORT THUMBSCREW](#) [745564-1](#) [748174-2](#) [F03-02](#) [SUS316](#) [F1209](#) [751-00001](#) [80011](#) [809704-1](#) [8700](#) [8860220](#)
[9047](#) [95000002B](#) [9885-2](#)