

Products

- О <u>Ву Туре</u> .
 - Connectors • Electromechanical Components
 - . Electronic Modules
 - Fiber Optics
 - Filters
 - Identification & Labeling Passive Components
 - Power Sources
 - . RF & Microwave Products
 - Tooling Products
 - Touch Screen Displays •
 - Tubing, Molded and Harnessing Products Wire, Cable and Cable Assemblies
 - List all product ty pes...
- O By Industry
 - Aerospace & Defense Products

 - <u>Appliance</u>
 <u>Autom otive</u>
 - Communications <u>Computer & Consumer Electronics</u>
 - Industrial & Comm ercial
 - Instrumentation & Medical
- O By Brand
- O <u>A to Z</u> O <u>Product News</u>

Documentation

- O Find Documents & Drawings
- 0 0 Find CAD Models
- SPICE/Electrical Models
- NAFTA Certificate of Origin 0 O White Papers

<u>Resources</u>

- 0 RoHS Compliance & Alternates
- 0 0 Cross Reference Products
- Compare Multiple Products Check Distributor Inventory 0
- O Find Authorized Distributors

• My Account

- O Sign In O Register
- <u>Customer Support</u>

 - Support
 RoHS Support Center
 Glossary of Terms
 eBulletin Newsletter

1-1520237-0 Product Details

Live Product Chat US Only

Power Toggle Switches

No Image Available

Not EU RoHS or ELV Compliant

- Product Highlights:
- Double Pole Single Throw Configuration (Pole-Throw) ٠ Toggle Length = 17.07 m m
- ٠ Toggle Style = Baton
- Bushing Length = 11.91 mm
 Term ination Type = Screw-In Terminal
- View all Features | Find Sim ilar Products

Documentation & Additional Information

Product Drawings:

• <u>DIM'SFOR DBL. POLE TOOL HANDLE SW. FOR EUROPEAN USE</u> (PDF, English)

Catalog Pages/Data Sheets:

1-1520237-0

Active

None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information)

- <u>2D Drawing</u> (DXF, Version E)
- <u>3D Model</u> (IGES, Version E)
- <u>3D Model</u> (STEP, Version E)

List all Docum ents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Configuration (Pole-Throw) = Double Pole Single Throw
- Termination Type = Screw-In Terminal

Electrical Characteristics:

- UL/CSA 125V Current Rating (Amps.) = 16
- UL/CSA 250V Current Rating (Amps.) = 8
- UL/CSA 125V Horse Power Rating (hp) = 1.00

Housing Related Features:

- Toggle Length (m m [in]) = 17.07 [0.672]
- Toggle Style = Baton

Provide Website Feedback Contact Customer Support Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support 2008 Ty co Electronics Corporation All Rights Reserved

Related Products: Tooling

Configuration Related Features:

• Bushing Length (mm [in]) = 11.91 [0.469]

Industry Standards:

- <u>RoHS/ELV Compliance</u> = Not ELV/RoHS compliant
- Lead Free Solder Processes = Not relevant for lead free process

Other:

• Brand = Alcoswitch

Previous 1 [2] 3 4 5 ... 20 Next Quick Links

- Check Pricing & Availability ٠
- Search for Tooling Product Feature Selector
- Compare Products •
 - Contact Us About This Product

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Toggle Switches category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below :

A19HV 8A1-C-222 60012L 6006L 6663 7101MD9V30GE 7101SPDV30BE 7103SDV30BE 7105D 7108P3YAV2BE 71YY50282 7201MD9AVBE 7301K38 7306K36 7310K36 7314K36 7506K4 7592K6 7691K14 7700K1 8396K108 8824K14 8828K13 G2VX G3VX PS83-121G A101MD9AB04 A101SD9AB04 A101SDCQ04 A103SD9AQ04 A107TZB04 A123P32YZQ A123S1YZG A127S1YCQ 1-1825192-0 A131S1YZQ A201SCWZB04 A207SYCB04 A208J61ZQ0004 A221K12KAG A221S1YZQ A221T1TCQ A232K12KZQ A232M1YCQ A323S1CWZQ A423S1CWZG-M8 A423S1YZQ 12149A-3V 12156AX408 12147AGKX679