

# SKINTOP® ST NPT / BS NPT

SKINTOP® NPT, polyamide cable gland with conical NPT thread and wide, variable clamping ranges for optimum strain relief











Variety of approval certifications



Optimum strain relief



Mechanical resistance



Maximum vibration protection



Good chemical resistance

#### **Benefits**

Conical NPT thread Permanent vibration protection Optimum strain relief Wide, variable clamping ranges Maximum reliability

### **Application range**

Used in areas where a lot of cables and wires need to be inserted into housings with minimum space requirements Machine and equipment manufacturing Automation technology Devices
Housings

### Norm references / Approvals

UL File Nr. E79903

Last Update (10.01.2018)
©2018 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02\_03.16



# SKINTOP® ST NPT / BS NPT

## **Product Make-up**

NPT connection thread acc. to ASME B1.20.1 - 2013

SKINTOP® STR NPT is equipped with a reduction seal insert to seal cables and wires with small outer diameters.

#### Note

Refer to SKINTOP® PG accessories for suitable accessories. Note that SKINTOP® GMP-GL counter nut is not compatible with this model.

3/8" = PG9

1/2" = PG13.5

3/4" = PG21

1" = PG29

## **Technical Data**

Classification ETIM 5: ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6: ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Colour delivered: Silver grey (RAL 7001)

Black (RAL 9005), UV-resistant

Material: Body: Polyamide

Seal: CR

Protection rating: IP 68 - 5 bar

Temperature range: Dynamic: -20 °C to +100 °C

Fixed: -40°C to +100°C

#### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Article designation / size	Clamping range ØF (mm)	SW wrench size mm	Overall length, C (mm)
SKINTOP® ST NPT silver grey				
53016010	NPT 3/8"	3.5 - 8	19	43
53016030	NPT 1/2"	5 - 12	24	47
53016050	NPT 3/4"	13 - 18	33	53
53016060	NPT 1"	14 - 25	42	60
SKINTOP® ST NPT black				
53016210	NPT 3/8"	3.5 - 8	19	43
53016230	NPT 1/2"	5 - 12	24	47
53016250	NPT 3/4"	13 - 18	33	53
53016260	NPT 1"	14 - 25	42	60
SKINTOP® STR NPT silver grey				
53016110	NPT 3/8"	2 - 6	19	43
53016130	NPT 1/2"	4 - 9	24	47
53016150	NPT 3/4"	9 - 16	33	53
SKINTOP® STR NPT black				
53016310	NPT 3/8"	2 - 6	19	43
53016330	NPT 1/2"	4 - 9	24	47
53016350	NPT 3/4"	9 - 16	33	53
SKINTOP® BS NPT silver grey				
53016610	NPT 3/8"	3.5 - 8	19	80.5
53016630	NPT 1/2"	5 - 12	24	104
53016650	NPT 3/4"	13 - 18	33	133
SKINTOP® BS NPT black				
53016810	NPT 3/8"	3.5 - 8	19	80.5
53016830	NPT 1/2"	5 - 12	24	104
53016850	NPT 3/4"	13 - 18	33	133



# SKINTOP® ST NPT / BS NPT



# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Glands, Strain Reliefs & Cord Grips category:

Click to view products by Lapp Kabel manufacturer:

Other Similar products are found below:

120-116-1-1-20BP 120-116-1-1-32BE 120-117-40 120-123-14 120-123-16 120-125-16 120-125-16R 120-125-16Y 120-125-24Y 120-125-28R 120-125-32 120-125-32R 120-125-40 120-125-56 120-126-14 120-126-16 120-126-20 120-126-20BL 120-126-20R 120-126-24 120-126-28 120-126-32 120-126-40BL 120-116-1-1-06BP-509 120-116-1-1-06CP 120-116-1-1-16BE 120-116-1-1-28BP 120-123-20 120-123-24 120-123-32 120-125-20 120-125-20Y 120-125-24 120-125-24R 120-125-28Y 120-126-14BL 120-126-16R 120-126-16Y 120-126-24BL 120-126-28BL 120-126-32BL 120-126-40 120-126-48 120-126-48BL 1300980012 1300980105 DBZM-6828 1498 15190-103 R2