# **FERROXCUBE**

# DATA SHEET

# E71/33/32 E cores and accessories

Supersedes data of September 2004

2008 Sep 01




# E cores and accessories

## **CORE SETS**

#### **Effective core parameters**

SYMBOL	PARAMETER	VALUE	UNIT
Σ(I/A)	core factor (C1)	0.218	mm <sup>-1</sup>
V <sub>e</sub>	effective volume	102000	mm <sup>3</sup>
l <sub>e</sub>	effective length	149	mm
A <sub>e</sub>	effective area	683	mm <sup>2</sup>
A <sub>min</sub>	minimum area	676	mm <sup>2</sup>
m	mass of core half ≈ 260 g		g



#### Core halves

 $A_L$  measured in combination with a non-gapped core half, clamping force for  $A_L$  measurements 60  $\pm 20$  N, unless stated otherwise.

GRADE	A <sub>L</sub> (nH)	μ <sub>e</sub>	TOTAL AIR GAP (μm)	TYPE NUMBER
3C90	100 ±5% <sup>(1)</sup>	≈ 17	≈ 17800	E71/33/32-3C90-E100
	160 ±5% <sup>(1)</sup>	≈ 28	≈ 9620	E71/33/32-3C90-E160
	250 ±5% <sup>(1)</sup>	≈ 43	≈ 5280	E71/33/32-3C90-E250
	315 ±5% <sup>(1)</sup>	≈ 55	≈ 3900	E71/33/32-3C90-E315
	400 ±8% <sup>(1)</sup>	≈ 69	≈ 2860	E71/33/32-3C90-E400
	630 ±10% <sup>(1)</sup>	≈ 109	≈ 1620	E71/33/32-3C90-E630
	10800 ±25%	≈ 1880	≈ 0	E71/33/32-3C90
3C92 des	8000 ±25%	≈ 1390	≈ 0	E71/33/32-3C92
3C94	10800 ±25%	≈ 1880	≈ 0	E71/33/32-3C94
3C95 des	13330 ±25%	≈ 2315	≈ 0	E71/33/32-3C95
3F3	100 ±5% <sup>(1)</sup>	≈ 17	≈ 17800	E71/33/32-3F3-E100
	160 ±5% <sup>(1)</sup>	≈ 28	≈ 9620	E71/33/32-3F3-E160
	250 ±5% <sup>(1)</sup>	≈ 43	≈ 5280	E71/33/32-3F3-E250
	315 ±5% <sup>(1)</sup>	≈ 55	≈ 3900	E71/33/32-3F3-E315
	400 ±8% <sup>(1)</sup>	≈ 69	≈ 2860	E71/33/32-3F3-E400
	630 ±10% <sup>(1)</sup>	≈ 109	≈ 1620	E71/33/32-3F3-E630
	10000 ±25%	≈ <b>1740</b>	≈ 0	E71/33/32-3F3

### Note

1. Measured in combination with an equal gapped core half.

2008 Sep 01

# E cores and accessories

E71/33/32

# Properties of core sets under power conditions

	B (mT) at	CORE LOSS (W) at				
GRADE	H = 250 A/m; f = 25 kHz; T = 100 °C	f = 25 kHz; B = 200 mT; T = 100 °C	f = 100 kHz; B = 100 mT; T = 100 °C	f = 100 kHz; B = 200 mT; T = 25 °C	f = 100 kHz; B = 200 mT; T = 100 °C	f = 400 kHz; B = 50 mT; T = 100 °C
3C90	≥320	≤ 12	≤ 16.5	_	_	-
3C92	≥370	_	≤ 11.5	-	≤ 60	_
3C94	≥320	_	≤ 11.5	_	≤ 60	_
3C95	≥320	_	_	≤73.4	≤ 69.4	_
3F3	≥320	_	≤ 14	_	_	≤ 29

2008 Sep 01 3

# E cores and accessories

E71/33/32

#### **DATA SHEET STATUS DEFINITIONS**

DATA SHEET STATUS	PRODUCT STATUS	DEFINITIONS
Preliminary specification	Development	This data sheet contains preliminary data. Ferroxcube reserves the right to make changes at any time without notice in order to improve design and supply the best possible product.
Product specification	Production	This data sheet contains final specifications. Ferroxcube reserves the right to make changes at any time without notice in order to improve design and supply the best possible product.

#### **DISCLAIMER**

**Life support applications** — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Ferroxcube customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Ferroxcube for any damages resulting from such application.

#### **PRODUCT STATUS DEFINITIONS**

STATUS	INDICATION	DEFINITION
Prototype	prot	These are products that have been made as development samples for the purposes of technical evaluation only. The data for these types is provisional and is subject to change.
Design-in	des	These products are recommended for new designs.
Preferred		These products are recommended for use in current designs and are available via our sales channels.
Support	sup	These products are <b>not</b> recommended for new designs and may not be available through all of our sales channels. Customers are advised to check for availability.

2008 Sep 01 4

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Ferrite Cable Cores category:

Click to view products by Ferroxcube manufacturer:

Other Similar products are found below:

2643626102 FX28R0984-0 FX28R0984-2 AB 3X2X3SM 2643164251 2643665709 2661626402 LB 2.8X4.5U 28R1127 28R1260
28R1575 SM28R0760 SM28R1531 2631006302 2643165451 2643178351 28R0760 MS 21X14X4.5 W SM28B1101 SS7X4X3W 4327
030 16141 ASSE017-2 2643103102 2643164151 2943666671 4327 030 12611 2643163851 AB4X2X6SM 432703013631 LB4X2X8U
28B1101 28B0785 SM28R1575 SM28R1260 74270051 2643625902 74278032 2643480009 2673069901 HFB123049-300 HFB143064100 HFB143064-300 HFB170070-000 ETD29/16/10-3C94 ETD29-3F3 ETD39-3C94 RFP1-20-10-A5 RFP1-40-28-M-A5 RFP2-10-10-A5
RFP2-25-12-A5