



LCD-GRAPHIC MODULE

240x128 WITH CONTROLLER



negative blue:
EA W240-7KHC bzw.
EA W240-7KHLW

**optional
Touch Panel**



yellow-green:
EA W240-7KHLEDB

FEATURES

- * HIGH CONTRAST SUPERTWIST DISPLAY
- * AVAILABLE WITH AND WITHOUT TOUCH PANEL
- * CONTROLLER T6963C BUILT-IN
- * CONNECTION VIA 8-BIT DATA BUS
- * BUILT-IN CHARACTER SET
- * COMBINE TEXT AND GRAPHIC ELEMENTS
- * SELF DEFINABLE CHARACTERS
- * POWER SUPPLY +5V only, typ. 50mA (W./O. BACKLIGHT)
- * OPERATING TEMPERATURE -20 ... +70°C
- * TEMPERATURE COMPENSATION ON-BOARD

ACCESSORIES

- * HIGH-LEVEL-G. CONTROLLER, 3 FONTS + GRAPH.FCT. EA IC6963-PGH
- * READY TO USE UNIT WITH RS-232: EA KIT240-7xxx

ORDERING INFORMATION

LCD GRAPHIC MODULE 240x128 DOTS WITH LED-B./L.
NEGATIVE BLUE WITH CFL-B./L.
NEGATIVE BLUE WITH LED-B./L. WHITE

WITH TOUCH PANEL AND LED-B./L.
WITH TOUCH PANEL, NEGATIVE BLUE, CFL-B./L.
WITH TOUCH PANEL, NEGATIVE BLUE, LED-B./L.

EA W240-7KHLEDB
EA W240-7KHC
EA W240-7KHLW

EA W240-7KHLEDTP
EA W240-7KHCTP
EA W240-7KHLWTP

**ELECTRONIC
ASSEMBLY**
making things easy

LC-DISPLAY SERIES EA W240-7K

These graphic displays provide a resolution of 240x128 dots. All of them are featured with high contrast STN technology. 3 different backlights are available:

- **EA W240-7KHLEDB** is featured with yellow/green LED backlight. That means that displays do have black characters on yellow/green illuminated background. Power consumption for backlight is typ. 900mA at forward voltage of typ. 4.1V. A current limiting resistor is necessary in any case (e.g. at 5V: $R = (5V - 4.1V) / 700mA = 1.3 \Omega$). Maximum current for backlight is 2000mA (note: heavy heat will occur). Life time of LED backlight is 100,000 hours, operating temperature range is -20..+70°C (built-in temperature compensation).
- **EA W240-7KHC** is featured with CFL backlight. That means that displays do have white characters on blue background (negative mode). Operating the CFL backlight requires a CFL inverter **EA CXA-E005W**. Power consumption for backlight is about 300mA@5V. Life time of backlight depends on application with 10,000 up to 30,000 hours. Operating temperature range is -20..+70°C (built-in temperature compensation).
- **EA W240-7KHLW** is also negative blue and is featured with a white LED backlight. This kind of backlight requires a current source or limiting resistor for operation. Current consumption is with max. 135mA (@25°C) and 3.0..3.6V extreme low. Operating temperature range is -20..+70°C, featured with built-in temperature compensation. For temperatures above +25°C do not forget to design in a derating for current.

BUILT-IN CONTROLLER T6963 C

All modules come with controller T 6963C. It is good for direct connection to 8 bit microprocessor system and contains a comfortable command set. There is for example a character set already built-in, which can be extended or redefined in complete. Each character can be attributed with e.g. "invert", "blink" or "invisible".

lin graphic mode on-board display RAM (32kB) provides up to 8 full-screen pages. Text and graphic layer can be displays via "and-", "or-", "exor-" function..

CONNECTION

A 1-row pin header can be soldered into 2.54mm eyelet strip.


Touch Panel

All versions are available with and without touch panel as a standard. Construction is a resistive matrix type. It can be operated with blank finger or stick. Surface is hardened and anti-reflex. resolution is 10x6 fields.

Contrast adjustment



Pin 17 is an output with its -16..-18V. Via external potentiometer contrast can be adjusted then.

Pin	Symbol	Function
1	GND	Ground Potential for logic (0V)
2	VDD	Power supply for logic (+5V)
3	VADJ	Operating voltage for LC driving (input)
4	C/D	L: Data input H: Command input
5	RD	L: Data Read
6	WR	L: Data Write
7..14	DB0..7	Data Bus Line
15	CE	Enable signal (falling edge)
16	RST	L: Reset
17	VO	Output voltage for LC driving (ca. -16V)
18	MD2	Textmode L: 40 columns H: 32 columns
19	FS	Font Select L: 8x8 Font+Graphic H: 6x8 Font
20	NC	Do not connect





DIMENSION

without Touch Panel



all dimensions are in mm

with Touch Panel



all dimensions are in mm



TOUCH PANEL

Built-in touch panel is similar to membrane key switch construction. There are 10x6 matrix areas. Touching a field 1..60 with finger or stick will cause a connection between a column and a row. In example a touch in the area of field #42 will lead to a connection between pin 5 and pin 12. Resistance depends on pressure and may change between 300Ω and 10kΩ. Non

Beispiel										
Pin	16	15	14	13	12	11	10	9	8	7
1	1	2	3	4	5	6	7	8	9	10
2	11	12	13	14	15	16	17	18	19	20
3	21	22	23	24	25	26	27	28	29	30
4	31	32	33	34	35	36	37	38	39	40
5	41	42	43	44	45	46	47	48	49	50
6	51	52	53	54	55	56	57	58	59	60

operated connection is open. Please note that there is a capacity between each lines and columns (about 100pF). Driver voltage may not exceed +5V.

Technische Daten				
Spezifikation	min	typ	max	Einheit
On-Widerstand	300		10.000	Ω
Spannung	0,5		5	V
Schaltstrom	10u		10m	A
Betätigungskraft	150		200	g
Kontaktpellen		10		ms
Temperaturbereich	-30		+75	°C
Lebensdauer	1.000.000			Schaltspiele

Zuordnung Feld-Nr zu Pin										
Pin	16	15	14	13	12	11	10	9	8	7
1	1	2	3	4	5	6	7	8	9	10
2	11	12	13	14	15	16	17	18	19	20
3	21	22	23	24	25	26	27	28	29	30
4	31	32	33	34	35	36	37	38	39	40
5	41	42	43	44	45	46	47	48	49	50
6	51	52	53	54	55	56	57	58	59	60

CONTROLLER T6963

On right hand there's a command table of T6963. Detailed informations you can find at our full data sheet *Manual T696C* at <http://www.lcd-module.de>

Command	Command Code								Description	Remark			
	D7	D6	D5	D4	D3	D2	D1	D0					
Pointer Set	0	0	1	0	0	N2	N1	N0	N2 0 0 1	N1 0 1 0	N0 1 0 0	Cursor pointer set Offset register set Address pointer set	Status Check
Control Word Set	0	1	0	0	0	0	N1	N0	N1 0 0 1 1	N0 0 1 0 1		Text home address set Text area set Graphic home address set Graphic area set	Status Check
Mode Set	1	0	0	0	CG	N2	N1	N0	N2 0 0 0 1	N1 0 0 1 0	N0 0 1 1 0	Graphic and Text; CG=0: ROM, CG=1: RAM OR EXOR AND Text only (attribute capability)	
Display Mode	1	0	0	1	N3	N2	N1	N0				N3=0: Graphic display off N3=1: Graphic display on N2=0: Text display off N2=1: Text display on N1=0: Cursor display off N1=1: Cursor display on N0=0: Cursor blink off N0=1: Cursor blink on	
Cursor Pattern Select	1	0	1	0	0	N2	N1	N0	N2 0 1	N1 0 1	N0 0 1	specifies the number of cursor lines 1 line cursor (bottom line) 8 line cursor (8x8 dot cursor)	
Data Auto Read/Write	1	0	1	1	0	0	N1	N0		N1 0 0	N0 0 1 1	Continuous data can be written or read Data auto write set Data auto read set Auto reset	
Data Read/Write	1	1	0	0	0	N2	N1	N0				Data read/write command for 1 byte N2=0: Address pointer up/down N2=1: Address pointer unchanged N1=0: Address pointer up N1=1: Address pointer down N0=0: Data write N0=1: Data read	
Screen Peeking	1	1	1	0	0	0	0	0				Transfer display data to data stack for read from CPU	Status Check
Screen Copy	1	1	1	0	1	0	0	0				1 line display data which address is indicated by address pointer is copied to graphic RAM area	Status Check
Bit Set/Reset	1	1	1	1	N3	N2	N1	N0				N3=0: Bit reset N3=1: Bit set N2, N1, N0 indicates the bit in the pointed address (000 is LSB)	Status Check

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LCD Graphic Display Modules & Accessories](#) *category:*

Click to view products by [ELECTRONIC ASSEMBLY](#) *manufacturer:*

Other Similar products are found below :

[NA57W001B](#) [HDM64GS12L-Y11S](#) [LCM-H12864GSFH-Y](#) [MGLS-240128-Z05](#) [GLK19264A-7T-1U-TCI-LV-E](#) [DEM 128032A](#) [FGH](#)
[RG12864F-FHW-M](#) [EGLK19264A-7T-WB-VPT-PL](#) [HG2G-V5FT22TF-W](#) [HG1G-4VT22TF-S](#) [HDM64GS24L-2-Y14S](#) [LTS-2301AP](#) [LTS-](#)
[6760P](#) [LTS-6980HR](#) [RG12864A-GHC-V](#) [RG12864A-GHY-V](#) [RG12864A-TIG-V](#) [RG12864A-TIY-V](#) [RG12864A-YHY-X](#) [RG12864B-](#)
[FHW-V](#) [RG12864B-GHW-V](#) [RG12864C-YHW-V](#) [RG12864K-BIW-VBG](#) [RG160128A-TIW-V](#) [RG240128B-YHY-M](#) [RG320240A1-BIW-V](#)
[RG320240B-BIW-V](#) [RG320240B-FHW-V](#) [DEM 097032A](#) [SGH-PY](#) [DEM 122032A](#) [SYH-LY](#) [DEM 122032C](#) [SBH-PW-N-12](#) [DEM 128064A](#)
[SBH-PW-N](#) [DEM 128064B](#) [SBH-PW-N](#) [DEM 128064F](#) [FGH-P\(RGB\)](#) [DEM 128064G](#) [FGH-PW](#) [DEM 128064I](#) [FGH-PW](#) [DEM 128064J](#)
[SBH-PW-N](#) [DEM 128064O](#) [FGH-PW](#) [DEM 128064Q](#) [SBH-PW-N](#) [DEM 128128D](#) [FGH-PW](#) [DEM 240064B](#) [FGH-PW](#) [DEM 240064B](#) [SBH-](#)
[PW-N](#) [DEM 240160A](#) [SBH-PW-N](#) [DEM 320240B](#) [FGH-PW-N](#) [DEM 320240C](#) [FGH-PW](#) [EA W240-7KHLW](#) [RX12864A1-BIW](#)
[RX12864D3-BIW](#) [RX240128A-FGN](#) [RX240128A-TIW](#)