



<b>DATA SHEET</b>	5550 2460
<b>SILVYN® MPC-M</b>	valid from : 21.12.2015

The SILVYN® MPC M is a polyamide conduit gland for smooth and corrugated conduits.  
The hexagonal body with integrated conduit connection enables best assembling.



**Material:** PA 66

**Features:** Dust protection  
Moisture protection  
Tensile strength

**Resistance:** To oil

**Temperature range** -40°C up to +120°C

**Colour** Black (UV-Resistant)  
Grey (RAL 7001)

**Norm Reference:**



**Notes:** Free of halogen, Phosphor and Sulphur

**Protection class** IP 65 up to IP 68

**Dimensions table:**

Part No.	Part name	Total length mm	Smallest inner Ø mm	Largest outer Ø mm	Length of thread mm	SW
<b>black</b>						
5550 2460	SILVYN® MPC-M 16x1,5/1	38	9	24	11	23
5550 2461	SILVYN® MPC-M 16x1,5/2	40	10,5	28	11	25
5550 2462	SILVYN® MPC-M 20x1,5/1	41	10,5	28	14	25
5550 2463	SILVYN® MPC-M 20x1,5/2	43	14,5	33	14	30
5550 2464	SILVYN® MPC-M 25x1,5	45	19	42	15	37
5550 2465	SILVYN® MPC-M 32x1,5/1	46	24,5	45	16	41
5550 2469	SILVYN® MPC-M 32x1,5/2	48	24,5	48	16	45
5550 2466	SILVYN® MPC-M 40x1,5	59	33	60	16	60
5550 2467	SILVYN® MPC-M 50x1,5	55	39	64	16	60
5550 2468	SILVYN® MPC-M 63x1,5	56	48	76	16	73
<b>grey</b>						
5550 2441	SILVYN® MPC-M 16x1,5/1	38	9	24	11	23
5550 2442	SILVYN® MPC-M 16x1,5/2	40	10,5	28	11	25
5550 2443	SILVYN® MPC-M 20x1,5/1	41	10,5	28	14	25
5550 2444	SILVYN® MPC-M 20x1,5/2	43	14,5	33	14	30
5550 2445	SILVYN® MPC-M 25x1,5	45	19	42	15	37
5550 2446	SILVYN® MPC-M 32x1,5/1	46	24,5	45	16	41
5550 2447	SILVYN® MPC-M 32x1,5/2	48	24,5	48	16	45
5550 2448	SILVYN® MPC-M 40x1,5	59	33	60	16	60
5550 2449	SILVYN® MPC-M 50x1,5	55	39	64	16	60
5550 2439	SILVYN® MPC-M 63x1,5	56	48	76	16	73

elaborated by: PDP: M. Auch	Document: DB55502460_3EN	page 1 von 2
--------------------------------	--------------------------	--------------



<b>DATA SHEET</b>	5550 2460
<b>SILVYN<sup>®</sup> MPC-M</b>	valid from : 21.12.2015

**Suitable**

- SILVYN<sup>®</sup> SI
- SILVYN<sup>®</sup> SP
- SILVYN<sup>®</sup> SP-PU
- SILVYN<sup>®</sup> EL waved/smooth
- SILVYN<sup>®</sup> ELU waved/smooth
- SILVYN<sup>®</sup> ELÖ waved/smooth
- SILVYN<sup>®</sup> ELT waved/smooth
- SILVYN<sup>®</sup> ELR smooth

**Allocation table:**

Conduit	 <b>SILVYN<sup>®</sup> SI</b>	 <b>SILVYN<sup>®</sup> SP/ SP-PU</b>	 <b>SILVYN<sup>®</sup> EL/ELÖ/ELT/ELR/ELU</b>
SILVYN <sup>®</sup> MPC-M 16x1,5/1	11x14		12
SILVYN <sup>®</sup> MPC-M 16x1,5/2	13x16	12x16	16
SILVYN <sup>®</sup> MPC-M 20x1,5/1	13x16	12x16	16
SILVYN <sup>®</sup> MPC-M 20x1,5/2		16x20	20
SILVYN <sup>®</sup> MPC-M 25x1,5		22x27	25
SILVYN <sup>®</sup> MPC-M 32x1,5/1			30
SILVYN <sup>®</sup> MPC-M 32x1,5/2			32
SILVYN <sup>®</sup> MPC-M 40x1,5			40
SILVYN <sup>®</sup> MPC-M 50x1,5			50
SILVYN <sup>®</sup> MPC-M 63x1,5		49x56	63

For more information please see our current catalogue.

Please do not hesitate to contact our laboratory if there any questions regarding resistance against aggressive agents and special oils.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Conduit Fittings & Accessories](#) category:*

*Click to view products by [Lapp Kabel](#) manufacturer:*

Other Similar products are found below :

[S53.35A](#) [260-416](#) [DM0240-1/2A](#) [817.612.0](#) [55506625](#) [1.511.2001.50](#) [1.533.1601.50](#) [1.533.2001.50](#) [52005810](#) [817.716.0](#) [712.015.0](#) [216-420](#) [2276](#) [2663-P](#) [C2070-P](#) [3582V](#) [2643-P](#) [4975](#) [2644-P](#) [90480](#) [2404-P](#) [1047561](#) [2723-P](#) [55506355](#) [1.513.1101.14](#) [55502461](#) [55502462](#) [55502463](#) [55502464](#) [55502473](#) [166-22214](#) [166-22215](#) [166-24800](#) [166-25801](#) [166-30318](#) [SHR-C1](#) [2037 12-20 LGR](#) [2037 16-24 LGR](#) [HP50SS](#) [55502470](#) [SH PA6 BL ND10](#) [5308 946](#) [295.012.0](#) [2955 M16](#) [2955 M25](#) [2955 M32](#) [2955 M40](#) [297.212.0](#) [297.240.0](#) [298.012.0](#)