

BERGSTAK® 0.8MM MEZZANINE CONNECTORS

Extra-ordinary Product Range; Benchmark Performance; Dual-source Champion

DESCRIPTION

Versatile, high density parallel-board-to-board connector system offers twelve PCB stack heights in nine sizes up to two hundred positions.

Stack height flexibility supports evolving designs and emerging mechanical requirements with a common mating interface.

Special housing and blade-on-beam terminal features provide easy PCB assembly, worry-free mating and long-term reliability.



FEATURES & BENEFITS

- 0.8mm double-row contact pitch conserves printed circuit board space
- Vast range of sizes and stack heights support diverse electronic packaging schemes
 - 40 to 200 position sizes in 20 position increments
 - 5mm to 16mm stack heights in 1mm increments
- Choice of gold-based and palladium-based platings provide protection in different environments and applications
- Tapered PCB locator pegs increase the ease and accuracy of hand assembly
- Blade-on-beam contacts allow peeling for safer, easier un-mating
- Tape and Reel packaging supports high speed automated assembly
- Optimize from Gen.2 to Gen.3 high speed performance on some stack heights
- Fully inter-matable with similar competitive connectors

PLUS


- Optimized "blade-on-beam" contact mating maximizes connection integrity
 - Early receptacle contact point increases mating wipe and allows early engagement/late disengagement
 - Precision-tapered contacts control mating stress while providing reliable, high normal force
 - Coined contact tips assure smooth, safe wiping action during connector mating
 - Connector polarization, generous lead-in angles and precise contact positioning ensure precise mating alignment and reliability

TARGET MARKETS / APPLICATIONS

- Routers
- Servers
- Telecom/Datacom equipment
- Office equipment
- IP phones
- Test and Measurement
- Point-of-Sale terminals
- Portable industrial terminals


RECEPTACLE

Precision-tapered contacts control mating stress while providing reliable, high normal force




Early-contact point allows early engagement / late disengagement and increases mating wipe

PLUG



Coined contact tips assure smooth, safe wiping action during connector mating

PART NUMBER SELECTOR



HEIGHT SELECTOR

		PLUGS			
		61083-XX1XXXXX	61083-XX2XXXXX	61083-XX3XXXXX	61083-XX4XXXXX
RECEPTACLES	61082-XX1XXXXX 3.70 mm (0.146 in.)				
	61082-XX2XXXXX 7.70 mm (0.303 in.)				
	61082-XX3XXXXX 11.70 mm (0.461 in.)				
		STACK			
		HEIGHTS			

For special additional options and updates, consult drawings at www.fci.com/bergstak

TECHNICAL INFORMATION

MATERIALS

- Housing
 - Glass filled LCP (UL94 V-0)
- Contact base metal
 - Receptacles: Copper Alloy, High Spring
 - Plugs: Brass
- Contact area finish
 - Gold or Gold flash over palladium-nickel (GXT) over nickel
- Solder area finish
 - Matte pure tin over nickel

MECHANICAL PERFORMANCE

- Durability: 100 cycles
- Mating force: 0.9N (90 gramf) maximum/contact
- Un-mating force: 0.1N (10 gramf) minimum/contact

ENVIRONMENTAL

- Temperature range: -40°C to +85°C
- High temperature life: 105°C +/- 5°C for 1000 hours
- Humidity: 90-95% relative humidity for 96 hours
- Mixed Flowing Gas Class 2a (30 GXT)

SPECIFICATION

- GS-12-547 BergStak 0.8mm Product Specification
- GS-29-010 Test report, Competitive inter-mating

ELECTRICAL PERFORMANCES

- Insulation resistance:
 - Initial: 1000 MΩ minimum
 - After test: 100 MΩ minimum
- Current rating:
 - 0.8 amp/contact
- Contact resistance:
 - Initial: 30 mΩ maximum
 - After test: 50 mΩ maximum
- Voltage rating:
 - 100 V AC
- Signal Integrity
(Differential pairs, connector and SMT pads only)
 - Impedance Range: 81 to 108 ohms @ 50 ps edge (10-90%)
 - Return Loss: < 10 dB up to 5 GHz
 - Insertion Loss: < 1.5 dB up to 5 GHz
 - NEXT: ≤ 4.0% for a 50 ps edge (10-90%)
 - FEXT: ≤ 2.4% for a 50 ps edge (10-90%)
 - S Parameter models available at www.fci.com/bergstak

APPROVALS AND CERTIFICATIONS

- UL certificate, file no. E66906
- CSA, file no. LR46923

PACKAGING

- Tape and reel
- Tubes

The PCIe® mark is a registered trademark of the PCI-SIG Corp



Choose precisely what you need from FCI's MezzSelect™ product portfolio.

In-line and array-configured connectors satisfy a wide range of low-to-high pin count and low-to-high speed applications in many electronics segments.

The MezzSelect™ Connector Family is supported by simple, powerful web-based design tools and other resources to help customers expedite connector design work and improve time-to-market.

www.mezzselect.com

Please note that the information in this datasheet is subject to change without notice.
Visit www.fciconnect.com/bergstak for additional technical information.

www.fci.com
www.fciconnect.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[10135583-642402LF](#) [89885-310LF](#) [589158040000018](#) [6-1393048-0](#) [68683-613](#) [MDF7-12DP-2.54DSA](#) [MDF7-18P-2.54DSA\(01\)](#) [MDF7-20DP-2.54DSA](#) [MDF7-26D-2.54DSA\(55\)](#) [MDF7-3P-2.54DSA\(01\)](#) [MDF7B-3P-2.54DSA\(55\)](#) [MDF7C-11P-2.54DSA\(55\)](#) [MDF7C-18P-2.54DSA\(55\)](#) [MDF7C-5P-2.54DSA\(01\)](#) [MDF7P-5P-2.54DSA\(55\)](#) [75234-0516](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-360C008-C](#) [FCN-360C040-C](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [93696-325LF](#) [11828-1FA](#) [AXK630345P](#) [18097-0013](#) [ICA-328STT](#) [2007042-2](#) [304400-2](#) [FCN-214Q030-G/0](#) [FCN-215Q040-G/0](#) [FCN-230C068-ESA](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [FCN-360A3](#) [FCN-360C040-B](#) [210-93-314-41-105000](#) [2-22603-0](#) [379-064-521-202](#) [MDF7-12P-2.54DSA\(01\)](#) [MDF7-16P-2.54DS\(56\)](#) [MDF7-40DP-2.54DSA\(55\)](#) [MDF7-8P-2.54DSA\(55\)](#) [MDF7B-16P-2.54DSA\(55\)](#) [AXG720047](#) [5031084030](#)