



## TECHNICAL DATA

# 2763

## PVC Adhesive Tape

### DESCRIPTION

**Scapa 2763** is a plasticized PVC tape, single coated with a rubber adhesive.  
**Scapa 2763** is available in black and yellow.

### APPLICATIONS

- Wrapping of automotive electrical wiring harnesses
- Hand application
- Product designed for applications which require a good temperature resistance, class T2 (105°C)

### PRODUCT BENEFITS

- Tough, flexible and conformable
- Easy and smooth unwind
- Self-extinguishing on harness
- Lead free
- Conforms to European Directive 2000/53/EC for End of Vehicle Life (ELV) recycling (does not contain heavy metals)
- Operating temperature between -30°C to +105°C

## TECHNICAL PROPERTIES

	<b>Unit</b>	<b>Nominal Value</b>	<b>Test Method</b>
Thickness	mm	0.11	AFERA 5006
Tensile Strength	N/cm	25	AFERA 5004
Elongation at Break	%	180	AFERA 5004
Peel Adhesion to Steel	N/cm	1.5	AFERA 5001
Peel Adhesion to Backing	N/cm	1.5	AFERA 5001
Flame Resistance	/	Self-extinguishing Type B	RENAULT/PSA

## STANDARD PRESENTATION

- Roll length: 33metres
- Roll width: 9, 12, 19, 25 and 30mm
- Core: 38mm – Scapa branded cardboard core
- Packaging: Cardboard – Towerpack
- Colours: Black and yellow

## RECOMMENDATIONS

*Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +5°C and +25°C. A strict use-by date of 24 months from the date of manufacture is recommended.*

*The tape should be applied with sufficient tension and a minimum of two layers with a half overlap to ensure optimum bonding. The final layer should be wrapped with a lower tension to prevent flagging effects.*

*Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.*

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Adhesive Tapes](#) category:*

*Click to view products by [Scapa](#) manufacturer:*

Other Similar products are found below :

[PF24.0W](#) [4718](#) [4516-1/4x36](#) [56-YELLOW-34"X72YD](#) [00-021200-13972-7](#) [021200-64630](#) [60 TAPE \(1"\)](#) [62-GRAY-12"X36YD](#) [62-GRAY-1"X36YD](#) [69-1"X36YD](#) [764-1"x36yd-Red](#) [764-1"x36yd-White](#) [PG ASSY](#) [926-1/4X18YD](#) [967454-1](#) [1194-14"X36YD](#) [1181 19MM X 16,5 METERS](#) [1182-7.7X10](#) [1245-34"X18YD](#) [1267](#) [130C-1X15FT](#) [130-1x10FT](#) [1345-3/8x18yrd](#) [1380-2"X8"](#) [E39-RS1-CA](#) [1900-48mm](#) [22-1/2X36YD](#) [2229-P-2-1/2x3-3/4](#) [88-SUPER-34X44FT](#) [890103N001](#) [2670](#) [SJ3527N-Black-1.5"x50yd](#) [EVK-TA-TM047NBH01](#) [AD-UCUSB-DCAUD-SPL](#) [20-1"X60YDS](#) [2020-18mmx55m](#) [H150](#) [3900-Blue](#) [3939-24mmx55m](#) [396-1"x36yd](#) [4016-34"x36yd](#) [4462W-12"x72yd](#) [44-TAN-14"X90YD](#) [4504-34x18](#) [471-Trans-1"x36yd-Bulk](#) [5414 34X36](#) [C-22](#) [35-Gray-1/2](#) [371-Tan-48mmx50m](#) [4008-12"X36YD](#)