


Purpose

SEP-03 is used for galvanic isolation devices connected via a USB cable. Provides surge protection devices HOST, eg. PC from external devices that are connected directly to the power grids, industrial power supply systems or high-voltage measurement. If you connect an external power amplifier is used as the transmitted signal and increases the efficiency of current up to 1A for the connected devices.





power

power	
USB	5V DC
Uopt	12÷30V DC
load current	
USB	<400mA
Uopt	<1A
USB standard	1.1 / 2.0
speed	
low speed	1,5Mbps
full speed	12Mbps
types of connectors	1×A / 1×B
galvanic isolation	
tracks A -> B	5kV RMS
UUSB -> tracks A/B	1kV DC
Uopt -> tracks A/B	none
working temperature	-25÷40°C
terminal	screw terminals 2,5mm ²
tightening torque	0,4Nm
dimensions	1 module (18mm)
mounting	on TH-35 rail
degree of protection	IP20

- 1 -

D141212

- 2 -

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Measuring Tools category:

Click to view products by F&F manufacturer:

Other Similar products are found below :

 G336
 M225203-01
 G426
 G1333
 G1327
 G1154
 G1150
 G1152
 G1153
 G1155
 G1009
 1051-03
 121010D
 121050D
 25541
 8255

 NF-221200130
 20323
 20329
 20363
 20365
 20515
 20516
 G800
 G1229
 5205000
 5206000
 5223000
 6921000
 YT-30061
 W002900

 W061008
 W061009
 W061010
 W062004
 W066005
 W066006
 15225
 16135
 16456
 17215
 17218
 17271
 17670
 17672
 17677
 17953

 18115
 18879