

# NB6L16

## 2.5 V / 3.3 V Multilevel Input to Differential LVPECL/LVNECL Clock or Data Receiver/ Driver/Translator Buffer

### Description

The NB6L16 is a high precision, low power ECL differential clock or data receiver/driver/translator buffer. The device is functionally equivalent to the EL16, EP16, LVEL16 and NBSG16 devices. With output transition times of 70 ps, it is ideally suited for high frequency, low power systems. The device is targeted for Backplane buffering, GbE clock/data distribution, Fibre Channel distribution and SONET clock/data distribution applications.

Input accept LVNECL (Negative ECL), LVPECL (Positive ECL), LVTTTL, LVCMOS, CML, or LVDS. Outputs are 800 mV ECL signals.

The  $V_{BB}$  pin, an internally generated voltage supply, is available to this device only. For single-ended input conditions, the unused differential input is connected to  $V_{BB}$  as a switching reference voltage.  $V_{BB}$  may also rebias AC coupled inputs. When used, decouple  $V_{BB}$  and  $V_{CC}$  via a 0.01  $\mu$ F capacitor and limit current sourcing or sinking to 0.5 mA. When not used,  $V_{BB}$  should be left open.

### Features

- Input Clock Frequency  $\geq 6$  GHz
- Input Data Rate Frequency  $\geq 6$  Gb/s
- Low 12 mA Typical Power Supply Current
- 70 ps Typical Rise/Fall Times
- 130 ps Input Propagation Delay
- On-Chip Reference for ECL Single-Ended Input –  $V_{BB}$  Output
- PECL Mode Operating Range:  
 $V_{CC} = 2.375$  V to 3.465 V with  $V_{EE} = 0$  V
- NECL Mode Operating Range:  
 $V_{CC} = 0$  V with  $V_{EE} = -2.375$  V to  $-3.465$  V
- Open Input Default State
- LVDS, LVPECL, LVNECL, LVCMOS, LVTTTL and CML Input Compatible
- These Devices are Pb-Free, Halogen Free and are RoHS Compliant



ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)




SOIC-8 NB  
D SUFFIX  
CASE 751-07




TSSOP-8  
DT SUFFIX  
CASE 948R-02

### MARKING DIAGRAMS\*



SOIC-8 NB



TSSOP-8

- A = Assembly Location
- L = Wafer Lot
- Y = Year
- W = Work Week
- = Pb-Free Package


(Note: Microdot may be in either location)  
\*For additional marking information, refer to Application Note [AND8002/D](#).

### ORDERING INFORMATION

| Device      | Package                | Shipping†        |
|-------------|------------------------|------------------|
| NB6L16DG    | SOIC-8 NB<br>(Pb-Free) | 98 Units / Tube  |
| NB6L16DR2G  | SOIC-8 NB<br>(Pb-Free) | 2500 Tape & Reel |
| NB6L16DTG   | TSSOP-8<br>(Pb-Free)   | 100 Units / Tube |
| NB6L16DTR2G | TSSOP-8<br>(Pb-Free)   | 2500 Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, [BRD8011/D](#).

## NB6L16



**Figure 1. Pinout (Top View) and Logic Diagram**

**Table 1. PIN DESCRIPTION**

| Pin | Name      | I/O   | Default State | Description  |
|-----|-----------|---|---------------|--|
| 1   | NC        | –   | –             | No Connect. The NC pin is electrically connected to the die and <b>MUST</b> be left open.                        |
| 2   | D         | LVDS, CML, LVPECL, LVNECL, LVTTTL, LVCMOS Input | LOW           | Non-inverted differential clock/data input. Internal 75 k $\Omega$ to $V_{CC}$ and 37.5 k $\Omega$ to $V_{EE}$ . |
| 3   | $\bar{D}$ | LVDS, CML, LVPECL, LVNECL, LVTTTL, LVCMOS Input | HIGH          | Inverted differential clock/data input. Internal 37.5 k $\Omega$ to $V_{CC}$ and 75 k $\Omega$ to $V_{EE}$ .     |
| 4   | $V_{BB}$  | –   | –             | Internally generated ECL reference voltage supply.   |
| 5   | $V_{EE}$  | –   | –             | Negative power supply voltage.   |
| 6   | $\bar{Q}$ | ECL Output                                      |               | Inverted differential ECL output. Typically terminated with 50 $\Omega$ resistor to $V_{CC} - 2.0$ V.            |
| 7   | Q         | ECL Output                                      |               | Non-inverted differential ECL output. Typically terminated with 50 $\Omega$ resistor to $V_{CC} - 2.0$ V.        |
| 8   | $V_{CC}$  | –   | –             | Positive power supply voltage.   |

**Table 2. ATTRIBUTES**

| Characteristics   | Value                       |
|---|-----------------------------|
| Internal Input Default State Resistor (R1)                                  | 37.5 k $\Omega$             |
| Internal Input Default State Resistor (R2)                                  | 75 k $\Omega$               |
| ESD Protection<br>Human Body Model<br>Machine Model<br>Charged Device Model | > 2 kV<br>> 100 V<br>> 1 kV |
| Moisture Sensitivity, Indefinite Time Out of Drypack (Note 1)               | Pb-Free Pkg                 |
| SOIC–8 NB<br>TSSOP–8  | Level 1<br>Level 3          |
| Flammability Rating<br>Oxygen Index: 28 to 34                               | UL 94 V–0 @ 1.125 in        |
| Transistor Count  | 167                         |
| Meets or exceeds JEDEC Spec EIA/JESD78 IC Latchup Test                      |                             |

1. For additional information, see Application Note [AND8003/D](#).

# NB6L16

**Table 3. MAXIMUM RATINGS**

| Symbol        | Parameter  | Condition 1   | Condition 2  | Rating                     | Units                       |
|---------------|--|---|--|----------------------------|-----------------------------|
| $V_{CC}$      | PECL Mode Power Supply                             | $V_{EE} = 0\text{ V}$   |  | 3.6                        | V                           |
| $V_{EE}$      | NECL Mode Power Supply                             | $V_{CC} = 0\text{ V}$   |  | -3.6                       | V                           |
| $V_I$         | PECL Mode Input Voltage<br>NECL Mode Input Voltage | $V_{EE} = 0\text{ V}$<br>$V_{CC} = 0\text{ V}$                          | $V_I \leq V_{CC}$<br>$V_I \geq V_{EE}$   | 3.6<br>-3.6                | V                           |
| $I_{out}$     | Output Current                                     | Continuous<br>Surge   |  | 25<br>50                   | mA                          |
| $V_{INPP}$    | Differential Input Voltage $ D - \bar{D} $         | $V_{CC} - V_{EE} \geq 2.8\text{ V}$<br>$V_{CC} - V_{EE} < 2.8\text{ V}$ |  | 2.8<br>$ V_{CC} - V_{EE} $ | V                           |
| $I_{BB}$      | $V_{BB}$ Sink/Source                               |   |  | $\pm 0.5$                  | mA                          |
| $T_A$         | Operating Temperature Range                        |   |  | -40 to +85                 | $^{\circ}\text{C}$          |
| $T_{stg}$     | Storage Temperature Range                          |   |  | -65 to +150                | $^{\circ}\text{C}$          |
| $\theta_{JA}$ | Thermal Resistance (Junction-to-Ambient)           | 0 lfpm<br>500 lfpm  | SOIC-8 NB<br>SOIC-8 NB   | 190<br>130                 | $^{\circ}\text{C}/\text{W}$ |
| $\theta_{JC}$ | Thermal Resistance (Junction-to-Case)              | Standard Board  | SOIC-8 NB  | 41 to 44                   | $^{\circ}\text{C}/\text{W}$ |
| $\theta_{JA}$ | Thermal Resistance (Junction-to-Ambient)           | 0 lfpm<br>500 lfpm  | TSSOP-8<br>TSSOP-8   | 185<br>140                 | $^{\circ}\text{C}/\text{W}$ |
| $\theta_{JC}$ | Thermal Resistance (Junction-to-Case)              | Standard Board  | TSSOP-8  | 41 to 44                   | $^{\circ}\text{C}/\text{W}$ |
| $T_{sol}$     | Wave Solder  | Standard<br>Pb-Free   | $\leq 3\text{ sec @ } 248^{\circ}\text{C}$<br>$\leq 3\text{ sec @ } 260^{\circ}\text{C}$ | 265<br>265                 | $^{\circ}\text{C}$          |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

# NB6L16

**Table 4. DC CHARACTERISTICS, PECL** ( $V_{CC} = 2.5\text{ V}$ ,  $V_{EE} = 0\text{ V}$  (Note 3))

| Symbol   | Characteristic                         | -40°C |      |      | 25°C |      |      | 85°C |      |      | Unit |
|----------|--|-------|------|------|------|------|------|------|------|------|------|
|          |  | Min   | Typ  | Max  | Min  | Typ  | Max  | Min  | Typ  | Max  |      |
| $I_{EE}$ | Negative Power Supply Current (Note 4) | 10    | 12   | 18   | 10   | 12   | 18   | 10   | 12   | 18   | mA   |
| $V_{OH}$ | Output HIGH Voltage (Note 5)           | 1350  | 1450 | 1550 | 1400 | 1500 | 1600 | 1450 | 1550 | 1650 | mV   |
| $V_{OL}$ | Output LOW Voltage (Note 5)            | 565   | 725  | 870  | 630  | 765  | 920  | 690  | 825  | 970  | mV   |

**DIFFERENTIAL INPUT DRIVEN Single-Ended** ((Figures 10, 12) (Note 7))

|          |  |                 |  |                 |                 |  |                 |                 |  |                 |    |
|----------|--|-----------------|--|-----------------|-----------------|--|-----------------|-----------------|--|-----------------|----|
| $V_{th}$ | Input Threshold Reference Voltage Range (Notes 1, 6) | 1125            |  | $V_{CC}$<br>-75 | 1125            |  | $V_{CC}$<br>-75 | 1125            |  | $V_{CC}$<br>-75 | mV |
| $V_{IH}$ | Single-Ended Input HIGH Voltage                      | $V_{th}$<br>+75 |  | $V_{CC}$        | $V_{th}$<br>+75 |  | $V_{CC}$        | $V_{th}$<br>+75 |  | $V_{CC}$        | mV |
| $V_{IL}$ | Single-Ended Input LOW Voltage                       | $V_{EE}$        |  | $V_{th}$<br>-75 | $V_{EE}$        |  | $V_{th}$<br>-75 | $V_{EE}$        |  | $V_{th}$<br>-75 | mV |

**DIFFERENTIAL INPUTS DRIVEN DIFFERENTIALLY** ((Figures 11, 13) (Note 8))

|           |   |              |           |                 |              |           |                 |              |           |                 |               |
|-----------|---|--------------|-----------|-----------------|--------------|-----------|-----------------|--------------|-----------|-----------------|---------------|
| $V_{IHD}$ | Differential Input HIGH Voltage                                     | 1200         |           | $V_{CC}$        | 1200         |           | $V_{CC}$        | 1200         |           | $V_{CC}$        | mV            |
| $V_{ILD}$ | Differential Input LOW Voltage                                      | $V_{EE}$     |           | $V_{CC}$<br>-75 | $V_{EE}$     |           | $V_{CC}$<br>-75 | $V_{EE}$     |           | $V_{CC}$<br>-75 | mV            |
| $V_{CMR}$ | Input Common Mode Range (Differential Cross-Point Voltage) (Note 2) | 950          |           | $V_{CC}$<br>-38 | 950          |           | $V_{CC}$<br>-38 | 950          |           | $V_{CC}$<br>-38 | mV            |
| $V_{ID}$  | Differential Input Voltage ( $V_{IHD} - V_{ILD}$ )                  | 75           |           | 2500            | 75           |           | 2500            | 75           |           | 2500            | mV            |
| $I_{IH}$  | Input HIGH Current<br>D<br>$\bar{D}$                                |              | 50<br>10  | 150<br>150      |              | 50<br>10  | 150<br>150      |              | 50<br>10  | 150<br>150      | $\mu\text{A}$ |
| $I_{IL}$  | Input LOW Current<br>D<br>$\bar{D}$                                 | -150<br>-150 | -5<br>-30 |                 | -150<br>-150 | -5<br>-30 |                 | -150<br>-150 | -5<br>-30 |                 | $\mu\text{A}$ |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

1.  $V_{th}$  is applied to the complementary input when operating in Single-Ended mode.
2.  $V_{CMR}$  minimum varies 1:1 with  $V_{EE}$ ,  $V_{CMR}$  maximum varies 1:1 with  $V_{CC}$ .
3. Input and output parameters vary 1:1 with  $V_{CC}$ .  $V_{EE}$  can vary +0.125 V to -1.3 V.
4. All input and output pins left open.
5. All loading with 50  $\Omega$  to  $V_{CC} - 2.0\text{ V}$ .
6. Do not use  $V_{BB}$  as a reference voltage for Single-Ended PECL signals when operating device at  $V_{CC} - V_{EE} < 3.0\text{ V}$ .
7.  $V_{th}$ ,  $V_{IH}$ , and  $V_{IL}$  parameters must be complied with simultaneously.
8.  $V_{IHD}$ ,  $V_{ILD}$ ,  $V_{ID}$  and  $V_{CMR}$  parameters must be complied with simultaneously.

# NB6L16

**Table 5. DC CHARACTERISTICS, PECL** ( $V_{CC} = 3.3\text{ V}$ ,  $V_{EE} = 0\text{ V}$  (Note 3))

| Symbol   | Characteristic                         | -40°C |      |      | 25°C |      |      | 85°C |      |      | Unit |
|----------|--|-------|------|------|------|------|------|------|------|------|------|
|          |  | Min   | Typ  | Max  | Min  | Typ  | Max  | Min  | Typ  | Max  |      |
| $I_{EE}$ | Negative Power Supply Current (Note 4) | 10    | 12   | 18   | 10   | 12   | 18   | 10   | 12   | 18   | mA   |
| $V_{OH}$ | Output HIGH Voltage (Note 5)           | 2150  | 2250 | 2350 | 2200 | 2300 | 2400 | 2250 | 2350 | 2450 | mV   |
| $V_{OL}$ | Output LOW Voltage (Note 5)            | 1365  | 1525 | 1670 | 1430 | 1565 | 1720 | 1490 | 1625 | 1770 | mV   |

**DIFFERENTIAL INPUT DRIVEN Single-Ended** ((Figures 10, 12) (Note 6))

|          |  |               |      |               |               |      |               |               |      |               |    |
|----------|--|---------------|------|---------------|---------------|------|---------------|---------------|------|---------------|----|
| $V_{th}$ | Input Threshold Reference Voltage Range (Note 1) | 1125          |      | $V_{CC} - 75$ | 1125          |      | $V_{CC} - 75$ | 1125          |      | $V_{CC} - 75$ | mV |
| $V_{IH}$ | Single-Ended Input HIGH Voltage                  | $V_{th} + 75$ |      | $V_{CC}$      | $V_{th} + 75$ |      | $V_{CC}$      | $V_{th} + 75$ |      | $V_{CC}$      | mV |
| $V_{IL}$ | Single-Ended Input LOW Voltage                   | $V_{EE}$      |      | $V_{th} - 75$ | $V_{EE}$      |      | $V_{th} - 75$ | $V_{EE}$      |      | $V_{th} - 75$ | mV |
| $V_{BB}$ | Output Voltage Reference                         | 1880          | 1980 | 2070          | 1880          | 1980 | 2070          | 1880          | 1980 | 2070          | mV |

**DIFFERENTIAL INPUTS DRIVEN DIFFERENTIALLY** ((Figures 11, 13) (Note 7))

|           |   |              |           |               |              |           |               |              |           |               |               |
|-----------|---|--------------|-----------|---------------|--------------|-----------|---------------|--------------|-----------|---------------|---------------|
| $V_{IHD}$ | Differential Input HIGH Voltage                                     | 1200         |           | $V_{CC}$      | 1200         |           | $V_{CC}$      | 1200         |           | $V_{CC}$      | mV            |
| $V_{ILD}$ | Differential Input LOW Voltage                                      | $V_{EE}$     |           | $V_{CC} - 75$ | $V_{EE}$     |           | $V_{CC} - 75$ | $V_{EE}$     |           | $V_{CC} - 75$ | mV            |
| $V_{CMR}$ | Input Common Mode Range (Differential Cross-Point Voltage) (Note 2) | 950          |           | $V_{CC} - 38$ | 950          |           | $V_{CC} - 38$ | 950          |           | $V_{CC} - 38$ | mV            |
| $V_{ID}$  | Differential Input Voltage ( $V_{IHD} - V_{ILD}$ )                  | 75           |           | 2500          | 75           |           | 2500          | 75           |           | 2500          | mV            |
| $I_{IH}$  | Input HIGH Current<br>D<br>$\bar{D}$                                |              | 50<br>10  | 150<br>150    |              | 50<br>10  | 150<br>150    |              | 50<br>10  | 150<br>150    | $\mu\text{A}$ |
| $I_{IL}$  | Input LOW Current<br>D<br>$\bar{D}$                                 | -150<br>-150 | -5<br>-30 |               | -150<br>-150 | -5<br>-30 |               | -150<br>-150 | -5<br>-30 |               | $\mu\text{A}$ |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lpm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

1.  $V_{th}$  is applied to the complementary input when operating in Single-Ended mode.
2.  $V_{CMR}$  minimum varies 1:1 with  $V_{EE}$ ,  $V_{CMR}$  maximum varies 1:1 with  $V_{CC}$ .
3. Input and output parameters vary 1:1 with  $V_{CC}$ .  $V_{EE}$  can vary +0.925 V to -0.5 V.
4. All input and output pins left open.
5. All loading with 50  $\Omega$  to  $V_{CC} - 2.0\text{ V}$ .
6.  $V_{th}$ ,  $V_{IH}$ , and  $V_{IL}$  parameters must be complied with simultaneously.
7.  $V_{IHD}$ ,  $V_{ILD}$ ,  $V_{ID}$  and  $V_{CMR}$  parameters must be complied with simultaneously.

# NB6L16

**Table 6. DC CHARACTERISTICS, NECL** ( $V_{CC} = 0\text{ V}$ ,  $V_{EE} = -3.465\text{ V}$  to  $-2.375\text{ V}$  (Note 3))

| Symbol   | Characteristic                         | -40°C |       |       | 25°C  |       |       | 85°C  |       |       | Unit |
|----------|--|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
|          |  | Min   | Typ   | Max   | Min   | Typ   | Max   | Min   | Typ   | Max   |      |
| $I_{EE}$ | Negative Power Supply Current (Note 5) | 10    | 12    | 18    | 10    | 12    | 18    | 10    | 12    | 18    | mA   |
| $V_{OH}$ | Output HIGH Voltage (Note 4)           | -1150 | -1050 | -950  | -1100 | -1000 | -900  | -1050 | -950  | -850  | mV   |
| $V_{OL}$ | Output LOW Voltage (Note 4)            | -1935 | -1775 | -1630 | -1870 | -1735 | -1580 | -1810 | -1675 | -1530 | mV   |

**DIFFERENTIAL INPUT DRIVEN Single-Ended** ((Figures 10, 12) (Note 6))

|          |  |                |       |              |                |       |              |                |       |              |    |
|----------|--|----------------|-------|--------------|----------------|-------|--------------|----------------|-------|--------------|----|
| $V_{th}$ | Input Threshold Reference Voltage Range (Note 1) | $V_{EE} +1125$ |       | $V_{CC} -75$ | $V_{EE} +1125$ |       | $V_{CC} -75$ | $V_{EE} +1125$ |       | $V_{CC} -75$ | mV |
| $V_{IH}$ | Single-Ended Input HIGH Voltage                  | $V_{th} +75$   |       | $V_{CC}$     | $V_{th} +75$   |       | $V_{CC}$     | $V_{th} +75$   |       | $V_{CC}$     | mV |
| $V_{IL}$ | Single-Ended Input LOW Voltage                   | $V_{EE}$       |       | $V_{th} -75$ | $V_{EE}$       |       | $V_{th} -75$ | $V_{EE}$       |       | $V_{th} -75$ | mV |
| $V_{BB}$ | Output Voltage Reference                         | -1420          | -1320 | -1230        | -1420          | -1320 | -1230        | -1420          | -1320 | -1230        | mV |

**DIFFERENTIAL INPUTS DRIVEN DIFFERENTIALLY** ((Figures 11, 13) (Note 7))

|           |   |                |           |              |                |              |              |                |           |              |               |
|-----------|---|----------------|-----------|--------------|----------------|--------------|--------------|----------------|-----------|--------------|---------------|
| $V_{IHD}$ | Differential Input HIGH Voltage                                     | $V_{EE} +1200$ |           | $V_{CC}$     | $V_{EE} +1200$ |              | $V_{CC}$     | $V_{EE} +1200$ |           | $V_{CC}$     | mV            |
| $V_{ILD}$ | Differential Input LOW Voltage                                      | $V_{EE}$       |           | $V_{CC} -75$ | $V_{EE}$       |              | $V_{CC} -75$ | $V_{EE}$       |           | $V_{CC} -75$ | mV            |
| $V_{CMR}$ | Input Common Mode Range (Differential Cross-Point Voltage) (Note 2) | $V_{EE} +950$  |           | $V_{CC} -38$ | $V_{EE} +950$  |              | $V_{CC} -38$ | $V_{EE} +950$  |           | $V_{CC} -38$ | mV            |
| $V_{ID}$  | Differential Input Voltage ( $V_{IHD} - V_{ILD}$ )                  | 75             |           | 2500         | 75             |              | 2500         | 75             |           | 2500         | mV            |
| $I_{IH}$  | Input HIGH Current<br>$\frac{D}{\bar{D}}$                           |                | 50<br>10  | 150<br>150   |                | 50<br>10     | 150<br>150   |                | 50<br>10  | 150<br>150   | $\mu\text{A}$ |
| $I_{IL}$  | Input LOW Current<br>$\frac{D}{\bar{D}}$                            | -150<br>-150   | -5<br>-30 | -150<br>-150 | -5<br>-30      | -150<br>-150 | -5<br>-30    | -150<br>-150   | -5<br>-30 | -150<br>-150 | $\mu\text{A}$ |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

1.  $V_{th}$  is applied to the complementary input when operating in Single-Ended mode.
2.  $V_{CMR}$  minimum varies 1:1 with  $V_{EE}$ ,  $V_{CMR}$  maximum varies 1:1 with  $V_{CC}$ .
3. Input and output parameters vary 1:1 with  $V_{CC}$ .
4. All loading with  $50\ \Omega$  to  $V_{CC} - 2.0\text{ V}$ .
5. All input and output pins left open.
6.  $V_{th}$ ,  $V_{IH}$ , and  $V_{IL}$  parameters must be complied with simultaneously.
7.  $V_{IHD}$ ,  $V_{ILD}$ ,  $V_{ID}$  and  $V_{CMR}$  parameters must be complied with simultaneously.


# NB6L16

**Table 7. AC CHARACTERISTICS** ( $V_{CC} = 0\text{ V}$ ;  $V_{EE} = -3.465\text{ V}$  to  $-2.375\text{ V}$  or  $V_{CC} = 2.375\text{ V}$  to  $3.465\text{ V}$ ;  $V_{EE} = 0\text{ V}$  (Note 1))


| Symbol                   | Characteristic   | -40°C      |            |          | 25°C       |            |          | 85°C       |            |          | Unit |
|--------------------------|--|------------|------------|----------|------------|------------|----------|------------|------------|----------|------|
|                          |  | Min        | Typ        | Max      | Min        | Typ        | Max      | Min        | Typ        | Max      |      |
| $V_{OUTPP}$              | Output Voltage Amplitude<br>$f_{in} < 3\text{ GHz}$<br>$f_{in} < 6\text{ GHz}$ (See Figures 2 & 3)                                     | 500<br>270 | 700<br>350 |          | 500<br>270 | 700<br>350 |          | 500<br>270 | 700<br>300 |          | mV   |
| $f_{DATA}$               | Maximum Operating Data Rate  | 6          |            |          |            |            |          |            |            |          | Gb/s |
| $t_{PLH}$ ,<br>$t_{PHL}$ | Propagation Delay to<br>Output Differential @ 1 GHz  | 80         | 130        | 180      | 80         | 130        | 180      | 85         | 135        | 185      | ps   |
| $t_{SKEW}$               | Duty Cycle Skew (Note 2)<br>Device-to-Device Skew  |            | 3<br>30    | 25<br>60 |            | 3<br>30    | 25<br>60 |            | 3<br>30    | 25<br>60 | ps   |
| $t_{JITTER}$             | RMS Random Clock Jitter<br>$f_{in} < 6\text{ GHz}$ (Note 3)<br>Peak-to-Peak Data Dependent Jitter<br>$f_{in} < 6\text{ Gb/s}$ (Note 4) |            | 0.2<br>2   | 1<br>12  |            | 0.2<br>2   | 1<br>12  |            | 0.2<br>2   | 1<br>12  | ps   |
| $V_{INPP}$               | Input Voltage Swing / Sensitivity<br>(Differential Configuration) (Note 5)   | 75         | 700        | 2500     | 75         | 700        | 2500     | 75         | 700        | 2500     | mV   |
| $t_r$<br>$t_f$           | Output Rise/Fall Times<br>(20%–80%) Q, $\bar{Q}$   | 30         | 70         | 120      | 30         | 70         | 120      | 30         | 70         | 120      | ps   |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lpm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

1. Measured using a 800 mV source, 50% duty cycle clock source. All loading with  $50\ \Omega$  to  $V_{CC}$ . Input edge rates 40 ps (20% – 80%).
2. See Figure 9  $t_{skew} = |t_{PLH} - t_{PHL}|$  for a nominal 50% differential clock input waveform. Skew is measured between outputs under identical transitions and conditions @ 1 GHz.
3. Additive RMS jitter with 50% duty cycle clock signal at 6 GHz.
4. Additive Peak-to-Peak data dependent jitter with NRZ PRBS  $2^{23}-1$  data rate at 6 Gb/s.
5.  $V_{INPP(max)}$  cannot exceed  $V_{CC} - V_{EE}$ . (Applicable only when  $V_{CC} - V_{EE} < 2500\text{ mV}$ ). Input voltage swing is a single-ended measurement operating in the differential mode.




**Figure 2. Output Voltage Amplitude ( $V_{OUTPP}$ ) versus Input Clock Frequency ( $f_{IN}$ ) and Temperature at  $V_{CC} - V_{EE} = 3.3\text{ V}$**




**Figure 3. Output Voltage Amplitude ( $V_{OUTPP}$ ) versus Input Clock Frequency ( $f_{IN}$ ) and Temperature at  $V_{CC} - V_{EE} = 2.5\text{ V}$**

# NB6L16




**Figure 4. Typical Output Waveform at 2.488 Gb/s with PRBS 2<sup>23</sup>-1 (Total System Pk-Pk Jitter is 16 ps. Device Pk-Pk Jitter Contribution is 3 ps)**




**Figure 5. Typical Output Waveform at 6.125 Gb/s with PRBS 2<sup>23</sup>-1 (Total System Pk-Pk Jitter is 17 ps. Device Pk-Pk Jitter Contribution is 4 ps)**


NOTE:  $V_{CC} - V_{EE} = 3.3 \text{ V}$ ;  $V_{IN} = 700 \text{ mV}$ ;  $T_A = 25^\circ\text{C}$ .



**Figure 6. Propagation Delay versus Power Supply Voltage and Temperature**




**Figure 7. Rise/Fall Time versus Power Supply Voltage and Temperature**




**Figure 8.  $I_{EE}$  Current versus Temperature and Power Supply Voltage**




# NB6L16




**Figure 9. AC Reference Measurement**




**Figure 10. Differential Input Driven Single-Ended**



**Figure 11. Differential Inputs Driven Differentially**




**Figure 12.  $V_{th}$  Diagram**



**Figure 13.  $V_{CMR}$  Diagram**

## NB6L16



**Figure 14. Typical Termination for Output Driver and Device Evaluation**  
(See Application Note [AND8020/D](#) – Termination of ECL Logic Devices)


### Resource Reference of Application Notes

- AN1405/D** – ECL Clock Distribution Techniques
- AN1406/D** – Designing with PECL (ECL at +5.0 V)
- AN1503/D** – ECLinPS™ I/O SPICE Modeling Kit
- AN1504/D** – Metastability and the ECLinPS Family
- AN1568/D** – Interfacing Between LVDS and ECL
- AN1672/D** – The ECL Translator Guide
- AND8001/D** – Odd Number Counters Design
- AND8002/D** – Marking and Date Codes
- AND8020/D** – Termination of ECL Logic Devices
- AND8066/D** – Interfacing with ECLinPS
- AND8090/D** – AC Characteristics of ECL Devices

# NB6L16

## PACKAGE DIMENSIONS


SOIC-8 NB  
D SUFFIX  
CASE 751-07  
ISSUE AK



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: MILLIMETER.
  3. DIMENSION A AND B DO NOT INCLUDE MOLD PROTRUSION.
  4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
  5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.
  6. 751-01 THRU 751-06 ARE OBSOLETE. NEW STANDARD IS 751-07.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.80        | 5.00 | 0.189     | 0.197 |
| B   | 3.80        | 4.00 | 0.150     | 0.157 |
| C   | 1.35        | 1.75 | 0.053     | 0.069 |
| D   | 0.33        | 0.51 | 0.013     | 0.020 |
| G   | 1.27 BSC    |      | 0.050 BSC |       |
| H   | 0.10        | 0.25 | 0.004     | 0.010 |
| J   | 0.19        | 0.25 | 0.007     | 0.010 |
| K   | 0.40        | 1.27 | 0.016     | 0.050 |
| M   | 0°          | 8°   | 0°        | 8°    |
| N   | 0.25        | 0.50 | 0.010     | 0.020 |
| S   | 5.80        | 6.20 | 0.228     | 0.244 |

### SOLDERING FOOTPRINT\*




SCALE 6:1  $\left(\frac{\text{mm}}{\text{inches}}\right)$

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# NB6L16

## PACKAGE DIMENSIONS

TSSOP-8  
DT SUFFIX  
CASE 948R-02  
ISSUE A



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: MILLIMETER.
  3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
  4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
  5. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
  6. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 2.90        | 3.10 | 0.114     | 0.122 |
| B   | 2.90        | 3.10 | 0.114     | 0.122 |
| C   | 0.80        | 1.10 | 0.031     | 0.043 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| F   | 0.40        | 0.70 | 0.016     | 0.028 |
| G   | 0.65 BSC    |      | 0.026 BSC |       |
| K   | 0.25        | 0.40 | 0.010     | 0.016 |
| L   | 4.90 BSC    |      | 0.193 BSC |       |
| M   | 0°          | 6°   | 0°        | 6°    |

ECLinPS is a trademark of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries.

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Buffers & Line Drivers](#) category:*

*Click to view products by [ON Semiconductor](#) manufacturer:*

Other Similar products are found below :

[5962-9217601MSA](#) [634810D](#) [875140G](#) [HEF4022BP](#) [HEF4043BP](#) [NL17SG125DFT2G](#) [NL17SZ126P5T5G](#) [NLU1GT126CMUTCG](#)  
[NLU3G16AMX1TCG](#) [NLV27WZ125USG](#) [MC74HCT365ADTR2G](#) [BCM6306KMLG](#) [54FCT240CTDB](#) [Le87401NQC](#) [Le87402MQC](#)  
[028192B](#) [042140C](#) [051117G](#) [070519XB](#) [065312DB](#) [091056E](#) [098456D](#) [NL17SG07DFT2G](#) [NL17SG17DFT2G](#) [NL17SG34DFT2G](#)  
[NL17SZ07P5T5G](#) [NL17SZ125P5T5G](#) [NLU1GT126AMUTCG](#) [NLV27WZ16DFT2G](#) [5962-8982101PA](#) [5962-9052201PA](#) [74LVC07ADR2G](#)  
[MC74VHC1G125DFT1G](#) [NL17SH17P5T5G](#) [NL17SZ125CMUTCG](#) [NLV17SZ07DFT2G](#) [NLV37WZ17USG](#) [NLVHCT244ADTR2G](#)  
[NC7WZ17FHX](#) [74HCT126T14-13](#) [NL17SH125P5T5G](#) [NLV14049UBDTR2G](#) [NLV37WZ07USG](#) [74VHC541FT\(BE\)](#) [RHFAC244K1](#)  
[74LVC1G17FW4-7](#) [74LVC1G126FZ4-7](#) [BCM6302KMLG](#) [74LVC1G07FZ4-7](#) [74LVC1G125FW4-7](#)