



PRODUCT DATASHEET

Coating Thickness Tester



Dual Technology provides automatic recognition

For ferrous and non-ferrous substrates

Features:

- Automatic substrate recognition
- · Magnetic induction for ferrous substrates
- · Eddy current measurement for non-ferrous substrates
- Easy-to use menu system
- Two measuring modes: Single and Continuous
- Two working modes: Direct and Group
- Memory stores 400 readings: 80 Direct and 320 Group
- User-programmable high/low alarms
- Min/Max/Average
- · One or two point calibration
- · USB interface includes software
- Complete with two AAA batteries, USB cable, software, Calibration Iron, Calibration Aluminum, Precision Standards, and pouch case.





Specifications		
Sensor Probe	Ferrous	Non-Ferrous
Working Principle	Magnetic Induction	Eddy Current
Measuring Range	0 to 1250µm	0 to 1250µm
	0 to 49mils	0 to 49mils
Basic Accuracy	±3%	±3%
Resolution	0.1µm (0.004mils)	0.1µm (0.004mils)
Minimum Curvature Radius	1.5mm (59.06mils)	3mm (118.1mils)
Minimum Diameter	7mm (275.6mils)	5mm (196.9mils)
Minimum Thickness	0.5mm (19.69mils)	0.3mm (11.81mils)
Dimensions	4.7 x 2.4 x 1.25" (120 x 62 x 32mm)	
Weight	6.17oz (175g)	

Ordering Information:

CG204Coating Thickness Tester **CG204-REF**Calibration References

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Test Accessories - Other category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

AO1026 AO1035 AO1051 AO1059 149118 C20 RS40 RS41 AO1030 AO1032 AO1036 AO1058 4742 KTS288540 00415 00163
046450 GPR10 ADPTR-HDV VS-AVT-C02-L03 VS-AVT-CABLE-04 VS-AVT-CABLE-16 VS-AVT-CABLE-20 VS-AVT-CABLE-30
VS-CKP14-6 VS-CKP4-000 VS-AVT2-C02L03 VS-AVT2-C08L10 CKSB1-00 CKSB6-2 CKSB10-8 GP73800080 MPT-VF 98-CAL020
LSP08-RTS 1-1437358-1 4408 POMONA AX-904 DME D110 T1 LMLH 50 1508-POM 00836 85392-12 207P18.2222.F CR-31 7708
ST18/SMAM/SMAM/72 CT2299 C700 34192A