

This document was generated on 09/30/2016

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0749818504

Status: Active

Overview: VHDM-HSD™ Backplane Connectors

Description: VHDM-HSD™ Backplane Header, 2.00mm Pitch, 6-Row, Guide Pin Signal Module,

Pin End Version, 100 Circuits, Pin Length 5.15mm, Series:74984 Enables designers to create custom loaded connectors utilizing standard pin lengths 4.25, 4.75, 5.15 and

6.25mm

**Documents:** 

Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-74031-999 (PDF)

**Agency Certification** 

UL E29179

General

Product Family Backplane Connectors

Series 74981
Application Backplane
Application Tooling Documents TM-622010999
Comments No Keying Orientation

Component Type PCB Header

Overview <u>VHDM-HSD™ Backplane Connectors</u>

Product Name VHDM-HSD™ UPC 883906537494

**Physical** 

Circuits (Loaded) 100
Circuits (maximum) 100
Color - Resin Black
Durability (mating cycles max) 200
First Mate / Last Break No
Flammability 94V-0
Guide to Mating Part Yes
Keying to Mating Part None

Material - Metal Copper-Nickel-Silicon, High Performance Alloy (HPA),

Stainless Steel

Material - Plating Mating Gold
Material - Plating Termination Matte Tin

Material - Resin High Temperature Thermoplastic


Net Weight 16.848/g Number of Columns 25

Number of Pairs Open Pin Field

Number of Rows 6
Orientation Vertical
PC Tail Length 2.50mm
PCB Locator No
PCB Retention None
PCB Thickness - Recommended 1.80mm
Packaging Type Tube

Pitch - Mating Interface 2.00mm
Pitch - Termination Interface 2.00mm
Plating min - Mating 0.762µm
Plating min - Termination 0.762µm
Polarized to PCB Yes
Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -55°C to +105°C



**EU ELV** 

**Not Relevant** 

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ED/21/2016 (20 June 2016)

Halogen-Free Status

Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image ELV Not Relevant

Search Parts in this Series

74981 Series

**Mates With** 

74880 VHDM-HSD™ Daughtercard

**Use With** 

**Daughtercard Modules** 

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

**Description** Product # Signal Pin Inserter 0622015700

Repair Tool

Insertion Module 0622020217

Signal Header, 6

Termination Interface: Style Through Hole - Compliant Pin

2.0A **Current - Maximum per Contact** 5.0 Gbps Data Rate

Shielded No

Voltage - Maximum 120V AC (RMS)/DC

**Material Info** 

**Electrical** 

**Reference - Drawing Numbers** 

**Product Specification** PS-74031-999 SD-74981-010 Sales Drawing

Note: HDM, HDM+, VHDM, VHDM-HSD and GbX are trademarks or registered trademarks of Amphenol TCS.

This document was generated on 09/30/2016

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Row by 25 Wide,

50.00mm

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

2332816-1 89006-1137LF 650827-1 65762-001LF 73474-201LF 74040-1346 74075-0267 88911-201LF 9514M0C20D 1410191-1 1410337-1 1410368-3 1410964-2 1410326-3 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 2187462-1 2226278-6 KA81-07 91290-101LF 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 2226279-2 22354-8 437-5040-000 5-1393565-0 532449-3 532803-2 34745-0001 0740618502 0760151403 0760551105 0760551608 0761451128 0761651124 0761655108 0761659807 0769853208 0736440217 0758324203