

Isolating Transformers Type STOS:

Isolating transformers type STO are intended mainly for applications requiring protection against electric shock and IP44 protection grade of the casing.

Portable version is provided with a reinforced polycarbonate case and build-in soft start system.

Plugs and sockets are components intended for general applications or CEE type components at request.

The electric circuit features the following components: transformer, 2,5mb power cord with a 230V plug and two output sockets: 230V – 1x 230V Uni-Schuko / 16A oraz 1x 230V 6h 16A 2P+E IP44

General Informations:

Nominal Output Power: 1500-4000VA
 Rated voltage: 230V
 Frequency: 50 – 60Hz
 Output voltage: 230V

Max. ambient temp.: 40°C
 Protection grade: IP-44



Technical Details:

Type	Continuous output power	Rated voltage	Output voltage	Nominal Current	Dimensions [mm] A x B x height	Weight [kg]
STOS1500	1500VA	230V	230V	6,5A	380 x 330 x 170	13,5
STOS3000	3000VA	230V	230V	13A	380 x 330 x 170	17,5
STOS4000	4000VA	230V	230V	17,5 A	380 x 330 x 170	19,5

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Current Transformers](#) category:

Click to view products by [Toroidy](#) manufacturer:

Other Similar products are found below :

[MP3500](#) [BV UI 302 0156](#) [45029](#) [BV EI 302 2863](#) [BV EI 303 2809](#) [BV EI 303 3060](#) [BV EI 305 2309](#) [BV EI 306 3604](#) [BV EI 481 1295](#) [BV EI 481 1325](#) [BV UI 301 0133](#) [BV UI 302 0144](#) [BV UI 302 0161](#) [BV UI 304 0019](#) [BV UI 304 0129](#) [BV UI 304 0159](#) [BV UI 304 0173](#) [TI-EF16-2X4V-4W](#) [SPCT62/40150/5AVA3CL1](#) [SPCT62/30100/5AVA1CL1](#) [SPCT62/3075/5AVA1CL3](#) [SPCT62/40150/5AVA1.5CL1](#) [SPCT62/40200/5AVA2.5CL0.5](#) [SPCT62/40300/5AVA3CL0.5](#) [CTD-KIT](#) [44013](#) [44017](#) [44021](#) [44098](#) [44101](#) [44134](#) [44171](#) [44174](#) [44178](#) [44180](#) [44248](#) [44250](#) [44278](#) [44339](#) [44340](#) [44373](#) [44375](#) [44376](#) [44378](#) [44379](#) [44436](#) [44831](#) [B82801B0925A200](#) [PA3655NL](#) [PA3828NL](#)