



Specifications:

Current Rating:1.0A AC/DC
 Voltage Rating:30V AC/DC
 Contact Resistance:20m ohm. Max.
 Insulation Resistance:1000M ohm. Min.
 Withstanding Voltage:500V AC For One Minute
 Operating Temperature Range:-40°C ~ +105°C
 Material and Finish
 Insulator:High Temp. Plastic (UL94V-0)
 Contact:Copper Alloy
 Finish:Tin Plated

How to Order

TMM-X-X-XX-X

Type
 1-IDC Male
 2-IDC Plug
 3-DIP Male Straight
 4-DIP Female Straight
 5-DIP Female R/A
 6-SMT Female Straight

Locking System
 0-without lock
 L-with lock

Packaging
 1 - Tape & Reel
 2 - Tube
 3 - Bag

Number of Positions
 04, 06, 08, 10, 12,
 14, 16, 18 or 20

| Circuits | Dimension | | Circuits | Dimension | |
|----------|-----------|-------|----------|-----------|-------|
| | A | B | | A | B |
| 4 | 8.45 | 2.54 | 16 | 23.69 | 17.78 |
| 6 | 10.99 | 5.08 | 18 | 26.23 | 20.32 |
| 8 | 13.53 | 7.62 | 20 | 28.77 | 22.86 |
| 10 | 16.07 | 10.16 | 22 | 31.31 | 25.40 |
| 12 | 18.61 | 12.70 | 24 | 33.85 | 27.94 |
| 14 | 21.15 | 15.24 | 26 | 36.39 | 30.48 |

| TOLERANCE (mm) | APPROVALS | DATE | TITLE | AMPHENOL Amphenol European Design Center | |
|----------------------------|---------------------------|------------|--------------------------------------|--|--------------|
| X. ±0.3 | DRAWN Stephane | 2008/04/22 | Micro Match IDC type Male | Scale N.A. | Sheet 1 of 1 |
| XX ±0.1 | CHECKED Rob K. | 2008/04/23 | | | |
| XXX ±0.05 | APPROVED Rob K. | 2008/04/23 | | | |
| UNLESS OTHERWISE SPECIFIED | UNIT MM | SIZE A4 | DRAWING N° TMM-1-0-XX-X | REV. A | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Amphenol](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)