

Voltage - Maximum

This document was generated on 02/09/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0855135110			
Status:	Active			
Overview: Description:	Magnetic and Modula Modular Jack, Vertica	<u>Magnetic and Modular Jacks and Plugs</u> Modular Jack, Vertical, Top Entry, Surface Mount, 6/6, Low Profile, Pick-and-Place Polyimide Tape, 22" Reel		E
Documents:				
3D Model		Test Summary STR-1425-001 (PDF)		
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		
	tion PS-85513-002-001 (PD		<u></u>	
	ication AS-85513-001-001 (Series imag	e - Reference only
General			EU ELV	
Product Family		Modular Jacks/Plugs	Not Relevant	
Series		85513	NOT Relevant	
Comments		Reflow Capable, Small Panel Cutout	EU RoHS	China RoHS
Component Type		PCB Jack	Compliant	<u></u>
		PCB Jack No	REACH SVHC	
Magnetic Overview		-	Not Contained Per	
		Magnetic and Modular Jacks and Plugs	ED/30/2017 (7 July	
Performance Category		3	2017)	
Power over Ethernet (PoE)		N/A	Halogen-Free	
Product Literature Order No		987650-8441	Status	
Product Name		Modular Jack 6/6		
UPC		887191677613	Low-Halogen Need more information on product	
Physical				-
Boot Color		N/A	environmental cor	npliance?
			Email productcomp	iance@moley.com
Color - Resin		Black	Email <u>productcompliance@molex.com</u> Please visit the <u>Contact Us</u> section for	
Durability (mating cycles max)		2500	non-product complia	
Inverted / Top Latch		No		ance questions.
Jack Height		12.70mm	China ROHS	Green Image
Lightpipes/LEDs		None	ELV	Not Relevant
Material - Metal		Copper Alloy	RoHS Phthalates	Not Contained
Material - Plating I		Gold over Palladium Nickel		Not Contained
Material - Plating	Termination	Tin		
Material - Resin		High Temperature Thermoplastic		
Net Weight		2.258/g	Search Parts in this Series	
Orientation		Vertical (Top Entry)	85513 Series	
PCB Locator		No		
PCB Retention		Yes	Mates With	
Packaging Type		Embossed Tape on Reel	<u>90075</u> Modular Plug	
Pitch - Mating Inte		1.02mm		
Pitch - Termination Interface		1.27mm	Lleo With	
Plating min - Mating		0.051µm, 1.016µm	Use With	
Plating min - Termination		1.905µm	90075 Modular Plugs	
Ports		1		
Positions / Loaded		6/6		
Surface Mount Compatible (SMC)		Yes		
Temperature Range - Operating		-40°C to +85°C		
Termination Interfa		Surface Mount		
Waterproof / Dustproof		No		
Wire/Cable Type		N/A		
Electrical				
Current - Maximur	n per Contact	1.5A		
Shielded	•	No		
Voltage - Maximum		125\/ DC		

125V DC

Material Info

Reference - Drawing Numbers Application Specification Product Specification Sales Drawing Test Summary

AS-85513-001-001 PS-85513-002-001 SD-85513-010 STR-1425-001

This document was generated on 02/09/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 RJE231881317T
 MP1010RX-1000
 MP44RX-1000
 GAX-3-66
 GAX-8-62
 93606-0253
 GD-A-44
 GDCX-PA-66-50
 GDCX-PN-64
 GDCX-PN-64

 PN-66
 GDCX-PN-66-50
 GDLX-A-66
 GDLX-A-88
 GDLX-N-66
 GDLX-S-88K
 GDTX-S-88-50
 GDX-PA-1010
 GLX-A-44
 GLX-N

 1010M-BLK
 GLX-N-44M
 GLX-S-88M-BLK
 GMX-N-1010
 GMX-S-1010
 GMX-SMT2-N-1010
 GMX-SMT2-N-64-50
 GMX

 SMT2-S6-88
 GMX-SMT4-N-88
 GPX-2-64
 GRT1-BT1-5
 GSGX-N-2-88
 GSX-NS2-88-3.05
 GSX-NS2-88-3.05-50
 GSX-NS-88-3.05-30

 GSX-NS-88-3.05-50
 GSX-NS-88-3.68
 1-1775629-2
 GWLX-S-88-GR
 GWLX-S9-88-YG
 1300500326
 1300500227
 1300530003

 1300570002
 1324640-4
 RJ11FTVC2G
 RJ11FTVC2N
 RJFTVX2SA1G
 132764-001
 1400000
 1413176