

fouborq snoiteotions

PCT-RCA-59

Universal RCA Compression Connector, Series 59 60% through Quad-Shield



GENERAL SPECIFICATIONS	
Bandwidth	5 MHz to 3 GHz
Impedance	75 Ohms (Nominal)
Return Loss	Minimum -30 dB to 1 GHz
Shielding Effectiveness	-80 dB Minimum
VSWR	≤ 1.065 @ 1GHz
Operating Voltage	90 V (at 60 Hz continuous AC)
Operating Temperature	-40° F to +140° F, -40° C to +60° C
Cable Range	RG 59 Cable 60% through Quad-Shield
Cable Retention	>50 lbf. (22.68 kgf)
Cable Insertion	<20 lbs. maximum insertion force
PHYSICAL CHARACTERISTICS	
Length Before Compression	1.42 inches (36.25mm)
Length After Compression	1.28 inches (32.55mm)
Pin Diameter	.125 inches (3.18mm)
Construction Material	Nickel Plated Brass
Insulator	Delrin Insulator
Pin Construction	Brass with Gold Plating
TOOLING	
Compression tool	PCT-AIO-CT
PART NUMBER	
PCT-RCA-59	Universal RCA Compression Connector, Series 59 60% through Quad Shield

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connectors / Coaxial Connectors category:

Click to view products by PCT manufacturer:

Other Similar products are found below :

R125315120 8915-1511-000 89674-0827 5916-1103-603 0106-001-000 6-0001-3 6001-7071-019 6002-7051-003 6002-7551-202 6059674-1 619550-1 630059-000 M39012/25-0021 M39012/79-3008 M39030/3-01N M39030/3-03N M3933/25-29N M3933/25-36N 6500-7071-046 6501-1071-002 M83723/72W24576 M83723/72W2457N 6769 CX050L2AQ 7002-1541-010 7003-1572-002 7004-1512-000 7009-1511-004 7010-1511-000 7029-1511-060 7101-1541-010 7101-1571-002 7105-1521-002 7145-1521-002 7209-1511-011 7210-1511-012 7210-1511-015 7210-1511-019 7210-1511-040 7225-1512-050 7242-1511-000 73137-5015 73216-2241 73251-0111 73251-0672 73276-1501 73366-0013 73404-2300 73413-6080 734151610