

Ferrule — FWS/FWL 1000Vdc: 2-30A

FWS 2-15A (20 x 127mm) FWL 20-30A (20 x 127mm)

Specifications

Description: Ferrule style full range

fuses.

Dimensions: See dimensions

illustrations.

Ratings:

Volts: — 1200Vac (FWL 20-30A)

- 1400Vac (FWS 8-15A)

- 2100Vac (FWS 2-6A)

- 1000Vdc (FWL/FWS 2-30)


Amps: - 2-30A

IR: - 45kA RMS Sym.

- 30kA @ 1000Vdc


Agency Information: CE, IEC 60077

Catalog Numbers




- ADD "I" to catalog number for indicating version.
- Enclosed finger-safe fuse holder CH127
- Open style fuse block 4530-OP
- See accessories on page 216.
 Watts loss provided at rated current.

Dimensions - mm (inches)



Indicating Version - Dimensions - mm (inches)



Features and Benefits


- Excellent cycling capability and DC performance
- Low arc voltage and low energy let-through (I2t)
- · Low watts loss in a compact size
- · Used with finger-safe holders/blocks

Typical Applications

- DC common bus
- · DC drives
- Power converters/rectifiers
- · Reduced voltage starters
- · Traction aux circuits
- · Capacitor protection

FWL/FWS 2-30A: 1000Vdc 2-30A (20 x 127mm)

Time-Current Curve



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Specialty Fuses category:

Click to view products by Eaton manufacturer:

Other Similar products are found below:

63NZ02GL 714125 722134 80NH00GR-6 FWH-200A FWP-32A14F FWP-50 HBM-25 12LCT 12TDLSJ63 REN-3 15.5CAVH2E ECF-2 ECF-4 ECF-6 170M0213 170M1314 170M1369-D 170M3809D BK/F02A-2AS BK/F02B-1A N-2-1/2 N-3-2/10 NITD2 20D16 20D16SC 20D27FB KAA-3 KAB-2 KAB-30 KAJ-60 KAW-3 2D16 LKN-125B 16D27SB 170M1564D 170M2616 170M2668 170M4161 170M4241 170M4699 ESD63 ABS-25 ABS-30 ABS-8 ACF-15 ACF-30 ACO-30 SSD10 200NH1M