JOBBER DRILLS

Straight Shank

Standard Helix

BS 328 DIN 338 ISO 235/1

01 000 HSS 01 000 01 030 HSS

 Range
 Finish

 1/16"-3/4"
 P1 Blue

 1.55mm-25.00mm
 P1 Blue


 1/64"-3/4"
 Bright

 0.30mm-25.00mm
 Bright

01 005 HSS 3/64"-3/4" TiN

1.00mm-20.00mm TiN

Point Angle 118' General Purpose



in '	Dia mm d	Flute Length mm	Overall Length mm I ₁	01030	01005 ability	in	Dia mm d	Flute Length mm I ₂	Overall Length mm I ₁	01000 01030 Availa		in	Dia mm d	Flute Length mm I ₂	Overall Length mm I ₁	01000 01030 Availa	
	*0.30	4	19	•	_		1.80	22	46	•	•		3.95	43	75		
	*0.32	4	19	•	_		1.85	22	46	•	•	5/32	5.55	43	75	•	•
	*0.35	4	19	•	_		1.90	22	46	•	•	0,00	4.00	43	75	•	•
	*0.38	4	19	•	_		1.95	24	49	•	•		4.05	43	75	•	•
*1/64		5	20	•	-	5/64		24	49	•	•		4.10	43	75	•	•
	*0.40	5	20	•	-		2.00	24	49	•	•		4. 15	43	75	•	•
	*0.42	5	20	•	-		2.05	24	49	•	•		4.20	43	75	•	•
	*0.45	5	20	•	-		2.10	24	49	•	•		4.25	43	75	•	•
	*0.48	5	20	•	-		2.15	27	53	•	•		4.30	47	80	•	•
	*0.50	6	22	•	-		2.20	27	53	•	•		4.35	47	80	•	•
	*0.52	6	22	•	-		2.25	27	53	•	•	11/64		47	80	•	•
	*0.55	7	24	•	-		2.30	27	53	•	•		4.40	47	80	•	•
	*0.58	7	24	•	-	2 /2 2	2.35	27	53	•	•		4.45	47	80	•	•
	*0.60	7	24	•	-	3/32	2.40	30	57 57	•	•		4.50	47	80	•	•
	*0.62 *0.65	8 8	26 26	•	-		2.40	30	57 57	•	•		4.55	47	80	•	•
	*0.68	9	28	•	-		2.45 2.50	30 30	57 57	•	•		4.60	47	80	•	•
	*0.70	9	28	•	-		2.55	30	57 57	•	•		4.65	47	80	•	•
	*0.72	9	28	•	-		2.60	30	57 57	•	•		4.70	47	80	•	•
	*0.75	9	28	•	_		2.65	30	57	•	•	3/16	4.75	47 52	80 86	•	•
	*0.78	10	30	•	_		2.70	33	61	•	•	3/10	4.80	52 52	86	•	•
*1/32		10	30	•	_		2.75	33	61	•	•		4.85	52	86	•	•
	*0.80	10	30	•	_	7/64	25	33	61	•	•	-	4.90	52	86	•	•
	*0.82	10	30	•	_	.,	2.80	33	61	•	•		4.95	52	86	•	
	*0.85	10	30	•	-		2.85	33	61	•	•		5.00	52	86	•	
	*0.88	11	32	•	_		2.90	33	61	•	•		5.10	52	86	•	•
	*0.90	11	32	•	_		2.95	33	61	•	•		5.15	52	86	•	•
	*0.92	11	32	•	-		3.00	33	61	•	•	13/64		52	86	•	•
	*0.95	11	32	•	-		3.05	36	65	•	•		5.20	52	86	•	•
	*0.98	12	34	•	-		3.10	36	65	•	•		5.25	52	86	•	•
	*1.00	12	34	•	•		3.15	36	65	•	•		5.30	52	86	•	•
	*1.05	12	34	•	•	1/8		36	65	•	•		5.35	57	93	•	•
	*1.10	14	36	•	•		3.20	36	65	•	•		5.40	57	93	•	•
/	*1.15	14	36	•	•		3.25	36	65	•	•		5.45	57	93	•	•
*3/64	** 20	16	38	•	•		3.30	36	65	•	•		5.50	57	93	•	•
	*1.20	16	38	•	•		3.35	36	65	•	•	7/32		57	93	•	•
	*1.25	16	38	•	•		3.40	39	70	•	•		5.60	57	93	•	•
	*1.30 *1.35	16 18	38 40	•	•		3.45	39	70	•	•		5.65	57	93	•	•
	*1.40	18	40	•	•		3.50	39	70	. •	•		5.70	57	93	•	•
	*1.45	18	40	•	•	9/64	3.55	39	70 70	•	•		5.75	57	93	•	•
•	*1.50	18	40	•	-	<i>3/</i> 04	3.60	39 39	70 70	•	•		5.80	57	93	•	•
	1.55	20	43	•	-		3.65	39 39	70 70	•	•		5.85 5.90	57 57	93	•	•
1/16		20	43	•	•		3.70	39	70	-	•	15/64	J.7U	57 57	93	•	•
.,	1.60	20	43	•	•		3.75	39	70	•	-	13/04	6.00	57 57	93 93	•	•
	1.65	20	43	•	•		3.80	43	75	•	•		6.05	63	93 101	•	•
	1.70	20	43	•	•		3.85	43	75	•	•		6.10	63	101	•	•
	1.75	22	46	•	•		3.90	43	75	•	•		6.15	63	101	•	-
										-	-		5	-5		•	•

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for presto manufacturer:

Other Similar products are found below:

Presto