



<u>PART NO.</u>	<u>HOLE DIAMETER</u> ±.003 [0.08]	<u>HEAD DIAMETER</u>	<u>SUGGESTED TOTAL BOARD THICKNESS</u>	<u>HEAD HEIGHT</u>	<u>LENGTH</u>		
RBF-4-8.6-8	.157(4.00)	.32(8.0)	.08-.17(2.1-4.3)	.04(1.0)	.34(8.6)		
RBF-4-11.1-8			.08-.28(2.1-7.2)		.44(11.1)		
RBF-4-15-8			.22-.42(5.7-10.7)		.59(15.0)		
RBF-4-8.6-12		.47(12.0)	.63(16.0)	.08-.17(2.1-4.3)	.06(1.5)	.34(8.6)	
RBF-4-11.1-12				.08-.28(2.1-7.2)		.44(11.1)	
RBF-4-15-12				.22-.42(5.7-10.7)		.59(15.0)	
RBF-4-8.6-16		.188(4.76)	.32(8.0)	.08-.17(2.1-4.3)	.08(2.0)	.34(8.6)	
RBF-4-11.1-16				.08-.28(2.1-7.2)		.44(11.1)	
RBF-4-15-16				.22-.42(5.7-10.7)		.59(15.0)	
RBF-4.8-8.6-8	*.250(6.35)		.47(12.0)	.08-.17(2.1-4.3)	.04(1.0)	.34(8.6)	
RBF-4.8-11.1-8				.08-.28(2.1-7.2)		.44(11.1)	
RBF-4.8-15-8				.22-.42(5.7-10.7)		.59(15.0)	
RBF-4.8-8.6-12			.63(16.0)	.63(16.0)	.08-.17(2.1-4.3)	.06(1.5)	.34(8.6)
RBF-4.8-11.1-12					.08-.28(2.1-7.2)		.44(11.1)
RBF-4.8-15-12					.22-.42(5.7-10.7)		.59(15.0)
RBF-4.8-8.6-16		*.281(7.14)	.32(8.0)	.08-.17(2.1-4.3)	.08(2.0)	.34(8.6)	
RBF-4.8-11.1-16				.08-.28(2.1-7.2)		.44(11.1)	
RBF-4.8-15-16				.22-.42(5.7-10.7)		.59(15.0)	
RBF-6.4-8.6-8	*.281(7.14)		.47(12.0)	.08-.17(2.1-4.3)	.04(1.0)	.34(8.6)	
RBF-6.4-11.1-8				.08-.28(2.1-7.2)		.44(11.1)	
RBF-6.4-15-8				.22-.42(5.7-10.7)		.59(15.0)	
RBF-6.4-8.6-12			.63(16.0)	.63(16.0)	.08-.17(2.1-4.3)	.06(1.5)	.34(8.6)
RBF-6.4-11.1-12					.08-.28(2.1-7.2)		.44(11.1)
RBF-6.4-15-12					.22-.42(5.7-10.7)		.59(15.0)
RBF-6.4-8.6-16		*.281(7.14)	.32(8.0)	.08-.17(2.1-4.3)	.08(2.0)	.34(8.6)	
RBF-6.4-11.1-16				.08-.28(2.1-7.2)		.44(11.1)	
RBF-6.4-15-16				.22-.42(5.7-10.7)		.59(15.0)	
RBF-7.1-11.1-8	*.281(7.14)		.47(12.0)	.08-.28(2.1-7.2)	.04(1.0)	.44(11.1)	
RBF-7.1-15-8				.15-.42(3.8-10.7)		.59(15.0)	
RBF-7.1-19-8				.27-.56(6.9-14.2)		.75(19.0)	
RBF-7.1-11.1-12			.63(16.0)	.63(16.0)	.08-.28(2.1-7.2)	.06(1.5)	.44(11.1)
RBF-7.1-15-12					.15-.42(3.8-10.7)		.59(15.0)
RBF-7.1-19-12					.27-.56(6.9-14.2)		.75(19.0)
RBF-7.1-11.1-16		.63(16.0)	.63(16.0)	.08-.28(2.1-7.2)	.08(2.0)	.44(11.1)	
RBF-7.1-15-16				.15-.42(3.8-10.7)		.59(15.0)	
RBF-7.1-19-16				.27-.56(6.9-14.2)		.75(19.0)	

* FOR USE IN METAL, LEADING EDGE OF HOLE MUST BE BROKE

- NOTES:
 1. MATERIAL: NYLON 6/6 (RMS-01).
 FLAME RETARDANT NYLON (RMS-19)
 AVAILABLE BY SPECIAL ORDER.
 2. COLOR: BLACK.
 NATURAL BY SPECIAL ORDER

B	SEE ECN # 917 FOR CHANGES	SK	01/18/05
A	RELEASED FOR PRODUCTION	SM	10/19/04
REV.	DESCRIPTION	ENGR.	DATE

TITLE: BARBED PUSH FASTENER				DWG IN IN [MM]		FINAL	
CREATED USING SOLIDWORKS	FILE #: RBF	DWN: D.J.Z.	APP: DJZ	PART #			
TOLERANCES UNLESS NOTED .XX=±.01 .XXX=±.005 FRAC.=±1/64 ANG.=±1°	SHEET: 1 OF 1	SHEET SIZE: B	DT: 06/09/2004	CHKD: SJ	SEE TABLE		PRINT TYPE
RE: RICHCO INC.			RICHCO, INC. ENG@RICHCO-INC.COM (773) 539-4060				CA

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [richco](#) manufacturer:

Other Similar products are found below :

[KLB450ART](#) [RBS-5-BK](#) [FMB-1](#) [DHURCS-3-01](#) [RRC-16-9-28-M2](#) [RRH-142-80-150](#) [DHURCS-4-01](#) [RRC-16-9-28-M1](#) [RT-310-190-222](#)
[RLCBSR-10-01](#) [OFST-1-L](#) [RFS1-15-7-A5](#) [RT-145-102-80](#) [RSH6-76100-50A](#) [RFP1-34-28-A5](#) [CAT-15-PP-BU](#) [CAT-32-PP](#) [RT-142-64-135](#)
[FGPT-92](#) [MFTH-2-01A-RT-M](#) [RT-290-190-77](#) [BMS-SAX300MM](#) [RRH-110-50-250](#) [SHR-32-6NB](#) [RCP-040-T](#) [LEDS2M-440-01](#) [SHR-C2](#)
[RKCF-08-A5](#) [CBSS-8-01](#) [RRH-120-85-150](#) [RFS1-15-15-A5](#) [RT-280-160-75](#) [MB-1-156](#) [RFS2-34-12-2-A5](#) [RT-175-95-127](#) [RT-290-190-75](#)
[RT-70-35-40](#) [SNGS-2](#) [SPGSG-2](#) [RT-100-70-50](#) [WSB-2-01A-RT](#) [SP3-4-01](#) [RT-100-70-70](#) [RRH-186-102-286](#) [VMCGN120-M3-L-K](#)
[OFHB3-4-19A-RT](#) [RRH-140-90-150](#) [RT-160-120-80](#) [RSFS-450](#) [SHR-32-PPB](#)