

UP-LCOFC Hi-Fi Interconnect & speaker series



hi-fi series

268-500-000 Twin Interconnect

Conductor	0.63mm bare ultra pure linear crystal oxygen free copper			
Insulation	Foam skin polyethylene			
Capacitance	<97 pF/m			
Screen	93% optical coverage LC-OFC braid			
Jacket	PVC/Neoprene composite sapphire blue RAL 5003			
Overall diameter	16.00 x 6.00mm			
Weight	110 Kg/Km			
Speaker cables				
Conductor	Bare ultra pure linear crystal oxygen free copper			
Insulation	Clear PVC			

Characteristics by stock code

Stock code	Description	Overall diameter	Weight Kg/Km	Conductor stranding	Conductor resistance Ohm/Km
268-502-000	2 x 2.5mm hi-fi	12.00 x 4.00mm	90	7 x (46 x 0.10mm)	24.50
268-504-000	2 x 4.0mm hi-fi	14.00 x 5.00mm	135	7 x (73 x 0.10mm)	12.50
268-506-000	2 x 6.0mm hi-fi	16.00 x 6.00mm	173	7 x (3 x (37 x 0.10mm))	7.30

• Maximum reel length 100 metres



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for van damme manufacturer:

Other Similar products are found below:

104-466-005 268401C 104-466-001 278-515-080 268-007-060 278-975-000 268024C 278-401-000 268026C 268005C 278-431-000 268308C 268542L 268001C 268502L 268575 268202 268009C 268011C 268307C 268-612-080 268002C 268-610-000 268012C 268018C 278-075-000 268208 268014C 268020C 278-775-000 268006C 268003C 268001CL