

CRYSTAL OSCILLATOR SPXO

SG-615 series SG-531 / SG-51 series

- Frequency range : 1.025 MHz to 135 MHz
- Supply voltage : 3.3 V / 5.0 V
- Function : Output enable(OE) Standby(\overline{ST})
- Pin compatible with full-size metal can. (SG-51 series)
- Pin compatible with half-size metal can. (SG-531 series)



Actual size

SG-615



SG-531



SG-51



Specifications (characteristics)

Item	Symbol	Specifications			Remarks
		SG-615P SG-531P SG-51P	SG-615PTJ SG-531PTJ SG-51PTJ	SG-615PH SG-531PH SG-51PH	
Output frequency range	f_0	1.025 MHz to 26 MHz	26.001 MHz to 66.667 MHz		
Supply voltage	V_{CC}	5.0 V \pm 0.5 V			
Temperature range	Storage temperature T_{stg}	-55 °C to +125 °C			Store as bare product after unpacking
	Operating temperature T_{use}	-20 °C to +70 °C			
Frequency tolerance	$F_{tol(osc)}$	B: $\pm 50 \times 10^{-6}$, C: $\pm 100 \times 10^{-6}$			-20 °C to +70 °C *1
Current consumption	I_{CC}	23 mA Max.	35 mA Max.		No load condition
Output disable current	I_{dis}	12 mA Max.	28 mA Max.	20 mA Max.	OE=GND
Symmetry	SYM	40 % to 60 %	—	40 % to 60 %	CMOS load: 50 % V_{CC} level
		40 % to 60 %	45 % to 55 %	—	TTL load: 1.4 V level
High output voltage	V_{OH}	V_{CC} -0.4 V Min.	2.4 V Min.	V_{CC} -0.4 V Min.	I_{OH} =-400 μ A(P,PTJ)/-4 mA(PH)
Low output voltage	V_{OL}	0.4 V Max.			I_{OL} =16 mA(P)/ 8 mA(PTJ)/ 4 mA(PH)
Output load condition (TTL)	L_{TTL}	10 TTL Max.	5 TTL Max.	—	$L_{CMOS} \leq 15$ pF
Output load condition (CMOS)	L_{CMOS}	50 pF Max.	—	50 pF Max.	
Output enable / disable input voltage	V_{IH}	2.0 V Min.	3.5 V Min.	2.0 V Min.	I_{IH} = 1 μ A Max. (OE= V_{CC})
	V_{IL}	0.8 V Max.	1.5 V Max.	0.8 V Max.	I_{IL} = -100 μ A Min. (OE=GND), PTJ: I_{IL} = -500 μ A Min. (OE=GND)
Output rise and fall time	t_r / t_f	8 ns Max.	—	7 ns Max.	CMOS load: 20 % V_{CC} to 80 % V_{CC} level
		8 ns Max.	5 ns Max.	—	TTL load: 0.4 V to 2.4 V level
Oscillation start up time	t_{osc}	4 ms Max.	10 ms Max.		Time at minimum supply voltage to be 0 s
Frequency aging	F_{aging}	$\pm 5 \times 10^{-6}$ / year Max.			+25 °C, V_{CC} =5.0 V, First year

*1 "B" tolerance will be available up to 55 MHz.

Specifications (characteristics)

Item	Symbol	Specifications			Remarks
		SG-615PCG SG-531PCG	SG-615SCG SG-531SCG	SG-615PCN	
Output frequency range	f_0	1.500 MHz to 26.000 MHz		26.001 MHz to 66.667 MHz	
Supply voltage	V_{CC}	2.7 V to 3.6 V			
Temperature range	Storage temperature T_{stg}	-55 °C to +125 °C			Store as bare product after unpacking
	Operating temperature T_{use}	-40 °C to +85 °C			
Frequency tolerance	$F_{tol(osc)}$	B: $\pm 50 \times 10^{-6}$ C: $\pm 100 \times 10^{-6}$ M: $\pm 100 \times 10^{-6}$			-20 °C to +70 °C -40 °C to +85 °C
Current consumption	I_{CC}	12 mA Max.		20 mA Max.	No load condition
Output disable current	I_{dis}	10 mA Max.	—	10 mA Max.	OE=GND (PCG,PCN)
Stand-by current	I_{std}	—	50 μ A Max.	—	\overline{ST} =GND (SCG)
Symmetry	SYM	45 % to 55 %			50 % V_{CC} level, L_{CMOS} =Max.
High output voltage	V_{OH}	V_{CC} -0.4 V Min.		V_{CC} -0.4 V Min.	I_{OH} =-8 mA
Low output voltage	V_{OL}	0.4 V Max.		0.4 V Max.	I_{OL} = 8 mA
Output load condition	L_{CMOS}	25 pF Max.		15 pF Max.	
Output enable / disable input voltage	V_{IH}	70 % V_{CC} Min.		70 % V_{CC} Min.	OE Terminal, \overline{ST} Terminal
	V_{IL}	20 % V_{CC} Max.		30 % V_{CC} Max.	
Output rise and fall time	t_r / t_f	4 ns Max.			20 % V_{CC} to 80 % V_{CC} level, $L_{CMOS} \leq$ Max.
Oscillation start up time	t_{osc}	12 ms Max.		10 ms Max.	$t=0$ at 90% V_{CC}
Frequency aging	F_{aging}	$\pm 5 \times 10^{-6}$ / year Max.			+25 °C, V_{CC} =3.3 V, First year

Specifications (characteristics)

Item	Symbol	Specifications			Remarks	
		SG-615PTW / STW SG-531PTW / STW	SG-615PHW / SHW SG-531PHW / SHW	SG-615PCW / SCW SG-531PCW / SCW		
Output frequency range	f ₀	55.001 MHz to 135.000 MHz		26.001 MHz to 135.000 MHz		
Supply voltage	V _{cc}	5.0 V ±0.5 V		3.3 V ±0.3 V		
Temperature range	Storage temperature	-55 °C to +125 °C			Store as bare product after unpacking	
	Operating temperature	-20 °C to +70 °C		-40 °C to +85 °C		
Frequency tolerance	F _{tol(osc)}	B: ±50 × 10 ⁻⁶ , C: ±100 × 10 ⁻⁶		M: ±100 × 10 ⁻⁶	-20 °C to +70 °C *1 -40 °C to +85 °C	
		—		—	—	
Current consumption	I _{cc}	45 mA Max.		28 mA Max.	No load condition(Max. frequency range)	
Output disable current	I _{dis}	30 mA Max.		16 mA Max.	OE=GND (PTW,PHW,PCW)	
Stand-by current	I _{std}	50 µA Max.			ST =GND (STW,SHW,SCW)	
Symmetry	SYM	—		40 % to 60 %	50 % V _{cc} level, L _{CMOS} =Max.	
		40 % to 60 %		—	—	1.4 V level, L _{CMOS} =Max.
High output voltage	V _{OH}	V _{cc} -0.4 V Min.			I _{OH} = 16 mA(PTW,STW,PHW,SHW), -8 mA(PCW,SCW)	
Low output voltage	V _{OL}	0.4 V Max.			I _{OL} = 16 mA(PTW,STW,PHW,SHW), 8 mA(PCW,SCW)	
Output load condition (TTL)	L _{TTL}	5 TTL Max.	—	—	f ₀ ≤ 90 MHz, Max.supply voltage	
Output load condition (CMOS)	L _{CMOS}	15 pF Max.			Max.frequency, Max.supply voltage	
Output enable / disable input voltage	V _{IH}	2.0 V Min.		70 % V _{cc} Min.	OE Terminal, ST Terminal	
	V _{IL}	0.8 V Max.		20 % V _{cc} Max.		
Output rise and fall time	t _r / t _f	—			4 ns Max.	20 % V _{cc} to 80 % V _{cc} level, L _{CMOS} ≤ Max.
		4 ns Max.		—	—	0.4 V to 2.4 V level
Oscillation start up time	t _{osc}	10 ms Max.			Time at minimum supply voltage to be 0 s	
Frequency aging	F _{aging}	±5 × 10 ⁻⁶ / year Max.			+25 °C, V _{cc} =5.0 V / 3.3 V, First year	

*1 "C" tolerance : f₀ ≥66.667 MHz(PTW,STW,PHW,SHW)

External dimensions

(Unit:mm)

Footprint (Recommended)

(Unit:mm)

● SG-615 series

● SG-531 series

● SG-51 series

● SG-615 series

Note.
 OE pin (P,PTJ,PH,PTW,PHW,PCW,PCN,PCG)
 OE pin = "H" or "open" : Specified frequency output.
 OE pin = "L" : Output is high impedance.
 ST pin (STW, SHW, SCW,SCG)
 ST pin = "H" or "open" : Specified frequency output.
 ST pin = "L" : Output is low level
 (weak pull - down), oscillation stops.

“3D STRATEGY” EPSON TOYOCOM

In order to meet customer needs in a rapidly advancing digital, broadband and ubiquitous society, we are committed to offering products that are one step ahead of the market and a rank above the rest in quality. To achieve our goals, we follow a “3D (three device) strategy” designed to drive both horizontal and vertical growth. We will to grow our three device categories of “Timing Devices”, “Sensing Devices” and “Optical Devices”, and expand vertical growth through a combination of products from these categories.

Quartz devices have become crucial in the network environment where products are increasingly intended for broadband, ubiquitous applications and where various types of terminals can transfer information almost immediately via LAN and WAN on a global scale. Epson Toyocom Corporation addresses every single aspect within a network environment. The new corporation offers “Digital Convergence” solutions to problems arising with products for consumer use, such as, core network systems and automotive systems.

PROMOTION OF ENVIRONMENTAL MANAGEMENT SYSTEM CONFORMING TO INTERNATIONAL STANDARDS

At Epson Toyocom, all environmental initiatives operate under the Plan-Do-Check-Action(PDCA) cycle designed to achieve continuous improvements. The environmental management system (EMS) operates under the ISO 14001 environmental management standard. All of our major manufacturing and non-manufacturing sites, in Japan and overseas, completed the acquisition of ISO 14001 certification. In the future, new group companies will be expected to acquire the certification around the third year of operations.

ISO 14000 is an international standard for environmental management that was established by the International Standards Organization in 1996 against the background of growing concern regarding global warming, destruction of the ozone layer, and global deforestation.

WORKING FOR HIGH QUALITY

Epson Toyocom quickly began working to acquire company-wide ISO 9000 series certification, and has acquired ISO 9001 or ISO 9002 certification for all targeted products manufactured in Japanese and overseas plants.

Epson Toyocom has acquired QS-9000 certification, which is of a higher level. Also, TS 16949 certification, which is also of a higher level, has been acquired.

QS-9000 is an enhanced standard for quality assurance systems formulated by leading U.S. automobile manufacturers based on the international ISO 9000 series.

ISO/TS 16949 is a global standard based on QS-9000, a severe standard corresponding to the requirements from the automobile industry.

Notice

- This material is subject to change without notice.
- Any part of this material may not be reproduced or duplicated in any form or any means without the written permission of Epson Toyocom.
- The information, applied circuitry, programming, usage, etc., written in this material is intended for reference only. Epson Toyocom does not assume any liability for the occurrence of infringing on any patent or copyright of a third party. This material does not authorize the licensing on for any patent or intellectual copyrights.
- Any product described in this material may contain technology or the subject relating to strategic products under the control of the Foreign Exchange and Foreign Trade Law of Japan and may require an export license from the Ministry of International Trade and Industry or other approval from another government agency.
- You are requested not to use the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes. You are also requested that you would not make the products available to any third party who may use the products for such prohibited purposes.
- These products are intended for general use in electronic equipment. When using them in specific applications that require extremely high reliability, such as the applications stated below, you must obtain permission from Epson Toyocom in advance.
/ Space equipment (artificial satellites, rockets, etc.) / Transportation vehicles and related (automobiles, aircraft, trains, vessels, etc.)
/ Medical instruments to sustain life / Submarine transmitters / Power stations and related / Fire work equipment and security equipment
/ traffic control equipment / and others requiring equivalent reliability.
- In this new crystal master for Epson Toyocom, product codes and markings will remain as previously identified prior to the merger. Due to the on-going strategy of gradual unification of part numbers, please review product codes and markings, as they will change during the course of the coming months.
We apologize for the inconvenience, but we will eventually have a unified part numbering system for Epson Toyocom that will be user friendly.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Epson manufacturer:

Other Similar products are found below :

[MA-505 24.0000M-C3 ROHS](#) [MC-405 32.7680K-G3: ROHS](#) [S5U13L02P00C100](#) [SG5032CAN 10.000000M-TJGA3](#) [SG-531P 7.3728MC:ROHS](#)
[X1G0044810005 SG7050CAN 10 MHZ](#) [SG531P IC Socket for 2520 case](#) [S5U1C31W74T1300](#) [S5U1C17W04T2100 IC Socket for 7050 case](#)
[S5U1C17W36T2100](#) [MC-306 32.7680K-E ROHS](#) [MA-505 24.0000M-C0:ROHS](#) [S5U13513P00C100](#) [S5U13781R01C100](#) [SG-210STF 13.5600ML3](#)
[SG-210STF 2.0480ML3](#) [Q3851CA000055 XG-1000CA 50 MHZ](#) [EG-2121CA 644.53125MLGPA](#) [SG-636PCE 25.0000MC3:ROHS](#) [MA-506](#)
[4.0000M-C3 ROHS](#) [EG-2121CA2000000M-LGPAL3](#) [S5U13U00P00C100](#) [S5U13513R00C100](#) [S5U13517P00C200](#) [FA-238 16.0000MB50X-A3](#)
[S5U13748P00C100](#) [S5U1C17W18T2100 IC Socket for 5032 case](#) [SG-210STF 8.0000ML](#) [Q325310110003 SG-531P 10 MHZ C](#) [MA-506 25.0000M-](#)
[C3:ROHS](#) [M160](#) [S5U1C17M13T2100](#) [S5U1C17M13T1100](#) [SG-210STF 7.3728ML3](#) [FC-12M 32.7680KA-AC0](#) [M150](#) [S5U1C17W15T2100](#) [XG-](#)
[2121CA 156.2500M-PGSNB](#) [SG-210STF 32.7680ML](#) [SG-636PTF 20.0000MC3: ROHS](#) [SG-210STF 27.0000ML0](#) [SG-8002JC MP BLANK:ROHS](#)
[SG5032CCN 14.745600M-HJGA3](#) [SG-615P 2.0000MC: ROHS](#) [Q13FC13F00001 FC-13F 32.768KHZ 12.5PF](#) [MA-306 18.4320M-C0:ROHS](#) [EG-](#)
[2121CA 156.2500M-LHPAB](#)