



<b>DATA SHEET</b>	0091300
<b>ÖLFLEX® HEAT 260 MC</b>	valid from : 05.02.2008

## Application

ÖLFLEX® HEAT 260 MC cables are heat resistant cables. Besides having excellent mechanical, thermal and physical properties, ÖLFLEX® HEAT 260 MC cables are characterized by very good electrical values as well as outstanding resistance against oil, weather and UV-radiation. In addition these cables are resistant against the action of water, acids, caustic solutions, solvents, paints, petrol and oils. They have also high dielectric strength and high abrasion resistance. The cables are flame retardant.

## Design

Conductor	fine strands of nickel plated copper wires acc. to IEC 60228 resp. VDE 0295, class 5
Core insulation	PTFE compound 5Y11 in acc. to VDE 0207 part 6 (polytetraflouroethylene)
Core identification	acc. to VDE 0293-1, with or without gn/ye ground conductor up to 5 cores coloured in acc. to HD 308 S2 resp. VDE 0293-308
Cable design	cores twisted together, PTFE-tape wrapping
Outer sheath	PTFE compound 6YM1 in acc. to VDE 0207 part 6, black

## Electrical properties at 20 °C

Nominal voltage	300 V / 500 V
Test voltage	3400 V AC

## Mechanical and thermal properties

Temperature range	-190 °C up to +260 °C max. conductor temperature for short time up to +300 °C
Min. bending radius	4 x cable diameter for fixed installation 15 x cable diameter for flex. applications
Tests	acc. to IEC 60811-x-x resp. VDE 0473 part 811-x-x and VDE 0472
EC directive	this cable confirms to ECD 2006/95/EC (low voltage directive).

elaborated by: TE-K: M. Herb / R. Krämer	Document: DB0091300EN	page 1 of 1
---	-----------------------	-------------

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Specialised Cables category](#):*

*Click to view products by [Lapp Kabel manufacturer](#):*

Other Similar products are found below :

[GP-IE515546DS-002](#) [96CB-L2020PIB2](#) [1200740161](#) [R88ACAKA0015SRE](#) [R88ACAWL005SDE](#) [1300660042](#) [1300660201](#) [1971465-2](#)  
[22733-8](#) [2R7004A20F060](#) [SSL009PC2DC012N](#) [FC2A-KC6C](#) [CCSFCBF2](#) [R7ACAB005S](#) [XS2WM12PUR4SA10M](#)  
[XS2WM12PVC4SA10M](#) [05AU05](#) [UCABLE](#) [10114734-2010LF](#) [XW2Z010H3](#) [XW2Z010H1](#) [5-1589827-8](#) [5-1589827-4](#) [861084-1](#)  
[XW2Z200JB24](#) [5-1589956-8](#) [CR4000A76M020](#) [1201140211](#) [1300140039](#) [CR4000A76M005](#) [CR4006A76M005](#) [10077488-N0550FDLF](#)  
[XW2ZRY150C](#) [I4JPBJLUXX100](#) [I4JPBJLUXX50](#) [CM06](#) [CM06W](#) [POE004](#) [0243 009 05](#) [0243 009 20](#) [0243 009 36](#) [0243 009 26](#) [0243 009](#)  
[23](#) [0243 009 01](#) [0243 009 30](#) [0243 008 05](#) [0243 008 20](#) [0243 008 36](#) [0243 008 23](#) [0243 008 01](#)