

# PROGRAMMING TOOL FOR SG-8000 SERIES



## SG - Writer II

 Programming tool for EPSON programmable oscillator SG-8000 series (Blank oscillator).

Able to program required frequency at customer side

- •External power supply by USB cable.
- •Available PC OS
- Windows7(32bit,64bit)etc,
- •Small body and easy carry.



#### Main Body Specifications

Name	SG-Writer II for Epson SG-8000 Series			
Operating Temperature	+10 °C to +40 °C Writing (+25 °C ±5 °C)			
Electric Power Supply	Via USB			
Standard Interface	USB 2.0 (Mini-b)			
Accessories	SG-Writer II			
	Instruction manual (Documents : Japanese, English)			
Software	SG-Writer II			
Option	Model	Product number	Model	Product number
SMD socket	SG-8003CG	Q91PR10W00024	SG-8002CE	Q91PR10W00010
*1	SG-8003CE	Q91PR10W00018	SG-8002LB	Q91PR10W00011
	SG-8003LB	Q91PR10W00019	SG-8002JF	Q91PR10W00006
	SG-8003JF	Q91PR10W00020	SG-8002CA	Q91PR10W00005
	SG-8003CA	Q91PR10W00021	SG-8002JC	Q91PR10W00004
			SG-8002JA	Q91PR10W00003
Onting		T =	1	
Option	Model	Product number	Model	Product number
Blank sample	SG-8003CG 1.8V	X1G0039910001	SG-8002CE	Q3321CE000001
	SG-8003CG 2.5V,3.3V	X1G0039910002	SG-8002LB	Q3323LB010002
	SG-8003CE 1.8V	Q33519E000001	SG-8002JF	Q3308JF020002
	SG-8003CE 2.5V,3.3V	Q33519E000002	SG-8002CA	Q3309CA000002
	SG-8003LB 1.8V	X1G0033010001	SG-8002JC	Q3307JC010002
	SG-8003LB 2.5V,3.3V	X1G0033010002	SG-8002JA	Q3306JA020002
	SG-8003JF 1.8V	X1G0030220001	SG-8002DC	Q3204DC010002
	SG-8003JF 2.5V,3.3V	X1G0030220002	SG-8002DB	Q3203DB010002
	SG-8003CA 1.8V	X1G0032310001		
	SG-8003CA 2.5V,3.3V	X1G0032310002		

<sup>\*1</sup> If you have SMD socket of either SG-8002 series or SG-8003 series, it can use for both SG-8002 series and SG-8003 series.

If you are using SG-Writer II now and will purchase SMD socket newly, please choose SG-8003 series socket (Except JC, JA package).

#### Recommend PC Specifications (You need to connect the SG-Writer II to a PC when you are writing.)

Available PC OS	Windows 7(32bit,64bit)	
	Windows Vista(32 bit type)	
	Windows XP(32 bit type)	
Recommend CPU	Over Pentium 4 1.4GHz or equivalent Processor	
Recommend memory Capacity	Windows XP : Over 512MB	
	Windows Vista, Windows7 32bit : Over 1GB	
	Windows 7 64bit : Over 2GB	
	USB cable(Type A ↔ Mini-b)	
Other	Need SMD *2 socket when you write SG-8000 SMD products.	
	(Sold individually)	

<sup>\*2</sup> Conventional SMD socket for PROM Writer or SG-Writer (the previous model) can be used for SG-Writer II.

#### Precautions

•SG-8003 series has two types of Blank sample. Please write with correct typed sample shown below.

Vcc = 1.8 V type (For PE,SE)

Vcc = 2.5 V and 3.3 V type (For PD,SD,PC,SC)

\*It is able to identify Blank sample between SG-8002 series and SG-8003 series by marking.

•SG-8000 series common software still can write SG-8002 series.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

### Click to view similar products for epson manufacturer:

Other Similar products are found below:

MA-505 24.0000M-C3 ROHS MC-405 32.7680K-G3: ROHS FA-128 25.0000MF10Z-AC S5U13L02P00C100 SSU13U11P00C100 SG5032CAN 10.000000M-TJGA3 SG5032VAN 200.000000M-KEGA3 SG-210STF 2.0480ML3 SG-531P 7.3728MC:ROHS X1G0044810005 SG7050CAN 10 MHZ S5U1C31W74T1300 S5U1C17W04T2100 IC Socket for 7050 case SG-210STF 40.0000ML TSX-3225 26.0000MF10Z-B6 S5U13513P00C100 SG-210STF 13.5600ML3 SG5032CCN 16.000000M-HJGA3 Q3851CA000055 XG-1000CA 50 MHZ EG-2121CA 644.53125MLGPA M160 MA-506 4.0000M-C3 ROHS EG-2121CA2000000M-LGPAL3 S5U13U00P00C100 FA-118T 52.0000ME12Z-AC3 SG-Writer-II S5U1C17001H3100 S5U13513R00C100 IC Socket for 5032 case SG-210STF 4.0960ML S5U13517P00C200 S5U13748P00C100 S5U1C17W18T2100 SG-310SCF 20.0000MM S5U13781R01C100 Q336150110002 SG-615P 20 MHZ C MA-506 25.0000M-C3:ROHS S5U1C17M13T2100 S5U1C17M13T1100 TG-3541CE 32.7680KXB3 FA-238 25.0000MB50X-C3 RX-8803LC:UB3 PURE SN SG-3030LC 32.7680KB3, PURE SN SG-615P 8.0000MC3: ROHS Q3102JF010001 SG-3030JF 32.768KHZ B M150 S5U1C17W15T2100 FC-135 32.7680KA-K0 XG-2121CA 156.2500M-PGSNB FA-128 25.0000MF20X-WX