

AC/DC Current Probes – CP1- SERIES

Accurate, Rugged, Versatile and Reliable

- *Two models Multimeter (CP1000) and Oscilloscope (CP1005)*
- *Measurement of AC / DC and complex current waveforms*
- *1000A Range (CP1000) 100A / 1000A Ranges (CP1005)*
- *Excellent Accuracy with high resolution*
- *Wide Bandwidth with low phase shift*
- *DC Auto Zero and Auto Power Off*
- *Compact lightweight design*
- *Output voltages 1mV/A and 10mV/A (CP1005)*
- *Superior noise rejection for power electronics applications*



High Accuracy with Superior External Field Rejection

Advanced magnetic circuit design results in probes accuracy to be little affected by external magnetic fields or off-centre conductor positioning.

EN61010-2-032:2002 and EMC Conformance

Safety features including a tactile barrier and special jaw design provide the user with confidence when making measurements in hazardous voltage areas.

Conformance to EMC standards ensures high reliability through reduced susceptibility to electromagnetic interference.

TYPICAL APPLICATIONS

- Light industrial and residential electrical installation testing
- Battery charging systems
- Analysis of switching waveforms in inverters, switch mode power supplies and industrial controls
- Automotive applications eg., Cranking current measurement on car battery lead, current profiling, all requiring high accuracy and superior resolution.

CP1 SERIES_090817_03

GMC-I PROSyS Ltd.

Allied Business Centre | 1 Potter Place | Skelmersdale | Lancashire | WN8 9PH | United Kingdom
Telephone: +44 (0) 1695 567280 | Fax: +44 (0) 1695 567299
www.i-prosys.com | sales@i-prosys.com

Registered Company Number: 5116760
Vat Number: GB863880193

SPECIFICATIONS

NON-INVASIVE CURRENT MEASUREMENT

MODEL	CP1000	CP1005
Current Range (RMS)	1000A	100 / 1000A
Output Sensitivity	1mV/A	10 / 1mV/A
Resolution	± 500mA	±100mA / ±500mA
Basic Accuracy	± 1% of reading ± 0.5A	± 1% of rdg ± 0.1A / ± 0.5A
Conductor position sensitivity	< ± 1% relative to centre reading	
Frequency Range (-3dB)	10kHz	20kHz
Phase shift (up to 1kHz)	N/A	< 2 degrees
Load Impedance	> 100 kOhms	
Output connection	Safety 4mm plugs	Safety BNC connector

ENVIRONMENTAL DATA

Operating Temperature	0°C to 50°C (32°F to 122°F)
Temp. Coefficient	± 0.15% of reading per °C
Storage Temperature (without battery)	-20°C to 85°C

SAFETY

EN61010-2-032:2002,
300V, Measurement Category III, Pollution Degree 2.

MAXIMUM SAFE VOLTAGES

300V AC RMS or DC between uninsulated conductor and ground

POWER SUPPLY

Battery type	9v Alkaline: MN1604, PP3 IEC 6LR61 or equivalent
Battery life	50 hours typical

EMC Standard EN 61326-2-2:2006

All accuracies stated at 23°C ± 1°C (73.4°F ± 1.8°F)

MECHANICAL DATA

Dimensions (mm)	200 (H) x 74 (W) x 25 (D)
Jaw Capacity	32mm ∅
Weight	320gr.

Part No's	MODEL
P-12.600.1	CP1000
P-12.600.2	CP1005

GMC-I PROSyS Ltd. offer a wide range of non-invasive Probes and Clamp Meters for the measurement and analysis of Current and Voltage

CP1 SERIES_090817_03

GMC-I PROSyS Ltd.

Allied Business Centre | 1 Potter Place | Skelmersdale | Lancashire | WN8 9PH | United Kingdom
 Telephone: +44 (0) 1695 567280 | Fax: +44 (0) 1695 567299
 www.i-prosys.com | sales@i-prosys.com

Registered Company Number: 5116760
 Vat Number: GB863880193

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [gmc-i prosys](#) manufacturer:

Other Similar products are found below :

[GMC-I Prosys](#)