


# SANYO

## Cadnica




## Cell Type KR-AAH Specifications


Nominal Capacity		600mAh
Nominal Voltage		1.2V
Charging Current	Trickle	20mA
	Standard	60mA
Charging Time	Trickle	above 48Hrs.
	Standard	14 to 16Hrs.
Ambient Temperature	Charge	0°C to +70°C [+32°F to 158°F]
	Discharge	-20°C to +70°C [-4°F to 158°F]
	Storage	-30°C to +70°C [-22°F to 158°F]
Internal Impedance (Av.) (at 50% discharge)		18.0mΩ (at 1000Hz)
Weight		23g/0.81oz
Dimensions(D)×(H) (with tube)		14.3 <sup>0</sup> <sub>-0.5</sub> × 48.9 <sup>0</sup> <sub>-1</sub> mm 0.56 <sup>0</sup> <sub>-0.02</sub> × 1.93 <sup>0</sup> <sub>-0.04</sub> inch

### Typical Characteristics


Charge




Discharge (at high rate)




Charge




Discharge Trickle charge (at high temperature)



Discharge (at low rate)



Temperature (Charge & Discharge)



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [sanyo denki manufacturer](#):*

Other Similar products are found below :

[9A0812G401](#) [9A0824H401](#) [9G0824H102](#) [9GA0812P1H61](#) [9GA0812P1S61](#) [9GL1212F101](#) [9GV1412P1G001](#) [9GV3612G301](#)  
[9WG1212H102](#) [9WG1224G101](#) [SM2861-5255](#) [9GT0912P1M001](#) [9GV0312E302](#) [9S1212F4011](#) [9SG5748P5H01](#) [9WG1212E101](#) [489-007-](#)  
[L21](#) [103H5208-5240](#) [103H7126-1740](#) [103H7822-5740](#) [109-1001F13](#) [109-1003M30](#) [109-313](#) [109L1748H501](#) [109L5712H501](#)  
[109P1412M101](#) [109R0824S4D01](#) [109-1069](#) [109BF24HD2](#) [9L0412H301](#) [9GA0812P1S61P](#) [9G1212P4G03](#) [9G0612P1G03](#)  
[9CRB0812P8G001](#) [103H8221-5141](#) [103H8223-6340](#) [9LG1248P1H001](#) [SH1603-5240](#) [9GA0812P1H611](#) [9BD12SC6-1](#) [109P0824H701](#) [109-](#)  
[049C](#) [103H7123-5740](#) [9AH0912P4H03](#) [9G1224G1D01](#) [9GV1212P4G011](#) [9G1224M4D011](#) [9GV0824P1G03](#) [109P0624W602](#)  
[9WF0924S201](#)