


# Carolprene® Welding Cable

90°C 600 Volt



### Product Construction:

#### Conductor:

- 6 AWG through 500 kcmil fully annealed stranded bare copper Class K

#### Jacket:

- Premium-grade 90°C EPDM, red
- Temperature range: -40°C to +90°C

#### Jacket Marking:

- CAROLPRENE (SIZE) WELDING CABLE 600 VOLT MADE IN USA

#### Applications:

- Secondary voltage resistance welding leads
- Power supply applications not exceeding 600 volts AC

#### Features:

- Good flexibility
- Abrasion-resistant
- Good color retention

#### Packaging:

- 250' (76.2 m), 500' (152.4 m), and 1000' (304.8 m) reels
- MCM sizes cut to length
- Other put-ups available on special order

#### Industry Approvals:

- RoHS Compliant

### CAROLPRENE® WELDING CABLE – 600 VOLT – CLASS K – 30 AWG STRANDING

CATALOG NUMBER	COND. SIZE (AWG/kcmil)	CONDUCTOR STRAND	NOMINAL O.D.		APPROX. NET WT. LBS/M <sup>(15)</sup>	STD. CTN.
			INCHES	mm		
01778	6	259/30	0.380	9.65	135	250'
01777	4	374/30	0.400	10.16	172	250'
01776	2	625/30	0.465	11.81	260	250'
01775	1	778/30	0.495	12.57	317	250'
01774	1/0	990/30	0.560	14.22	400	250'
01773	2/0	1248/30	0.615	15.62	487	250'
01772	3/0	1586/30	0.670	17.02	605	250'
01771	4/0	2054/30	0.750	19.05	827	250'
99142*	250	2496/30	0.830	21.08	976	250'
99432*	350	3432/30	0.960	24.38	1338	250'
99202*	500	5054/30	1.200	30.48	1995	250'

<sup>(15)</sup> Actual shipping weight may vary.  
\* Non-stock item, minimum quantity required.

## WELDING CABLE AMPACITIES SINGLE CONDUCTOR

Required Cable Sizes: For Welding Cable Application

AMPS	length in feet for total circuit for secondary voltages only – do not use this table for 600 Volt in-line applications						
	100'	150'	200'	250'	300'	350'	400'
100	4	4	2	2	1	1/0	1/0
150	4	2	1	1/0	2/0	3/0	3/0
200	2	1	1/0	2/0	3/0	4/0	4/0
250	1	1/0	2/0	3/0	4/0		
300	1/0	2/0	3/0	4/0			
350	1/0	3/0	4/0				
400	2/0	3/0					
450	2/0	4/0					
500	3/0	4/0					
550	3/0	4/0					
600	4/0						

**REQUIRED CABLE SIZES SHOWN IN AWG NUMBERS**

The total circuit length includes both welding and ground leads (based on 4-volt drop) 60% duty cycle.

These values for current-carrying capacity are based on a copper temperature of 60°C (140°F), an ambient temperature of 40°C (104°F) and yield load factors from approximately 32% for the No. 2 AWG cable to approximately 23% for the No. 3/0 AWG cable, and higher for the smaller sizes. The sizes of cables generally used range from No. 2 AWG to No. 3/0 AWG. In actual service, the load factor may be much higher than indicated without overheating the cable, as the ambient temperature will generally be substantially lower than 40°C.

### Suggested Ampacities:

#### For 600 Volt In-Line Applications

AWG/kcmil	AMPERES	AWG/kcmil	AMPERES
500	695	1/0	190
350	552	1	160
250	445	2	140
4/0	310	4	100
3/0	265	6	75
2/0	223		

Ampacities for portable cable, continuous-duty (ambient temperature of 40°C). May not be suitable for all installations per National Electrical Code®.

### Ordering Part Number Example

**01771.38.03**

4/0 500' put-up in red  
.03 for red jacket



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [carol manufacturer](#):*

Other Similar products are found below :

[01364.35T.01](#) [C1321.41.01](#) [C2015A.12.04](#) [C4066A.38.10](#) [01104.99.01](#) [01343.35T.01](#) [02728-85-01](#) [5133290E](#) [2133016](#) [16065.41.01](#)  
[5131431E](#) [09814.99.01](#) [E2206S.41.86](#) [E1524S.41.03](#) [E2534S.41.03](#) [C2016A.12.03](#) [C2064A.12.02](#) [C0570A.41.10](#) [C1343A.41.10](#)  
[C1357.41.90](#) [C2405A.41.10](#) [C1352A.41.10](#) [C2536A.38.10](#) [C1361.38.90](#) [E2204S.41.02](#) [E3612S.41.03](#) [E1032S.25.10](#) [02604.41T.05](#)  
[02605.41T.05](#) [02608.41T.05](#) [02632.35T.05](#) [02634.41T.05](#) [02601.41T.05](#) [01360.35T.01](#) [01342.35T.01](#) [C-8002-12](#) [01380.35T.01](#)  
[01774.35T.01](#) [5133274E](#) [C2040A.21.03](#) [C2104A.12.06](#) [C1302.41.01](#) [E2032S.41.10](#) [E2242S.41.86](#) [E1502S.25.03](#) [E2004S.18.10](#)  
[02601.35T.05](#) [02602.35T.05](#) [02635.35T.05](#) [06200.61.06L](#)