



General ordering data

Order No.	0193260000
Short text for material	SAK 6N
EAN	4008190031893
Qty	100

IEC/EN 60079-7 rating data

Certificate No.	KEMA97ATEX1798U
max. voltage	550 V
Current	36 A
Conductor cross-section, max.	6 mm ²
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

Additional technical data

Type of connection	screwed
No. of identical terminals	1
Version	Feed-through terminal
Type of mouting	clipped
UL 94 flammability rating of insulation material	V2
Installation advice	TS 32
Colour of insulating material	beige
Insulating material	PA 66
Open sides	right
Operating temperature range	- 50 °C, + 100 °C
Connection direction	on side
No. of levels	1
Levels cross-connected internally	No
No. of terminal strips per level	2
Explosion-tested version "Ex e"	No
End plate required	Yes

CSA rating data

Min. cross-section (CSA)	AWG 20
Voltage CSA	600 V
Max. cross-section (CSA)	AWG 8
CSA current	47 A

Conductors for clamping (rated connection)

Stripping length	12 mm
Type of connection	Screw connection
No. of connections	2
Torque level with DMS electric screwdriver	3
Twin wire-end ferrule, min.	0,50 mm ²
Twin wire end ferrule, max.	4,00 mm ²
Tightening torque range	0.8...1.6 Nm
Solid, max.	10 mm ²
Flexible, max.	10 mm ²
flexible w. ferrule AEH, max. DIN 46228-1	6 mm ²
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	6 mm ²
flexible w. ferrule AEH, min. DIN 46228-1	0,5 mm ²
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0,5 mm ²
Clamping range, max.	10 mm ²
Clamping range, min.	0,33 mm ²
Clamping screw	M 3.5
Blade size	4.0 x 0.8 mm
Gauge to IEC 60947-1	A5
AWG conductor size, max.	8,37 mm ²
Stranded, max.	6 mm ²
Stranded, min.	0,5 mm ²
AWG conductor size, min.	AWG 22
Flexible, min.	0,5 mm ²
2nd type of connection	screwed
Solid, min.	0,5 mm ²
Connection direction	on side

Dimensions

TS 32 offset	4 mm
Height of lowest version	51,5 mm
Length	40 mm
Width	8 mm

Disconnect terminals

Torque level with DMS electric screwdriver	3
--	---

Rating data

Rated cross-section	6 mm ²
Rated voltage	800 V
Rated impulse withstand voltage	8 kV
Rated current	41 A
Norm	IEC 60947-7-1
Current with max. conductor	57 A
Pollution severity	3

UL rating data

Current (UL)	40 A
Voltage UL	600 V
Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 8

Approvals

Approvals CSA;GOST;0344;UL/UR;EX;CE;

Approvals



Approvals

Approvals



Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

Related products

Order No.	Short text for material
0193280000	SAK 6N BL

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [weidmuller](#) manufacturer:

Other Similar products are found below :

[56956](#) [0133660000](#) [68676](#) [69718](#) [EXO24CH](#) [7940000218](#) [8005181001](#) [8008180000](#) [8432240000](#) [8463580000](#) [8545830000](#) [8689870000](#)
[8705640000](#) [9001080000](#) [9003720000](#) [9004250000](#) [9004780000](#) [9013260000](#) [9014100000](#) [9019040000](#) [9026010000](#) [9028630000](#) [903708](#)
[9037350000](#) [9046290000](#) [9129643500](#) [913155](#) [919656](#) [919764](#) [9202230000](#) [9202850000](#) [9204260000](#) [9456750000](#) [9457913000](#) [980811](#)
[980826](#) [9912800003](#) [9916080000](#) [9916280012](#) [9918380000](#) [9919371224](#) [9925710000](#) [9926252005](#) [9927480024](#) [1166660000](#) [11751](#)
[1222550000](#) [ACT20X-2HDI-2SDO-RNC-S](#) [ACT20X-HUI-SAO-S](#) [ACT20X-SAI-HAO-S](#)