

# TLS Preset Clean Room Torque Screwdrivers

## Torque range from 0.04 to 13.6 N.m

Clean Room (CRS) Class 100

Want to know how to use this tool?



Watch our video

### Industry Sectors

Manufacturing



Automotive



Electronics



Military



Consumer Products

### Slipping Mechanism

Incorrect tightening is impossible



CRS 100-0022 FH



### Key Benefits

- These tools are designed to protect precision products from contamination during assembly. They are designed specifically for use in **Clean Rooms** by utilising suitable surface treatments and incorporating high performance seals in their design
- Operator fatigue is minimised by the soft reset action of the tool
- Complete control of the tightening process is achieved by eliminating both under and over tightening as these tools incorporate Torqueleader's slipping mechanism
- Suitable for use by operators of any skill level, as these tools will repeatedly deliver the set torque without the need for operator intervention due to the tamper-proof design

Order now... call our Sales Hotline +44 (0) 1483 894 476

Order Code	Model	Range		Drive	k mm	g	Repeatability	ISO 6789 Class	Colour
		ISO	Imperial						
015089	CRS 100-0022 FH	4-22 cN.m	6-32 ozf-in		104	072	+/- 6%	2F	Grey
015209	CRS 100-0135 FH	10-135 cN.m	0.9-12 lbf-in		111	210	+/- 6%	2F	Grey
015609	CRS 100-0406 FH	50-400 cN.m	4.4-36 lbf-in		127	280	+/- 6%	2F	Grey
015939	CRS 100-1360 FH	2.5-13.6 N.m	22-120 lbf-in		137	325	+/- 6%	2F	Grey



CRS Torque Screwdrivers are preset type torque tools. They must be set to the required value by using a **Torque Analyser**... see pages 45-52 for details

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [torqueleader](#) manufacturer:*

Other Similar products are found below :

[CRS 100-1360 FH](#) [QTC 55 0.9-55NM 035220](#) [ESD 450 FH](#) [ADS 25](#) [TT 50 F/HEX](#) [ESD 25 FH](#) [PRO 150 FH](#) [PRO 450 FH](#) [017500](#) [PRIME](#)  
[450 FH](#) [016500](#) [015200](#) [QSN 120 FH](#) [ESD 1350 FH](#) [CRS 100-0135 FH](#)