
693 LED Signal Tower Kompakt 36 in metal design









- Clear domes ensure signalling effect even in direct sunlight
- Plastic housing with aesthetic metal coating
- LED Permanent light elements with life duration up to 50,000 hours
- Simplified ordering through ready-assembled tower
- 36 mm diameter
- Can be operated with PLC control
- Available with user-friendly plug connection

TECHNICAL SPECIFICATIONS:

Dimensions (Diameter x Height): 2 tier: 36 x 113 mm

3 tier: 36 x 147 mm

Housing: Housing parts PC Fixing: Base mounting

Tube mounting Bracket mounting

Connection: cable, 2 m long,

M12 plug,

each with adapter M25 / M20 for

fixing rubber seal

Operating voltage: 24 V DC **Current consumption:** 40 mA per tier

Starting current: < 500 mA can be triggered via PLC

ORDER SPECIFICATIONS:

		Order no.	Connection type
2 tier	red/green	693 080 55	cable
	red/yellow	693 090 55	cable
	red/green	693 580 55	plug-type
	red/yellow	693 590 55	plug-type
3 tier	red/yellow/green	693 070 55	cable
	red/yellow/green	693 570 55	plug

Available from June 2005

ACCESSORIES:

Fixing bracket, black	960 693 01
Cable gland M20 x 1.5	960 693 02
Base with integrated tube M25 x 1.5	960 693 06
including rubber seals, silver	
M12 counter-plug with 5m cable	960 693 05



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for werma manufacturer:

Other Similar products are found below:

64330068	64411068	<u>64751075</u>	14095060	42532068	<u>64310055</u>	64712055	64722055	64732055	$\underline{82810055}$	85320055	57005258	63081000
85310060	20310000	64752055	64411075	64721075	82620000	20410075	42432075	69831075	85311060	85330055	82830055	64421075
57005267	58400068	95584035	96000014	42412075	82610000	82630000	64731075	14095050	57005268	64150000	21330000	58015255
44430075	64589075	97584091	42432068	63082000	13400075	15010055	64140000	64580068	14015060	64083000		