

MODELS:



FEATURES/BENEFITS:



-LOW INSERTION FORCE MAY REDUCE RISK OF REPETITIVE TRAUMA INJURY -WIDE WIRE RANGE FOR EASY INSTALLATION AT OEM AND IN FIELD -TOUCH-SAFE DESIGN ON BOTH HALVES, MEETS UL/CSA REQUIREMENT -MULTI-CONTACT DESIGN ALLOWS SAFE DISCONNECT UNDER LOAD -DUAL PORTS ON 103 SUPPORT BOTH SWITCHING & FULL LIGHT OUTPUT -DUAL PORTS ON 102X ALLOW ONE DISCONNECT ON FULL LIGHT OUTPUT


ELECTRICAL:		MECHANICAL:		
VOLTAGE: CURRENT: CURRENT INTERRUP	600 V MAX 6 A MAX TION: 10 CYCLES	18 AWG INSERTION FORCE: ½"KO (0.875" HOLE):	3 LB (13 N) MAX COMPLIANT	
PHYSICAL:		STANDARDS & SPECIFICATIONS:		
HOUSING: CONTACTS: PLATING: TEMPERATURE: STRIP LENGTH (LOAD STRIP LENGTH (LINE): COLOR: POLARIZED:		UL 2459 CSA- C22.2 NO. 2459-08 RoHS COMPLIANT NEC 2008 410.130(G) COMPLIANT CEC 30-308(4) COMPLIANT UL 94V-0 FLAME RATING US PATENT 7,473,123 OTHER US & FOREIGN PATENTS PENDING		

WIRF RANGE:


WINE NAME.						
	ORANGE CAP	102 WHITE CAP	103 WHITE CAP			
SOLID	12 -18 AWG	12 -18 AWG	18 AWG			
STRANDED	12-14 AWG (≤19 STRAND)	12-14 AWG (≤19 STRAND)	N/A			
TIN BONDED	12 AWG (≤19 STRAND) 14 AWG (≤19 STRAND) 16 AWG (≤26 STRAND) 18 AWG (≤16 STRAND)	12 AWG (≤19 STRAND) 14 AWG (≤19 STRAND) 16 AWG (≤26 STRAND) 18 AWG (≤16 STRAND)	18 AWG (≤16 STRAND)			

DIMENSIONS:











MODEL 102X

MODEL 102

MODEL 103

ORDERING INFO:

CATALOG#	MODEL	# CIRCUITS	PACKAGE TYPE:	WEIGHT LBS (KG):
30-102	102	2	1,000 PIECE CARTON	13.6 (6,2)
30-102X	102X	2	1,000 PIECE CARTON	13.6 (6,2)
30-103X	103	3	1,000 PIECE CARTON	18.8 (8,5)

SALES CONTACT:

FACTORY CONTACT:

ENGINEERED SOLUTIONS IDEAL INDUSTRIES, INC. BECKER PLACE SYCAMORE IL USA 60178

P: 1-800-324-9571 F: 1-888-222-6140

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for ideal industries manufacturer:

Other Similar products are found below:

30-103X 50-2100AN 50-686SF 50-686SM 30-152 50-2100LN 50-2101CR 50-682SF 30-1186M 50-2100MR 30-1186F 30-682F 30-1634 30-682SM 30-682SF 30-1642