

+135°C

20 MV/m





General purpose, flame retarded, polyolefin heat-shrinkable tubing



- Very good chemical and solvent resistance
- Wide range of colours including green/yellow stripes
- Flexible
- Excellent physical and electrical performance

CGPT is a tough, flexible, general purpose polyolefin tubing with good resistance to common fluids and solvents and a high dielectric strength. Available in 2:1 and 3:1 shrink ratios its unique blend of chemical, electrical and physical properties makes it suitable for a wide range of applications including electrical insulation, strain relief, cable bundling, colour coding and identification of wires, cables, pipes and electrical and electronic components and mechanical protection.

Ordering information

| | Inside diameter | | Wall thickness | Standard package | |
|------------------|------------------------------------|---------------------------------------|---------------------------------------|---------------------|-----------------------------------|
| | D (min) Expanded as supplied | d (max) Recovered after heating | W (nom) Recovered after heating | Spool quantity | |
| mm | mm | mm | mm | m | Ordering description |
| 2:1 Shrink ratio | 1.2 | 0.6 | 0.45 | 300 | CGPT-1.2/0.6-colour code |
| | 1.6 | 0.8 | 0.45 | 300 | CGPT-1.6/0.8-colour code |
| | 2.4 | 1.2 | 0.50 | 150 | CGPT-2.4/1.2-colour code |
| | 3.2 | 1.6 | 0.50 | 150 | CGPT-3.2/1.6-colour code |
| | 4.8 | 2.4 | 0.50 | 150 | CGPT-4.8/2.4-colour code • |
| | 6.4 | 3.2 | 0.65 | 75 | CGPT-6.4/3.2-colour code • |
| | 9.5 | 4.8 | 0.65 | 121 | CGPT-9.5/4.8-colour code-FSP* ● |
| | 12.7 | 6.4 | 0.65 | 91 | CGPT-12.7/6.4-colour code-FSP* • |
| | 19.0 | 9.5 | 0.75 | 60 | CGPT-19/9.5-colour code-FSP* • |
| | 25.4 | 12.7 | 0.90 | 60 | CGPT-25.4/12.7-colour code-FSP* • |
| | 32.0 | 16.0 | 0.95 | 30 | CGPT-32/16-colour code • |
| | 38.0 | 19.0 | 1.00 | 30 | CGPT-38/19-colour code • |
| | 51.0 | 25.4 | 1.15 | 30 | CGPT-51/25.4-colour code |
| | 76.0 | 38.0 | 1.25 | 15 | CGPT-76/38-colour code |
| - | 102.0 | 51.0 | 1.40 | 15 | CGPT-102/51-colour code |
| 3:1 Shrink ratio | 1.5 | 0.5 | 0.45 | 300 | CGPT-1.5/0.5-colour code |
| | 3.0 | 1.0 | 0.55 | 150 | CGPT-3/1-colour code |
| | 6.0 | 2.0 | 0.65 | 75 | CGPT-6/2-colour code |
| | 9.0 | 3.0 | 0.75 | 75 | CGPT-9/3-colour code |
| | 12.0 | 4.0 | 0.75 | 75 | CGPT-12/4-colour code |
| | 18.0 | 6.0 | 0.85 | 75 | CGPT-18/6-colour code |
| | 24.0 | 8.0 | 1.00 | 30 | CGPT-24/8-colour code |
| | 39.0 | 13.0 | 1.15 | 30 | CGPT-39/13-colour code |

| *Material supplied on Flat Spooled Pac | kaging (FSP) as standard |
|--|--------------------------|
|--|--------------------------|

| Standard colours | Black | Red | Yellow | Green |
|-------------------|-------|--------|--------|--------------------------------------|
| Standard Code | 0 | 2 | 4 | 5 |
| | Blue | White | Clear | Green/Yellow stripes (sizes marked) |
| | 6 | 9 | Χ | 45 |
| Non Standard Code | Brown | Orange | Violet | Grey |
| | 1 | 3 | 7 | 8 |

| Performance | Test | Test method | Test requirement | |
|----------------|-----------------------|--------------------------------|-------------------------|------------|
| | Heat ageing: | ISO188 (168 h at 150°C) | Ultimate elongation | 150% (min) |
| | Corrosion resistance: | ASTM D2671 (16 at 175°C) | No corrosion of mirrors | |
| | | Test fluids: | Petrol (100 octane) | |
| | | | Lubricating oil (0.148) | |
| | | | Hydraulic fluid (H515) | |
| Specifications | | Raychem Specification RW 2059. | | |
| | | Material Safety Data Sheet | available on request. | |

Installation instructions available on request.

Tyco and Raychem are trademarks. Other products, logos, company names mentioned herein may be trademarks of other respective owners.

All of the above material, including illustrations, is believed to be reliable, Users, however should independently evaluate the suitability of each product for their application. Tyco Electronics makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Electronics only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental indirect or consequential damages arising from the sale, resale, use or misuse of the product. Tyco Electronics Specifications are subject to change without notice. In addition Tyco Electronics reserves the right to make changes in materials or processing without notification to the Buyer, which do not affect compliance with any applicable specification.

61

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Identification category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

CU6337-000 CU6342-000 FCA-410-12 11631010 1-1768037-1 1-1768037-2 1-1768050-0 PXLK-VI Q62184-1 A64304-000 QMT221 HK032WE1NF038B 1330-0519-10 1395199-1 1395200-1 1395202-1 DMVF050WE-300S6 D-SCE-1K-2.4-50-4-CS7834 1538738-1 E90935-000 EC1238-000 EC1465-000 EC1855-000 EC1859-000 EC1863-000 EC5415-000 EC7277-000 EC7352-000 EC7603-000 EC7707-000 EC7735-000 EC7768-000 EC7828-000 EC7854-000 EC7952-000 EC8128-000 1768037-8 1768041-7 NC-127191-10-9 HS048WE2NF038B C03232-000 HTCM-SCE-14-4H-9 HTMS-3/16-9 HT-SCE-1/4-2.0-4 HT-SCE-3/16-2.0-4 HTTMS-1/2-1.50-9 HTTMS-CM-1/2-4H-9 HX-SCE-19.0-50-9 HX-SCE-6.4-50-4 C25254-000