

CGAT

Adhesive-Lined, Flexible, **Polyolefin Heat-Shrinkable** Tubing

Product Facts

- 3:1 Shrink ratio
- High-strength bonding
- Moisture-proof
- Environmental sealing
- RoHS compliant



Applications

CGAT is a flexible polyolefin heat-shrinkable tubing with an inner meltable adhesive lining designed for the commercial marketplace. It is suitable for the environmental protection of electrical components and the sealing of conductors. Typical applications are environmental sealing for electrical components, wire breakouts and cable jackets.

Installation

Minimum shrink temperature: 80°C [176°F] Minimum full recovery temperature: 115°C [239°F]

Operating Temperature Range


1-7

-30°C to 80°C [-22°F to 176°F]

Specifications/Approvals

Series		Raychem
CGAT	E85381 600V, 80°C	RW-2050

*Black only. Clear product is not flame-retardant



te.com



CGAT (Continued)

Product Dimensions

	Inside D	Diameter	Recovered Wall Thickness*	
Size	Minimum Expanded	Maximum Recovered	After Heating	After Heating
	as Supplied	After Heating	Black	Clear
3/1	3.0 [0.118]	1.0 [0.039]	1.00±0.25 [0.039±.010]	1.00±0.30 [0.039±.012]
6/2	6.0 [0.236]	2.0 [0.079]	1.00±0.25 [0.039±.010]	1.00±0.30 [0.039±.012]
9/3	9.0 [0.354]	3.0 [0.118]	1.35±0.25 [0.053±.010]	1.40±0.30 [0.055±.012]
12/4	12.0 [0.472]	4.0 [0.157]	1.50±0.25 [0.059±.010]	1.75±0.40 [0.039±.012]
18/6	18.0 [0.709]	6.0 [0.236]	1.70±0.25 [0.067±.010]	2.25±0.55 [0.089±.022]
24/8	24.0 [0.945]	8.0 [0.315]	1.90±0.25 [0.075±.010]	2.55±0.55 [0.100±.022]
39/13	39.0 [1.535]	13.0 [0.512]	2.10±0.25 [0.083±.010]	2.55±0.55 [0.100±.022]

*Wall thickness will be less if tubing recovery is restricted during shrinkage.

Ordering Information

-

Color	Standard	Black (-0) Clear (X, non-flame-retardant jacket)	
Size selection	Always order the largest size that will shrink snugly over the component to be covered.		
Standard packaging**	In 1.2 meter (4 foot) lengths or on spools.		
Ordering description	Specify product name, size and color (for example, CGAT-3/1-0).		

**Available in the convenient RaySpool packaging/dispensing system, for sizes 3/1 to 24/8.

1-8

9-1773447-9 CIS WR 08/2011 Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents. Dimensions are shown for reference purposes only. Specifications subject to change. USA: 1-800-522-6752 Canada: 1-905-475-6222 Mexico: 52-55-1106-0800 L. & S. America: 54-11-4733-2200 Germany: 49-6251-133-1999 China: 86-400-820-6015 Japan: 81-44-844-8013 UK: 44-800-267-666

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Shrink Tubing and Sleeves category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below :

 770-006S102
 5685710001
 CR8248-000
 CR9960-000
 603312-4
 607381P039
 611112-000
 617867N001
 6500750004
 CZ1420-000
 D-306-38

 770-007A303
 770-010Y106W1
 770-010Y706W1
 7771210001
 MFP-1/4"-Clear
 MFP-3/64"-Clear
 790-3012
 MFT-MT2000-NO.14-0-SP

 MHHT-4-15K2-G-104
 MIL-LT-1-1/2-4-SP
 MIL-LT-1-1/2-9-STK
 MIL-LT-1/2-2-STK
 MIL-LT-3/0-SP
 MIL-LT-3/32-0-SP
 MIL-LT-3/32-0-SP

 SP
 MIL-LT-3/4-6-SP
 MIL-LT-3/8-0-SP
 8159270001
 839602-000
 8423-6
 FP301-116-6"-Black
 FP301-1/2-48"-Black
 FP301-12-48"-Black-Hdr

 Hdr
 FP301-1/4-48"-Black
 FP301-1/4-48"-White-Hdr
 FP301-1-6"-Clear
 FP301-18-48"-Black-Hdr
 FP301-1/8-6"-Black
 FP301-18-6"-Black-Hdr

 Bulk
 FP301-316-48"-Blue-Hdr
 FP301-316-6"-Clear
 FP301-332-6"-Black
 912229N002
 120-126-16BL
 121-001-09
 121-018-32
 121-018-40

 121-123-1-1-32BTC
 121-123-1-1-40BTC
 I21-123-1-1-40BTC
 I20-126-16BL
 121-001-09
 121-018-32
 121-018-40