Pro-Power-SIL4

Silicon Coated Glass Braid Insulation sleeving. Class H (180°C) 4.0kV grade

Applications

Suitable for high temperature rated electrical equipment and appliances, for use as primary insulation or as secondary reinforcing. Also offers protection for conductors in high heat applications and in areas of likely mechanical damage.

Supplied in 5 metre coils.

Ordering Information

| PART Number | INSIDE DIAMETER (min) | WALL THICKNESS Typically (mm) |
|-----------------------|--------------------------|----------------------------------|
| Pro-Power-SIL4-2.00-0 | 2.0 | 0.80 |
| Pro-Power-SIL4-4.00-0 | 4.0 | 0.80 |
| Pro-Power-SIL4-6.00-0 | 6.0 | 0.80 |
| Pro-Power-SIL4-8.00-0 | 8.0 | 0.80 |

Colour

Black

Properties

| Thermal Classification | Class H (180°C) |
|--------------------------------|--|
| Construction | Silicon Coated Glass Braid |
| Maximum Short term Temperature | 250°C |
| Electric Strength @ 20°C | Tested to IEC 684-2 4.0kV/1 min ASTM D350 7000V |
| Flammability | Self Extinguishing |

This product is Compliant with ROHS 2002/95/EC the Restriction of use of certain Hazardous Substances in electrical and electronic equipment.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wire Identification category:

Click to view products by Pro Power manufacturer:

Other Similar products are found below :

 CU6337-000
 CU6342-000
 FCA-410-12
 11631010
 1-1768037-1
 1-1768037-2
 1-1768050-0
 PXLK-VI
 Q62184-1
 A64304-000
 QMT221

 HK032WE1NF038B
 1330-0519-10
 1395199-1
 1395200-1
 1395202-1
 DMVF050WE-30086
 D-SCE-1K-2.4-50-4-CS7834
 1538738-1

 E90935-000
 EC1238-000
 EC1465-000
 EC1855-000
 EC1859-000
 EC1863-000
 EC5415-000
 EC7352-000
 EC7603-000

 EC7707-000
 EC7735-000
 EC77828-000
 EC7854-000
 EC7952-000
 EC8128-000
 1768037-8
 1768041-7
 NC-127191-10-9

 HS048WE2NF038B
 C03232-000
 HTCM-SCE-14-4H-9
 HTMS-3/16-9
 HT-SCE-1/4-2.0-4
 HT-SCE-3/16-2.0-4
 HTTMS-1/2-1.50-9
 HTTMS

 CM-1/2-4H-9
 HX-SCE-19.0-50-9
 HX-SCE-6.4-50-4
 C25254-000
 EC7275-000
 EC73/16-2.0-4
 HTTMS-1/2-1.50-9
 HTTMS